

Product Information

Product description

Operational Sector :	Special rain-proof high-coloured white dispersion paint of good adhesion for line or different other marking on lawn (for example football stadium, tennis-court a.s.o.). Available in 25 kg tin for marking by rolling.
Features :	<ul style="list-style-type: none">- free of solvents and low in odour- water thinnable- rain-proof- high white and excellent opacity- proper adhesion- fast dry- compatibility with plant species and neutral to ground waters- does not affect the growing of the lawn
Content :	dispersion, titan dioxide, marble, chalk, talc, silicate fillers, water, additives, preservative.
Colour :	white, red
Specification :	Gloss: mat DIN 67 530 Spec. weight: approx. 1.50 g/cm ³ DIN 51 757 Viscosity: approx. 100 dPas DIN 53 019
Storage :	At least 2 years, if the tightly closed original packages are kept dry, protected against frost. Storage temperature: from +5°C till maximum +30°C.

Application

Processing conditions :	Do not apply bellow + 5 °C support or environment temperature.
Substrate preparation :	should be directly applied on the lawn.
Direction for use :	Stir well before use. Apply slowly and equal with all usual manual marking devices. Mipa Rasenmarkierungsfarbe for application by rolling may be diluted with water.
Application process :	Rolling with appropriate marking device.
Dilution :	Water

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

Product Information

Drying times : At 20° C and 65% relative air humidity:
dry to touch : after approx. 2 hours.
Prolonged drying time by lower temperatures.

Spreading ratio : Depending on the application method:
Approx. 5 - 10 g / liniar meter bei 10 cm line width.

Safety instructions

Mipa Rasenmarkierungsfarbe for rolling is slightly alkaline. Protect eyes and sensitive skin against colour. Wash away paint splashes immediately with sufficient clear water. Consider general hygienic rules. Keep out of reach for children.

Cleaning of tools

Tools should be cleaned immediately after use with water. Remove immediately the colour stains with water. Dried films should be removed with Mipa Abbeitzmittel (paint remover).

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.