

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.02.2023

Version number 7 (replaces version 6)

Revision: 28.02.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Mipa A 40 1K-Acrylspachtel**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Knife filler/ Surfacer
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
MIPA SE  
Am Oberen Moos 1  
D-84051 Essenbach  
Tel.: +49(0)8703-922-0  
Fax.: +49(0)8703-922-100  
e-mail: sdb-registratur@mipa-paints.com  
www.mipa-paints.com
- **1.4 Emergency telephone number:** International emergency number: +49(0)700 24112112 (MIP)

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning
- **Hazard-determining components of labelling:**  
n-Butyl acetate
- **Hazard statements**  
H226 Flammable liquid and vapour.  
H336 May cause drowsiness or dizziness.
- **Precautionary statements**  
P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read carefully and follow all instructions.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

(Contd. on page 2)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 28.02.2023

Version number 7 (replaces version 6)

Revision: 28.02.2023

**Trade name: Mipa A 40 1K-Acrylspachtel**

(Contd. of page 1)

- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains methyl methacrylate. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**2.3 Other hazards**
**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

**SECTION 3: Composition/information on ingredients**
**3.2 Mixtures**

Description: Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	10-25%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<5%
CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥0.1-<1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**
**4.1 Description of first aid measures**

General information: Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately rinse with water.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If symptoms persist consult doctor.

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures**
**5.1 Extinguishing media**
**Suitable extinguishing agents:**

 CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 3)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.02.2023

Version number 7 (replaces version 6)

Revision: 28.02.2023

**Trade name: Mipa A 40 1K-Acrylspachtel**

(Contd. of page 2)

- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Use only in well ventilated areas.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

#### 123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

#### 1330-20-7 Xylene

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 220 mg/m<sup>3</sup>, 50 ppm  
Sk; BMGV

#### 80-62-6 methyl methacrylate

WEL Short-term value: 416 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 208 mg/m<sup>3</sup>, 50 ppm

(Contd. on page 4)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 28.02.2023

Version number 7 (replaces version 6)

Revision: 28.02.2023

**Trade name: Mipa A 40 1K-Acrylspachtel**

(Contd. of page 3)

**· Ingredients with biological limit values:**
**1330-20-7 Xylene**

BMGV	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid

**· Additional information:** The lists valid during the making were used as basis.

**· 8.2 Exposure controls**
**· Appropriate engineering controls** No further data; see item 7.

**· Individual protection measures, such as personal protective equipment**
**· General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

**· Respiratory protection:**


In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

**· Hand protection**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

**· Material of gloves**

Butyl rubber, BR

 Recommended thickness of the material:  $\geq 0.7$  mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**· Eye/face protection**


Tightly sealed goggles

**SECTION 9: Physical and chemical properties**
**· 9.1 Information on basic physical and chemical properties**
**· General Information**
**· Physical state**

Fluid

**· Colour:**

According to product specification

**· Odour:**

Characteristic

**· Odour threshold:**

Not determined.

**· Melting point/freezing point:**

Undetermined.

(Contd. on page 5)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 28.02.2023

Version number 7 (replaces version 6)

Revision: 28.02.2023

**Trade name: Mipa A 40 1K-Acrylspachtel**

(Contd. of page 4)

<ul style="list-style-type: none"> <li>· <b>Boiling point or initial boiling point and boiling range</b></li> </ul>	124-128 °C (123-86-4 n-Butyl acetate)
<ul style="list-style-type: none"> <li>· <b>Flammability</b></li> </ul>	Flammable.
<ul style="list-style-type: none"> <li>· <b>Lower and upper explosion limit</b></li> </ul>	
<ul style="list-style-type: none"> <li>· <b>Lower:</b></li> </ul>	1.2 Vol % (123-86-4 n-Butyl acetate)
<ul style="list-style-type: none"> <li>· <b>Upper:</b></li> </ul>	7.5 Vol % (123-86-4 n-Butyl acetate)
<ul style="list-style-type: none"> <li>· <b>Flash point:</b></li> </ul>	25 °C (DIN 53213)
<ul style="list-style-type: none"> <li>· <b>Ignition temperature:</b></li> </ul>	370 °C (DIN 51794)
<ul style="list-style-type: none"> <li>· <b>Decomposition temperature:</b></li> </ul>	Not determined.
<ul style="list-style-type: none"> <li>· <b>pH</b></li> </ul>	Not determined.
<ul style="list-style-type: none"> <li>· <b>Viscosity:</b></li> </ul>	
<ul style="list-style-type: none"> <li>· <b>Kinematic viscosity</b></li> </ul>	Not determined.
<ul style="list-style-type: none"> <li>· <b>Dynamic at 20 °C:</b></li> </ul>	35,000-42,500 mPas
<ul style="list-style-type: none"> <li>· <b>Solubility</b></li> </ul>	
<ul style="list-style-type: none"> <li>· <b>water:</b></li> </ul>	Not miscible or difficult to mix.
<ul style="list-style-type: none"> <li>· <b>Partition coefficient n-octanol/water (log value)</b></li> </ul>	Not determined.
<ul style="list-style-type: none"> <li>· <b>Vapour pressure at 20 °C:</b></li> </ul>	10.7 hPa (123-86-4 n-Butyl acetate)
<ul style="list-style-type: none"> <li>· <b>Density and/or relative density</b></li> </ul>	
<ul style="list-style-type: none"> <li>· <b>Density at 20 °C:</b></li> </ul>	1.444 g/cm <sup>3</sup> (DIN 53217)
<ul style="list-style-type: none"> <li>· <b>Relative density</b></li> </ul>	Not determined.
<ul style="list-style-type: none"> <li>· <b>Vapour density</b></li> </ul>	Not determined.
<ul style="list-style-type: none"> <li>· <b>9.2 Other information</b></li> </ul>	
<ul style="list-style-type: none"> <li>· <b>Appearance:</b></li> </ul>	
<ul style="list-style-type: none"> <li>· <b>Form:</b></li> </ul>	Fluid
<ul style="list-style-type: none"> <li>· <b>Important information on protection of health and environment, and on safety.</b></li> </ul>	
<ul style="list-style-type: none"> <li>· <b>Auto-ignition temperature:</b></li> </ul>	Product is not selfigniting.
<ul style="list-style-type: none"> <li>· <b>Explosive properties:</b></li> </ul>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
<ul style="list-style-type: none"> <li>· <b>Solvent content:</b></li> </ul>	
<ul style="list-style-type: none"> <li>· <b>VOC (EC)</b></li> </ul>	27.66 %
<ul style="list-style-type: none"> <li>· <b>Solids content (weight-%):</b></li> </ul>	72.3 %
<ul style="list-style-type: none"> <li>· <b>Change in condition</b></li> </ul>	
<ul style="list-style-type: none"> <li>· <b>Evaporation rate</b></li> </ul>	Not determined.
<ul style="list-style-type: none"> <li>· <b>Information with regard to physical hazard classes</b></li> </ul>	
<ul style="list-style-type: none"> <li>· <b>Explosives</b></li> </ul>	Void
<ul style="list-style-type: none"> <li>· <b>Flammable gases</b></li> </ul>	Void
<ul style="list-style-type: none"> <li>· <b>Aerosols</b></li> </ul>	Void
<ul style="list-style-type: none"> <li>· <b>Oxidising gases</b></li> </ul>	Void
<ul style="list-style-type: none"> <li>· <b>Gases under pressure</b></li> </ul>	Void
<ul style="list-style-type: none"> <li>· <b>Flammable liquids</b></li> </ul>	Flammable liquid and vapour.
<ul style="list-style-type: none"> <li>· <b>Flammable solids</b></li> </ul>	Void
<ul style="list-style-type: none"> <li>· <b>Self-reactive substances and mixtures</b></li> </ul>	Void
<ul style="list-style-type: none"> <li>· <b>Pyrophoric liquids</b></li> </ul>	Void
<ul style="list-style-type: none"> <li>· <b>Pyrophoric solids</b></li> </ul>	Void
<ul style="list-style-type: none"> <li>· <b>Self-heating substances and mixtures</b></li> </ul>	Void
<ul style="list-style-type: none"> <li>· <b>Substances and mixtures, which emit flammable gases in contact with water</b></li> </ul>	Void
<ul style="list-style-type: none"> <li>· <b>Oxidising liquids</b></li> </ul>	Void
<ul style="list-style-type: none"> <li>· <b>Oxidising solids</b></li> </ul>	Void
<ul style="list-style-type: none"> <li>· <b>Organic peroxides</b></li> </ul>	Void
<ul style="list-style-type: none"> <li>· <b>Corrosive to metals</b></li> </ul>	Void

(Contd. on page 6)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.02.2023

Version number 7 (replaces version 6)

Revision: 28.02.2023

**Trade name: Mipa A 40 1K-Acrylspachtel**

(Contd. of page 5)

· **Desensitised explosives**

Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**  
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) : slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)



**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 28.02.2023

Version number 7 (replaces version 6)



Revision: 28.02.2023

**Trade name: Mipa A 40 1K-Acrylspachtel**

(Contd. of page 6)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**

<ul style="list-style-type: none"> <li>· <b>14.1 UN number or ID number</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>	UN1866
<ul style="list-style-type: none"> <li>· <b>14.2 UN proper shipping name</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG, IATA</b></li> </ul>	UN1866 RESIN SOLUTION RESIN SOLUTION
<ul style="list-style-type: none"> <li>· <b>14.3 Transport hazard class(es)</b></li> <li>· <b>ADR</b></li> </ul>	
	
<ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	3 (F1) Flammable liquids. 3
<ul style="list-style-type: none"> <li>· <b>IMDG, IATA</b></li> </ul>	
	
<ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	3 Flammable liquids. 3
<ul style="list-style-type: none"> <li>· <b>14.4 Packing group</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>	III
<ul style="list-style-type: none"> <li>· <b>14.5 Environmental hazards:</b></li> <li>· <b>Marine pollutant:</b></li> </ul>	No
<ul style="list-style-type: none"> <li>· <b>14.6 Special precautions for user</b></li> <li>· <b>Hazard identification number (Kemler code):</b></li> <li>· <b>EMS Number:</b></li> <li>· <b>Stowage Category</b></li> </ul>	Warning: Flammable liquids. 30 F-E, S-E A
<ul style="list-style-type: none"> <li>· <b>14.7 Maritime transport in bulk according to IMO instruments</b></li> </ul>	Not applicable.
<ul style="list-style-type: none"> <li>· <b>Transport/Additional information:</b></li> </ul>	
<ul style="list-style-type: none"> <li>· <b>ADR</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Transport category</b></li> <li>· <b>Tunnel restriction code</b></li> <li>· <b>Remarks:</b></li> </ul>	5L 3 D/E ≤ 450 l: 2.2.3.1.5 ADR
<ul style="list-style-type: none"> <li>· <b>IMDG</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Remarks:</b></li> </ul>	5L ≤ 30 l: 2.2.3.5 IMDG-Code
<ul style="list-style-type: none"> <li>· <b>UN "Model Regulation":</b></li> </ul>	UN 1866 RESIN SOLUTION, 3, III

GB

(Contd. on page 8)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.02.2023

Version number 7 (replaces version 6)

Revision: 28.02.2023

**Trade name: Mipa A 40 1K-Acrylspachtel**

(Contd. of page 7)

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
  - **Directive 2012/18/EU**
  - **Named dangerous substances - ANNEX I** None of the ingredients is listed.
  - **Seveso category P5c** FLAMMABLE LIQUIDS
  - **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
  - **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
  - **National regulations:**
  - **Additional classification according to Decree on Hazardous Materials, Annex II:**
- | Class | Share in % |
|-------|------------|
| NK    | 25-50      |
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- **Classification according to Regulation (EC) No 1272/2008**
- The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
- **Abbreviations and acronyms:**
- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

(Contd. on page 9)



**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 28.02.2023

Version number 7 (replaces version 6)

Revision: 28.02.2023

**Trade name: Mipa A 40 1K-Acrylspachtel**

Asp. Tox. 1: Aspiration hazard – Category 1

· \* **Data compared to the previous version altered.**

(Contd. of page 8)