Revision: 28.02.2023



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.02.2023

Version number 67 (replaces version 66)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: Mipa Kunststoffreiniger antistatisch
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Cleaning agent/ Cleaner
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0 Fax.: +49(0)8703-922-100

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

· 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Eye Dam. 1 H318 Causes serious eye damage.



Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 28.02.2023 Version number 67 (replaces version 66) Revision: 28.02.2023

Trade name: Mipa Kunststoffreiniger antistatisch

(Contd. of page 1)

· Hazard pictograms











GHS02 GHS05 GHS0

· Signal word Danger

· Hazard-determining components of labelling:

Isobutanol

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

| Dangerous components: | | |
|----------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| CAS: 78-83-1 EINECS: 201-148-0 Reg.nr.: 01-2119484609-23 | Isobutanol ♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Skin Irrit. 2, H315; STOT SE 3, H335-H336 | 25-50% |
| EC number: 920-750-0 Reg.nr.: 01-2119473851-33 | Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225; & Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336, EUH066 | 25-50% |
| EC number: 919-857-5 Reg.nr.: 01-2119463258-33 | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336, EUH066 | 2.5-<10% |
| EC number: 939-607-9 | Quaternary ammonium compounds, C12-14 (even- numbered)-alkylethyldimethyl, ethyl sulphates Acute Tox. 3, H311; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Acute Tox. 4, H302 | ≥0.025-<0.25% |
| | | (Contd. on page 3) |



according to 1907/2006/EC, Article 31

Printing date 28.02.2023 Version number 67 (replaces version 66) Revision: 28.02.2023

Trade name: Mipa Kunststoffreiniger antistatisch

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

- · After swallowing: Seek immediate medical advice.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Alcohol resistant foam
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 28.02.2023 Version number 67 (replaces version 66) Revision: 28.02.2023

Trade name: Mipa Kunststoffreiniger antistatisch

(Contd. of page 3)

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

78-83-1 Isobutanol

WEL Short-term value: 231 mg/m³, 75 ppm Long-term value: 154 mg/m³, 50 ppm

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: \geq 0.4 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

For the mixture of chemicals the penetration time has to be at least 60 minutes (Permeation according to EN 374 Part 3: Level 3).

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 28.02.2023 Version number 67 (replaces version 66) Revision: 28.02.2023

Trade name: Mipa Kunststoffreiniger antistatisch

(Contd. of page 4)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range 108 °C (78-83-1 Isobutanol)

• Flammability Highly flammable. • Lower and upper explosion limit

Lower: 0.9 Vol % (Hydrocarbons, C7-C9, n-alkanes,

isoalkanes, cyclics)

Fully miscible.

• **Upper:** 12 Vol % (78-83-1 Isobutanol)

Flash point: -8 °C (DIN 53213, Hydrocarbons, C7-C9, n-

alkanes, isoalkanes, cyclics)

· Ignition temperature: 390 °C (DIN 51794, 78-83-1 Isobutanol)

Decomposition temperature: Not determined. Not determined.

· Viscosity:

• Kinematic viscosity at 20 °C 10-15 s (DIN 53211/4) • Dynamic: Not determined.

· Solubility

· water:

· Partition coefficient n-octanol/water (log

value) Not determined.

Vapour pressure at 20 °C: 12 hPa (78-83-1 Isobutanol)

· Density and/or relative density

• Density at 20 °C: 0.772 g/cm³ (DIN 53217)

Relative densityVapour densityNot determined.Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

• **VOC (EC)** 99.80 % • **Solids content (weight-%):** 0.2 %

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Printing date 28.02.2023 Version number 67 (replaces version 66) Revision: 28.02.2023

Trade name: Mipa Kunststoffreiniger antistatisch

(Contd. of page 5)

| | | | tion | |
|--|--|--|------|--|
| | | | | |
| | | | | |
| | | | | |
| | | | | |

· Flammable solids

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure

Void
Void
Void

· Flammable liquids Highly flammable liquid and vapour.

Void

Void

· Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void Void · Organic peroxides Corrosive to metals Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability

· Desensitised explosives

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

78-83-1 Isobutanol

Oral LD50 2,460 mg/kg (rat)
Dermal LD50 3,400 mg/kg (rabbit)

- Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye damage.
- STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.
- · Aspiration hazard May be fatal if swallowed and enters airways.
- 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.



according to 1907/2006/EC, Article 31

Printing date 28.02.2023 Version number 67 (replaces version 66) Revision: 28.02.2023

Trade name: Mipa Kunststoffreiniger antistatisch

(Contd. of page 6)

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

| · 14.1 ON number or ID number · ADR, IMDG, IATA | UN1263 |
|----------------------------------------------------|------------------------------------------------------------------------------------------------------|
| · 14.2 UN proper shipping name | |
| ADR | UN1263 PAINT RELATED MATERIAL, ENVIRONMENTALLY HAZARDOUS |
| ·IMDG | PAINT RELATED MATERIAL (Hydrocarbons, C7- C9, Quaternary ammonium compounds), MARINE POLLUTANT |
| · IATA | POLLUTANT PAINT RELATED MATERIAL |
| | |

- · 14.3 Transport hazard class(es)
- · ADR



· Class 3 (F1) Flammable liquids.

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 28.02.2023 Version number 67 (replaces version 66) Revision: 28.02.2023

Trade name: Mipa Kunststoffreiniger antistatisch

| | (Contd. of page |
|--------------------------------------------------------------|--------------------------------------------------------------------------|
| Label | 3 |
| IMDG | |
| | |
| Class | 3 Flammable liquids. |
| Label | 3 |
| IATA | |
| 3 | |
| Class Label | 3 Flammable liquids. 3 |
| 14.4 Packing group ADR, IMDG, IATA | II |
| 14.5 Environmental hazards: | Product contains environmentally hazardo substances: Hydrocarbons, C7-C9 |
| Marine pollutant: | Yes Symbol (fish and trac) |
| Special marking (ADR): | Symbol (fish and tree) Symbol (fish and tree) |
| 14.6 Special precautions for user | Warning: Flammable liquids. |
| Hazard identification number (Kemler code): | 33 |
| EMS Number: | F-E, <u>S-E</u> |
| Stowage Category | В |
| 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| Transport/Additional information: | ., |
| ADR | |
| Limited quantities (LQ) | 5L |
| Transport category | 2 |
| Tunnel restriction code | D/E |
| IMDG Limited quantities (LQ) | 5L |
| UN "Model Regulation": | UN 1263 PAINT RELATED MATERIAL, 3, ENVIRONMENTALLY HAZARDOUS |

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

(Contd. on page 9)



according to 1907/2006/EC, Article 31

Printing date 28.02.2023 Version number 67 (replaces version 66) Revision: 28.02.2023

Trade name: Mipa Kunststoffreiniger antistatisch

(Contd. of page 8)

- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

| Class | Share in % |
|-------|------------|
| NK | 50-100 |

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

| H225 | Highly flammable liquid and vapour. |
|--------------|-------------------------------------|
| ロ //3 | mioniy ilanimadie iloulo and vadour |
| | |

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 1: Nazardous to the aquatic environment - long-term aquatic hazard — Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard — Category 2

* Data compared to the previous version altered.