Revision: 01.03.2023



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.03.2023

Version number 4 (replaces version 3)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Mipa PE-Verdünnung
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Thinner, Diluent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0 Fax.: +49(0)8703-922-100

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

• 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Ethyl acetate

· Hazard statements

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 01.03.2023 Version number 4 (replaces version 3) Revision: 01.03.2023

Trade name: Mipa PE-Verdünnung

(Contd. of page 1)

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

٠	Dan	gerous	comp	onents:
---	-----	--------	------	---------

CAS: 141-78-6 Ethyl acetate 50-100%

Reg.nr.: 01-2119475103-46 H336, EUH066

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

GB



according to 1907/2006/EC, Article 31

Printing date 01.03.2023 Version number 4 (replaces version 3) Revision: 01.03.2023

Trade name: Mipa PE-Verdünnung

(Contd. of page 2)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

141-78-6 Ethyl acetate

WEL Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm

Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

(Contd. on page 4)

(Contd. of page 3)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.03.2023 Version number 4 (replaces version 3) Revision: 01.03.2023

Trade name: Mipa PE-Verdünnung

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Physical state Fluid

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range 77-78 °C

• Flammability Highly flammable.

· Lower and upper explosion limit

• **Lower:** 2.1 Vol % • **Upper:** 11.5 Vol %

• **Flash point:** -4 °C (DIN EN ISO 1523:2002)

· Ignition temperature: 460 °C (DIN 51794)
 · Decomposition temperature: Not determined.
 · pH Not determined.

Viscosity:

· Kinematic viscosity at 20 °C 12-14 s (DIN 53211/4) · Dvnamic: Not determined.

· Dynamic: Not determine · Solubility

· water: Not miscible or difficult to mix.

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 01.03.2023 Version number 4 (replaces version 3) Revision: 01.03.2023

Trade name: Mipa PE-Verdünnung

(Contd. of page 4)

· Partition coefficient n-octanol/water (log

value) Not determined.

· Vapour pressure at 20 °C: 97 hPa

· Density and/or relative density

• **Density at 20 °C:** 0.9 g/cm³ (DIN EN ISO 2811-1)

Relative densityVapour densityNot determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

• Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

· VOC (EC) 100.00 %
· Solids content (weight-%): 0.0 %

Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard

classes

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure
Void
Void

Flammable liquids Highly flammable liquid and vapour.

Flammable solids
Self-reactive substances and mixtures
Void
Pyrophoric liquids
Void
Pyrophoric solids
Void
Self-heating substances and mixtures
Void

· Substances and mixtures, which emit

flammable gases in contact with water

Oxidising liquids

Oxidising solids

Organic peroxides

Corrosive to metals

Desensitised explosives

Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Carbon monoxide



according to 1907/2006/EC, Article 31

Printing date 01.03.2023 Version number 4 (replaces version 3) Revision: 01.03.2023

Trade name: Mipa PE-Verdünnung

(Contd. of page 5)

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

141-78-6 Ethyl acetate

Oral LD50 5,620 mg/kg (rat)

- Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1263

· 14.2 UN proper shipping name

· ADR UN1263 PAINT RELATED MATERIAL

· IMDG, IATA PAINT RELATED MATERIAL

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 01.03.2023 Version number 4 (replaces version 3) Revision: 01.03.2023

Trade name: Mipa PE-Verdünnung

(Contd. of page 6) · 14.3 Transport hazard class(es) · ADR · Class 3 (F1) Flammable liquids. · Label · IMDG, IATA 3 Flammable liquids. · Class ·Label 3 · 14.4 Packing group · ADR, IMDG, IATA 11 · 14.5 Environmental hazards: Not applicable. · 14.6 Special precautions for user Warning: Flammable liquids. · Hazard identification number (Kemler code): 33 · EMS Number: F-E,S-E · Stowage Category R · 14.7 Maritime transport in bulk according to **IMO** instruments Not applicable. · Transport/Additional information: · ADR · Limited quantities (LQ) 5L · Transport category 2 · Tunnel restriction code D/E · Limited quantities (LQ) 5L · UN "Model Regulation": UN 1263 PAINT RELATED MATERIAL, 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %		
NK	50-100		

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 01.03.2023 Version number 4 (replaces version 3) Revision: 01.03.2023

Trade name: Mipa PE-Verdünnung

(Contd. of page 7)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.