

Safety data sheet

according to 1907/2006/EC, Article 31

Version number 8 (replaces version 7)

Revision: 28.02.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: Mipa V.I.P. Exclusive Basecoat
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- No further relevant information available.
- Sector of Use
- SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- **Product category** PC9a Coatings and paints, thinners, paint removers
- · Application of the substance / the mixture Paint
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: MIPA SE
 Am Oberen Moos 1
 D-84051 Essenbach
 Tel.: +49(0)8703-922-0
 Fax.: +49(0)8703-922-100
 e-mail: sdb-registratur@mipa-paints.com
 www.mipa-paints.com
 * 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation. **Hazard pictograms**



· Signal word Warning

- Hazard-determining components of labelling: n-Butyl acetate 2-Methoxy-1-methylethyl acetate Methyl ethyl ketone
- Hazard statements
 H226 Flammable liquid and vapour.
 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

GB



Safety data sheet

according to 1907/2006/EC, Article 31 Version number 8 (replaces version 7)

Revision: 28.02.2023

_

Trade name: Mipa V.I.P. Exclusive Basecoat

(Contd. of page 1)

•	· Precautionary statements					
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.				
	P261	Avoid breathing dust/fume/gas/mist/vapours/spray.				
	P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.				
	P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].				
	P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.				
	P312	Call a POISON CENTER/doctor if you feel unwell.				
•	Additional information:					
	EUH066 Repeated exposure may cause skin dryness or cracking.					
•	2.3 Other hazards					

· Results of PBT and vPvB assessment

- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Γ

· Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 123-86-4	n-Butyl acetate	50-100%
EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336, EUH066	
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; (1) STOT SE 3, H336	10-25%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<5%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43	Methyl ethyl ketone Flam. Liq. 2, H225; (1) Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	<2.5%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzene Flam. Liq. 2, H225; H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	<2.5%
CAS: 7783-40-6 EINECS: 231-995-1	magnesium fluoride	<2.5%

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• General information: Immediately remove any clothing soiled by the product.

· After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact: Immediately rinse with water.

- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

⁻ GB



Safety data sheet

according to 1907/2006/EC, Article 31

Version number 8 (replaces version 7)

Revision: 28.02.2023

Trade name: Mipa V.I.P. Exclusive Basecoat

(Contd. of page 2)

 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- · Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm

Long-term value: 724 mg/m³, 150 ppm

(Contd. on page 4)



according to 1907/2006/EC, Article 31 Version number 8 (replaces version 7)

Revision: 28.02.2023

Printing date 28.02.2023

Trade name: Mipa V.I.P. Exclusive Basecoat

108-65-6 2-Methoxy-1-methylethyl acetate	(Contd. of page
WEL Short-term value: 548 mg/m ³ , 100 ppm	
Long-term value: 274 mg/m³, 50 ppm Sk	
-	
1330-20-7 Xylene	
WEL Short-term value: 441 mg/m³, 100 ppm	
Long-term value: 220 mg/m³, 50 ppm	
Sk; BMGV	
78-93-3 Methyl ethyl ketone	
WEL Short-term value: 899 mg/m³, 300 ppm	
Long-term value: 600 mg/m³, 200 ppm	
Sk, BMGV	
100-41-4 Ethylbenzene	
WEL Short-term value: 552 mg/m³, 125 ppm	
Long-term value: 441 mg/m ³ , 100 ppm	
Sk	
Ingredients with biological limit values:	
1330-20-7 Xylene	
BMGV 650 mmol/mol creatinine	
Medium: urine	
Sampling time: post shift	
Parameter: methyl hippuric acid	
78-93-3 Methyl ethyl ketone	
BMGV 70 µmol/L	
Medium: urine	
Sampling time: post shift	
Parameter: butan-2-one	
Additional information: The lists valid during the making were us	sed as basis.
8.2 Exposure controls	

- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- · Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

GB



according to 1907/2006/EC, Article 31

Revision: 28.02.2023

Printing date 28.02.2023 Version number 8 (replaces version 7)

Trade name: Mipa V.I.P. Exclusive Basecoat

(Contd. of page 4)

· Breakthrough time of glove material

- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

 9.1 Information on basic physical and chemical properties 		
General Information		
· Physical state	Fluid	
· Colour:	According to product specification	
· Odour:	Characteristic	
Odour threshold:	Not determined.	
• Melting point/freezing point:	Undetermined.	
· Boiling point or initial boiling point and		
boiling range	124-128 °C (123-86-4 n-Butyl acetate)	
· Flammability	Flammable.	
· Lower and upper explosion limit		
· Lower:	1 Vol % (Polyester resin, hydroxy functional)	
	10.8 Vol % (108-65-6 2-Methoxy-1-methylethyl	
· Upper:	acetate)	
- Flach nainti		
· Flash point:	27 °C (DIN EN ISO 1523:2002, 123-86-4 n-Butyl	
louritie a terrere eveture -		
· Ignition temperature:	315 °C (DIN 51794, 108-65-6 2-Methoxy-1-	
	methylethyl acetate)	
Decomposition temperature:	Not determined.	
рН	Not determined.	
· Viscosity:		
Kinematic viscosity at 20 °C	>60 s (ISO 6 mm)	
· Dynamic:	Not determined.	
· Solubility		
· water:	Not miscible or difficult to mix.	
 Partition coefficient n-octanol/water (log 		
value)	Not determined.	
· Vapour pressure at 20 °C:	10.7 hPa (123-86-4 n-Butyl acetate)	
Density and/or relative density		
· Density at 20 °C:	0.946 g/cm ³ (DIN EN ISO 2811-1)	
· Relative density	Not determined.	
Vapour density	Not determined.	
9.2 Other information		
· Appearance:		
Form:	Fluid	
Important information on protection of health		
and environment, and on safety.		
 Auto-ignition temperature: 	Product is not selfigniting.	
• Explosive properties:	Product is not explosive. However, formation of	
	explosive air/vapour mixtures are possible.	
· Solvent content:		
· VOC (EC)	73.96 %	
Solids content (weight-%):	26.0 %	
,	(Contd. on page 6)	
	(Conta. on page 6)	



according to 1907/2006/EC, Article 31 Version number 8 (replaces version 7)

Revision: 28.02.2023

Printing date 28.02.2023

Trade name: Mipa V.I.P. Exclusive Basecoat

		(Contd. of page
Change in condition		
Evaporation rate	Not determined.	
Information with regard to physical haz	ard	
classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Flammable liquid and vapour.	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008** • **Acute toxicity** Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

123-86-4 n-Butyl acetate

- Oral LD50 13,100 mg/kg (rat)
- Dermal LD50 >5,000 mg/kg (rabbit)
- STOT-single exposure May cause drowsiness or dizziness.
- 11.2 Information on other hazards
- Endocrine disrupting properties
- 78-93-3 Methyl ethyl ketone

List II

(Contd. on page 7)



Safety data sheet

according to 1907/2006/EC, Article 31

Version number 8 (replaces version 7)

Revision: 28.02.2023

Trade name: Mipa V.I.P. Exclusive Basecoat

(Contd. of page 6)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

- **12.2 Persistence and degradability** No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Endocrine disrupting properties
- For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.


SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.





according to 1907/2006/EC, Article 31

Revision: 28.02.2023

Printing date 28.02.2023

Version number 8 (replaces version 7)

	(Contd. of page
Label	3
• 14.4 Packing group • ADR, IMDG, IATA	<i>III</i>
· 14.5 Environmental hazards: · Marine pollutant:	No
• 14.6 Special precautions for user • Hazard identification number (Kemler code • EMS Number: • Stowage Category	Warning: Flammable liquids. e): 30 F-E, <u>S-E</u> A
[•] 14.7 Maritime transport in bulk according t IMO instruments	o Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Transport category Tunnel restriction code Remarks:	5L 3 D/E ≤ 450 I: -
· IMDG · Limited quantities (LQ) · Remarks:	5L ≤ 30 l: -
UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

National regulations:

· Additional classification according to Decree on Hazardous Materials, Annex II:

)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

[.] Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.

(Contd. on page 9)

GB



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.02.2023

Version number 8 (replaces version 7)

Revision: 28.02.2023

Trade name: Mipa V.I.P. Exclusive Basecoat

		(Contd. of page 8)
H319	Causes serious eye irritation.	(1 0)
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H412	Harmful to aquatic life with long lasting effects.	
EUHO	66 Repeated exposure may cause skin dryness or cracking.	
	fication according to Regulation (EC) No 1272/2008	
	assification of the mixture is generally based on the calculation method usin	a substance data
	ling to Regulation (EC) No 1272/2008.	g oubolance dala
	viations and acronyms:	
	ccord relatif au transport international des marchandises dangereuses par route (European Ag	areement Concerning
	national Carriage of Dangerous Goods by Road)	Joennen concerning
IMDG: II	nternational Maritime Code for Dangerous Goods	
	ternational Air Transport Association	
	obally Harmonised System of Classification and Labelling of Chemicals	
	: European Inventory of Existing Commercial Chemical Substances : European List of Notified Chemical Substances	
	nemical Abstracts Service (division of the American Chemical Society)	
	platile Organic Compounds (USA, EU)	
	ethal concentration, 50 percent	
	ethal dose, 50 percent	
	rsistent, Bioaccumulative and Toxic	
	ery Persistent and very Bioaccumulative g. 2: Flammable liguids – Category 2	
	g. 2: Flammable liquids – Category 2 g. 3: Flammable liquids – Category 3	
	px. 4: Acute toxicity – Category 4	
	. 2: Skin corrosion/irritation – Category 2	
	2: Serious eye damage/eye irritation – Category 2	
	E 3: Specific target organ toxicity (single exposure) – Category 3	
	E 2: Specific target organ toxicity (repeated exposure) – Category 2	
	x. 1: Aspiration hazard – Category 1 Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	
	compared to the previous version altered.	
Dala		GB