Revision: 03.02.2023



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.02.2023

Version number 9 (replaces version 8)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Mipa Vicrom "mirror glaze"
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- Product category PC9a Coatings and paints, thinners, paint removers
- · Application of the substance / the mixture Paint
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0 Fax.: +49(0)8703-922-100

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

• 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS02 GHS07

7 GHS08

· Signal word Danger

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 03.02.2023 Version number 9 (replaces version 8) Revision: 03.02.2023

Trade name: Mipa Vicrom "mirror glaze"

(Contd. of page 1)

· Hazard-determining components of labelling:

Xvlene

n-Butyl acetate Ethylbenzene

2-Methoxy-1-methylethyl acetate

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation. H319 Causes serious eye irritation.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

CAS: 123-86-4	n-Butyl acetate	25-50%
EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336, EUH066	
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate ♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	25-50%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene ♠ Flam. Liq. 3, H226; ♠ STOT RE 2, H373; Asp. Tox. 1, H304; ♠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-25%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43	Methyl ethyl ketone ♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-25%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	2.5-<10%



according to 1907/2006/EC, Article 31

Printing date 03.02.2023 Version number 9 (replaces version 8) Revision: 03.02.2023

Trade name: Mipa Vicrom "mirror glaze"

	(C	ontd. of page 2)
CAS: 108-21-4	isopropyl acetate	<2.5%
EINECS: 203-561-1	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	_
CAS: 141-78-6	Ethyl acetate	<2.5%
EINECS: 205-500-4	♠ Flam. Lig. 2, H225; ♠ Eye Irrit. 2, H319; STOT SE 3,	_
Reg.nr.: 01-2119475103-46	H336, EUH066	
. Additional information: Ec	or the wording of the listed hazard phrases refer to section 1	6

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Seek immediate medical advice.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 03.02.2023 Version number 9 (replaces version 8) Revision: 03.02.2023

Trade name: Mipa Vicrom "mirror glaze"

(Contd. of page 3)

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

Sampling time: post shift Parameter: methyl hippuric acid

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

S	Ε	C	T_{l})	V	8	\mathbf{H}	Eχ	00	su	re	CC	on	trc)ls	/p	ei	S	on	al	pr	01	tec	ti	01	1
---	---	---	---------	--	---	---	---	--------------	----	----	----	----	----	----	-----	-----	----	----	---	----	----	----	----	-----	----	----	---

8.1	Control	parameters	;
-----	---------	------------	---

123-8	86-4 n-Butyl acetate	
	Short-term value: 966 mg/m³, 200 ppm	
-	Long-term value: 724 mg/m³, 150 ppm	
108-6	65-6 2-Methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m³, 100 ppm	
	Long-term value: 274 mg/m³, 50 ppm Sk	
1330	-20-7 Xylene	
WEL	Short-term value: 441 mg/m³, 100 ppm	
	Long-term value: 220 mg/m³, 50 ppm Sk; BMGV	
78-9 3	3-3 Methyl ethyl ketone	
WEL	Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV	
100-4	41-4 Ethylbenzene	
WEL	Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk	
108-2	21-4 isopropyl acetate	
WEL	Short-term value: 849 mg/m³, 200 ppm	
141-7	78-6 Ethyl acetate	
WEL	Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm	
Ingre	edients with biological limit values:	
	-20-7 Xylene	

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 03.02.2023 Version number 9 (replaces version 8) Revision: 03.02.2023

Trade name: Mipa Vicrom "mirror glaze"

(Contd. of page 4)

78-93-3 Methyl ethyl ketone

BMGV 70 µmol/L

Medium: urine

Sampling time: post shift Parameter: butan-2-one

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Physical state

Fluid

· Colour:

According to product specification

· Odour:

Characteristic

Odour threshold:

Not determined.

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Revision: 03.02.2023 Printing date 03.02.2023 Version number 9 (replaces version 8)

Trade name: Mipa Vicrom "mirror glaze"

(Contd. of page 5)

Melting point/freezing point:

Boiling point or initial boiling point and

boiling range 79-80.5 °C (78-93-3 Methyl ethyl ketone)

· Flammability Flammable.

· Lower and upper explosion limit

1.1 Vol % (1330-20-7 Xylene) · Lower:

10.8 Vol % (108-65-6 2-Methoxy-1-methylethyl · Upper:

Undetermined.

24 °C (DIN EN ISO 1523:2002) · Flash point:

315 °C (DIN 51794, 108-65-6 2-Methoxy-1-· Ignition temperature:

methylethyl acetate)

Not determined. · Decomposition temperature: Not determined. · pH

· Viscosity:

· Kinematic viscosity at 20 °C

10-12 s (DIN 53211/4) · Dynamic: Not determined.

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value)

Not determined. Vapour pressure at 20 °C: 105 hPa (78-93-3 Methyl ethyl ketone)

Density and/or relative density

Density at 20 °C: 0.892 g/cm3 (DIN EN ISO 2811-1)

Not determined. · Relative density Not determined. · Vapour density

· 9.2 Other information

· Appearance:

Fluid · Form:

· Important information on protection of health

and environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

· VOC (EC) 99.55 % Solids content (weight-%): 0.5 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard

classes · Explosives Void Void · Flammable gases · Aerosols Void Oxidising gases Void · Gases under pressure Void

· Flammable liquids Flammable liquid and vapour.

· Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void

· Substances and mixtures, which emit

flammable gases in contact with water Void Oxidising liquids Void

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 03.02.2023 Version number 9 (replaces version 8) Revision: 03.02.2023

Trade name: Mipa Vicrom "mirror glaze"

(Contd. of page 6)

Void
Void
Void
Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.
- · STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard May be fatal if swallowed and enters airways.
- 11.2 Information on other hazards

· Endocrine disrupting properties

78-93-3 Methyl ethyl ketone

List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

GB



according to 1907/2006/EC, Article 31

Printing date 03.02.2023 Version number 9 (replaces version 8) Revision: 03.02.2023

Trade name: Mipa Vicrom "mirror glaze"

(Contd. of page 7)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number		
ADR, IMDG, IATA	UN1263	
14.2 UN proper shipping name ADR IMDG, IATA	UN1263 PAINT PAINT	
14.3 Transport hazard class(es)		
ADR		
Class	3 (F1) Flammable liquids.	
Label	3	
IMDG, IATA		
Class Label	<i>3 Flammable liquids.</i> <i>3</i>	
14.4 Packing group ADR, IMDG, IATA	III	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Warning: Flammable liquids.	
Hazard identification number (Kemler code, EMS Number:): 30 F-E,S-E	
Stowage Category	A A	
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.	
Transport/Additional information:		
ADR Limited quantities (LQ)	5L	
Transport category Tunnel restriction code	3 D/E	



according to 1907/2006/EC, Article 31

Printing date 03.02.2023 Version number 9 (replaces version 8) Revision: 03.02.2023

Trade name: Mipa Vicrom "mirror glaze"

(Contd. of page 8)
 IMDG
 Limited quantities (LQ)
 UN "Model Regulation":
 UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	50-100

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4

(Contd. on page 10)





Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.02.2023 Version number 9 (replaces version 8) Revision: 03.02.2023

Trade name: Mipa Vicrom "mirror glaze"

(Contd. of page 9)

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.