

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 40 (replaces version 39)

Revision: 01.02.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking · 1.1 Product identifier · Trade name: Mipa PU 250-30 2K-PU-Lack 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Paint · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: MIPA SE Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0 Fax.: +49(0)8703-922-100

e-mail: sdb-registratur@mipa-paints.com www.mipa-paints.com

• 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3

H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



· Signal word Warning

· Hazard-determining components of labelling: n-Butyl acetate 2-Methoxy-1-methylethyl acetate Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics Hydrocarbons, C9, aromatics Hazard statements H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

GB



Safety data sheet

according to 1907/2006/EC, Article 31

Version number 40 (replaces version 39) Revision

Revision: 01.02.2023

Trade name: Mipa PU 250-30 2K-PU-Lack

(Contd. of page 1)

 Precautionary s 	tatements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P35	3 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
· 2.3 Other hazard	ds
· Results of PBT	and vPvB assessment
• PBT: Not applica	ble.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

CAS: 123-86-4	n-Butyl acetate	<15%
EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336, EUH066	
CAS: 108-65-6	2-Methoxy-1-methylethyl acetate	2.5-<10%
EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	🚸 Flam. Liq. 3, H226; 🔶 STOT SE 3, H336	
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	<i>Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics</i>	2.5-<10%
	🚸 Flam. Liq. 3, H226; 🚸 Asp. Tox. 1, H304; 🚸 STOT SE 3, H336, EUH066	
CAS: 112-07-2	2-Butoxyethyl acetate	2.5-<5%
EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332 	
CAS: 64742-95-6	Hydrocarbons, C9, aromatics	1-<2.5%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	 ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H335- H336, EUH066 	
EC number: 915-687-0	Reaction mass of pentamethyl-piperidyl sebacate	<i>≥</i> 0.1-<0.25%
Reg.nr.: 01-2119491304-40	Repr. 2, H361f; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Aquatic Skin Sens. 1A, H317	

SECTION 4: First aid measures

• 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

- · After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.

• After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

GB



Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 01.02.2023

(Contd. of page 2)

Printing date 23.03.2023

Version number 40 (replaces version 39)

Trade name: Mipa PU 250-30 2K-PU-Lack

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet • 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- [•] 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Use only in well ventilated areas. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)

GB



Safety data sheet

according to 1907/2006/EC, Article 31 Version number 40 (replaces version 39)

Revision: 01.02.2023

Trade name: Mipa PU 250-30 2K-PU-Lack

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

108-65-6 2-Methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

112-07-2 2-Butoxyethyl acetate

WEL Short-term value: 332 mg/m³, 50 ppm Long-term value: 133 mg/m³, 20 ppm Sk

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.
- Respiratory protection:
- Not required.



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

GB



Safety data sheet according to 1907/2006/EC, Article 31

Version number 40 (replaces version 39)

Revision: 01.02.2023

(Contd. of page 4)

Trade name: Mipa PU 250-30 2K-PU-Lack

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and cher	mical properties
· General Information	
· Physical state	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and	ondetermined.
boiling range	124-128 °C (123-86-4 n-Butyl acetate)
·Flammability	Flammable.
· Lower and upper explosion limit	Traninable.
· Lower:	1.2 Vol % (123-86-4 n-Butyl acetate)
· Upper:	7.5 Vol % (123-86-4 n-Butyl acetate)
· Flash point:	30 °C (DIN 53213)
· Auto-ignition temperature:	315 °C (DIN 51794, 108-65-6 2-Methoxy-1-
Autorginuon temperature.	methylethyl acetate)
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	Not determined.
· Kinematic viscosity at 20 °C	200-220 s (ISO 6 mm)
Dynamic:	Not determined.
· Solubility	Not determined.
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log	
	Not determined.
value) · Vapour pressure at 20 °C:	<15 hPa (Hydroxy acrylic resin)
• Density and/or relative density	
· Density at 20 °C:	1.415 g/cm³ (DIN 53217)
· Relative density	Not determined.
· Vapour density	Not determined.
	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Fluid
 Important information on protection of heat 	alth
and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
· Solvent content:	
· VOC (EC)	26.07 %
Solids content (weight-%):	73.9 %
Change in condition	
· Evaporation rate	Not determined.
	(Contd. on page 6
	(Conta: on page of

GB



Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 01.02.2023

Printing date 23.03.2023

Version number 40 (replaces version 39)

Trade name: Mipa PU 250-30 2K-PU-Lack

		(Contd. of page
Information with regard to physical haz	ard	
classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Flammable liquid and vapour.	
Flammable solids	Void .	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

• **10.4 Conditions to avoid** No further relevant information available.

- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- STOT-single exposure May cause drowsiness or dizziness.

11.2 Information on other hazards

· Endocrin	e disrupting properties
540-97-6	Dodecamethylcyclohexasiloxane
511-02-6	Decamethylovclopentasilovane

541-02-6 Decamethylcyclopentasiloxane

556-67-2 octamethylcyclotetrasiloxane

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

(Contd. on page 7)

List II List II

List II, III

GB



Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 01.02.2023

Printing date 23.03.2023 Version number 40 (replaces version 39)

Trade name: Mipa PU 250-30 2K-PU-Lack

(Contd. of page 6)

12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR IMDG, IATA	UN1263 PAINT PAINT
14.3 Transport hazard class(es)	
ADR	
Class Label	3 (F1) Flammable liquids. 3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	<i>III</i>
14.5 Environmental hazards: Marine pollutant:	No



Safety data sheet

according to 1907/2006/EC, Article 31 Version number 40 (replaces version 39)

Revision: 01.02.2023

Trade name: Mipa PU 250-30 2K-PU-Lack

	(Contd. of page
· 14.6 Special precautions for user	Warning: Flammable liquids.
 Hazard identification number (Kemler cod 	
· EMS Number:	F-E, <u>S-E</u>
· Stowage Category	A
· 14.7 Maritime transport in bulk according	to
IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Transport category	3
· Tunnel restriction code	D/E
· Remarks:	<i>≤</i> 450 <i>I</i> : -
·IMDG	
· Limited quantities (LQ)	5L
Remarks:	<i>≤</i> 30 <i>l</i> : -
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations:

· Additional classification according to Decree on Hazardous Materials, Annex II:

Class Share in % NK 25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

Harmful in contact with skin. H312

May cause an allergic skin reaction. H317

- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

- H361f Suspected of damaging fertility.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 9)

GB



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.03.2023

Version number 40 (replaces version 39)

Revision: 01.02.2023

Trade name: Mipa PU 250-30 2K-PU-Lack

(Contd. of page 8)	
EUH066 Repeated exposure may cause skin dryness or cracking.	
Classification according to Regulation (EC) No 1272/2008	
The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.	
Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)	
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organisation	
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)	
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	I
CAS: Chemical Abstracts Service (division of the American Chemical Society)	I
VOC: Volatile Organic Compounds (USA, EU)	
PBT: Persistent, Bioaccumulative and Toxic	I
vPvB: very Persistent and very Bioaccumulative	I
Flam. Liq. 3: Flammable liquids – Category 3	I
Acute Tox. 4: Acute toxicity – Category 4	I
Skin Sens. 1: Skin sensitisation – Čategory 1	I
Skin Sens. 1A: Skin sensitisation – Category 1A	I
Repr. 2: Reproductive toxicity – Category 2	I
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	I
Asp. Tox. 1: Aspiration hazard – Category 1	I
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1	I
Aguatic Chronic 1: Hazardous to the aguatic environment - long-term aguatic hazard – Category 1	I
Aguatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2	I
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	I
* Data compared to the previous version altered.	
	J