Revision: 07.05.2025



Safety data sheet

according to UK REACH

Printing date 07.05.2025

Version number 41 (replaces version 40)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Mipasan Silikonharzfarbe FE
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Paint
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49 8703 92 20 Fax.: +49 8703 92 21 00

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

· 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



- Signal word Warning
- · Hazard-determining components of labelling:

2-octyl-2H-isothiazol-3-one 2-methyl-2H-isothiazol-3-one

C(M)IT/MIT (3:1)

1,2-Benzisothiazol-3(2H)-one

· Hazard statements

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

(Contd. on page 2)



according to UK REACH

Printing date 07.05.2025 Version number 41 (replaces version 40) Revision: 07.05.2025

Trade name: Mipasan Silikonharzfarbe FE

(Contd. of page 1)

P321 Specific treatment (see on this label).

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 1336-21-6 EINECS: 215-647-6	ammonia 20 % Skin Corr. 1B, H314; ♦ Aquatic Acute 1, H400; Aquatic Chronic 2, H411; ↑ STOT SE 3, H335 Specific concentration limit: STOT SE 3; H335: C≥ 5 %	<0.25%
CAS: 26530-20-1 EINECS: 247-761-7	2-octyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 ATE: LD50 oral: 125 mg/kg LD50 dermal: 311 mg/kg LC50/4 h inhalative: 0.27 mg/l Specific concentration limit: Skin Sens. 1A; H317:C ≥ 0.0015 %	≥0.0025-<0.025%
CAS: 2682-20-4 EINECS: 220-239-6	2-methyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317:C ≥ 0.0015 %	≥0.0015-<0.025%
CAS: 2634-33-5 EINECS: 220-120-9 Reg.nr.: 01-2120761540-60	1,2-Benzisothiazol-3(2H)-one Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ↑ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C≥ 0.05 %	<0.025%

onta. on page 3



according to UK REACH

Printing date 07.05.2025 Version number 41 (replaces version 40) Revision: 07.05.2025

Trade name: Mipasan Silikonharzfarbe FE

			_
		(Contd. of page 2)	
CAS: 886-50-0	terbutryn	≥0.0025-<0.025%	
EINECS: 212-950-5	Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Acute Tox. 4, H302; Skin Sens. 1B, H317		
CAS: 55965-84-9	C(M)IT/MIT (3:1)	<0.0015%	
Reg.nr.: 01-2120764691-48	Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 Specific concentration limits: Skin Corr. 1C; H314:C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %		

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system. Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)



according to UK REACH

Printing date 07.05.2025 Version number 41 (replaces version 40) Revision: 07.05.2025

Trade name: Mipasan Silikonharzfarbe FE

(Contd. of page 3)

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Protect from frost.
- · Storage class: 12
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)



according to UK REACH

Printing date 07.05.2025 Version number 41 (replaces version 40) Revision: 07.05.2025

Trade name: Mipasan Silikonharzfarbe FE

· Eye/face protection Goggles recommended during refilling

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Liquid

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and

boiling range 100 °C (7732-18-5 water, distilled, conductivity or

of similar purity)

· Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: Not applicable.
Decomposition temperature: Not determined.

pH at 20 °C 8.4-9

· Viscosity:

Kinematic viscosityDynamic at 20 °C:Not determined.9,300 mPas

·Solubility

· water: Fully miscible.

· Partition coefficient n-octanol/water (log

value) Not determined.

· Vapour pressure at 20 °C: 23 hPa (7732-18-5 water, distilled, conductivity or

of similar purity)

Density and/or relative density

Density at 20 °C: 1.307 g/cm³ (DIN 53217)

Relative densityVapour densityNot determined.Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

Ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Solvent content:

• VOC (EC) 1.56 %
• Solids content (weight-%): 60.2 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard

classes

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure
Flammable liquids
Void
Void

(Contd. on page 6)



according to UK REACH

Printing date 07.05.2025 Version number 41 (replaces version 40) Revision: 07.05.2025

Trade name: Mipasan Silikonharzfarbe FE

		(Contd. of page 5)
· Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
· Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC5	· LD/LC50 values relevant for classification:	
26530-20-1 2-octyl-2H-isothiazol-3-one		
Oral		125 mg/kg (ATE)
		125 mg/kg (rat)
Dermal	LD50	311 mg/kg (ATE)
		311 mg/kg (rat)

· Respiratory or skin sensitisation May cause an allergic skin reaction.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish

(Contd. on page 7)



according to UK REACH

Printing date 07.05.2025 Version number 41 (replaces version 40) Revision: 07.05.2025

Trade name: Mipasan Silikonharzfarbe FE

(Contd. of page 6)

· Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

14.1 UN number or ID number	
ADR, ADN, IMDG, IATA	Void
14.2 UN proper shipping name	
ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA	
Class	Void
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according	ng to
IMO instruments	Not applicable.

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable poisons

1336-21-6 ammonia 20 % 10%

(Contd. on page 8)



according to UK REACH

Revision: 07.05.2025 Printing date 07.05.2025 Version number 41 (replaces version 40)

Trade name: Mipasan Silikonharzfarbe FE

(Contd. of page 7)

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations:
- Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
1	<1
NK	<2.5

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Reievan	t pnrases
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
	H301 H302 H310 H311 H314 H315 H317 H318 H319 H330 H335 H400

Toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

Classification according to Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

(Contd. on page 9)





Safety data sheet according to UK REACH

Printing date 07.05.2025 Version number 41 (replaces version 40) Revision: 07.05.2025

Trade name: Mipasan Silikonharzfarbe FE

(Contd. of page 8)

Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A
Skin Sens. 1B: Skin sensitisation – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard — Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard — Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard — Category 3

* Data compared to the previous version altered.