Revision: 02.03.2023



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.03.2023

Version number 44 (replaces version 43)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Mipa 1K-Klarlack C 10
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Clear coating material, Varnish
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0 Fax.: +49(0)8703-922-100

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

• 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS02 GHS07 GH

- · Signal word Danger
- · Hazard-determining components of labelling: n-Butyl acetate

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 44 (replaces version 43) Revision: 02.03.2023

Trade name: Mipa 1K-Klarlack C 10

(Contd. of page 1)

Xylene

Methyl ethyl ketone

Hydrocarbons, C9, aromatics

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description**: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate This is a second of the sec	25-50%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43	Methyl ethyl ketone ♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-25%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	acetone ♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	5-<10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene ♠ Flam. Liq. 3, H226; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ↑ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 44 (replaces version 43) Revision: 02.03.2023

Trade name: Mipa 1K-Klarlack C 10

		(Contd. of page 2)
CAS: 64742-95-6	Hydrocarbons, C9, aromatics	1-<2.5%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	 ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H335-H336, EUH066 	
CAS: 100-41-4	Ethylbenzene	<2.5%
EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	♠ Flam. Liq. 2, H225; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ♠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	
EC number: 915-687-0	Reaction mass of pentamethyl-piperidyl sebacate	≥0.1-<0.25%
Reg.nr.: 01-2119491304-40	Repr. 2, H361f; ♦ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ♦ Skin Sens. 1A, H317	
· Additional information: Fo	r the wording of the listed hazard phrases refer to section	16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Seek immediate medical advice.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 44 (replaces version 43) Revision: 02.03.2023

Trade name: Mipa 1K-Klarlack C 10

(Contd. of page 3)

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit vail	ies that require monitoring at the workplace:
122 OF An Butul acatata	

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

78-93-3 Methyl ethyl ketone

WEL Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk. BMGV

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

1330-20-7 Xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

100-41-4 Ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm

· Ingredients with biological limit values:

78-93-3 Methyl ethyl ketone

BMGV 70 µmol/L

Medium: urine

Sampling time: post shift Parameter: butan-2-one

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 44 (replaces version 43) Revision: 02.03.2023

Trade name: Mipa 1K-Klarlack C 10

(Contd. of page 4)

1330-20-7 Xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- General Information
- · Physical state

Fluid

· Colour:

According to product specification

· Odour:

Characteristic

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 44 (replaces version 43) Revision: 02.03.2023

Trade name: Mipa 1K-Klarlack C 10

(Contd. of page 5)

• Odour threshold: Not determined. • Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range 56 °C (67-64-1 acetone)
Flammability Highly flammable.

· Lower and upper explosion limit

 Lower:
 1.2 Vol % (123-86-4 n-Butyl acetate)

 Upper:
 11.5 Vol % (78-93-3 Methyl ethyl ketone)

Flash point: 14 °C (DIN 53213)
 Ignition temperature: 370 °C (DIN 51794)
 Decomposition temperature: Not determined.
 pH Not determined.

· Viscosity:

• Kinematic viscosity at 20 °C 13 s (DIN 53211/4) • Dynamic: Not determined.

Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined.

· Vapour pressure at 20 °C: 233 hPa (67-64-1 acetone)

Density and/or relative density

Density at 20 °C: 0.903 g/cm³ (DIN 53217)

Relative densityVapour densityNot determined.Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

• **VOC (EC)** 81.17 % • **Solids content (weight-%):** 18.7 %

· Change in condition

· Evaporation rate Not determined.

Information with regard to physical hazard

classes

· Explosives Void

· Flammable gases Void

· Aerosols Void

· Oxidising gases Void

· Gases under pressure Void

• Flammable liquids Highly flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures

· Substances and mixtures, which emit

flammable gases in contact with water Void
Oxidising liquids Void
Oxidising solids Void

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 44 (replaces version 43) Revision: 02.03.2023

Trade name: Mipa 1K-Klarlack C 10

(Contd. of page 6)

· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · STOT-single exposure May cause drowsiness or dizziness.
- · Aspiration hazard May be fatal if swallowed and enters airways.
- · 11.2 Information on other hazards

· Endocrine disrupting properties		
78-93-3	Methyl ethyl ketone	List II
541-02-6	Decamethylcyclopentasiloxane	List II
556-67-2	octamethylcyclotetrasiloxane	List II, III
540-97-6	Dodecamethylcyclohexasiloxane	List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 8)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 44 (replaces version 43) Revision: 02.03.2023

Trade name: Mipa 1K-Klarlack C 10

Harmful to aquatic organisms

(Contd. of page 7)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, IMDG, IATA	UN1263	
14.2 UN proper shipping name ADR IMDG, IATA	UN1263 PAINT PAINT	
14.3 Transport hazard class(es)		
ADR		
Class Label	3 (F1) Flammable liquids. 3	
IMDG, IATA		
Class Label	3 Flammable liquids. 3	
14.4 Packing group ADR, IMDG, IATA	II.	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Warning: Flammable liquids.	
Hazard identification number (Kemler code): EMS Number:	33 F-E,S-E	
Stowage Category	B	
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.	
Transport/Additional information:		
ADR Limited quantities (LQ) Transport category	5L 2	



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 44 (replaces version 43) Revision: 02.03.2023

Trade name: Mipa 1K-Klarlack C 10

	(Contd. of page 8
· Tunnel restriction code	D/E
· IMDG · Limited quantities (LQ)	5L
· UN "Model Regulation":	UN 1263 PAINT, 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	50-100

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225	Highly flammable liquid and vapour.	

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 10)



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 44 (replaces version 43) Revision: 02.03.2023

Trade name: Mipa 1K-Klarlack C 10

(Contd. of page 9)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard — Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard — Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.

GB