

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2023

Version number 20 (replaces version 19)

Revision: 30.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Mipa AK 105-20 KH-Zinkphosphat-Dickschicht-Primer**

1.2 Relevant identified uses of the substance or mixture and uses advised against
No further relevant information available.

Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers

Application of the substance / the mixture Priming

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1

D-84051 Essenbach

Tel.: +49(0)8703-922-0

Fax.: +49(0)8703-922-100

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02

Signal word Warning

Hazard statements

H226 Flammable liquid and vapour.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2023

Version number 20 (replaces version 19)

Revision: 30.01.2023

Trade name: Mipa AK 105-20 KH-Zinkphosphat-Dickschicht-Primer

(Contd. of page 1)

- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P403+P235 Store in a well-ventilated place. Keep cool.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	2.5-<10%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	2-Butoxyethyl acetate Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	5-<10%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336, EUH066	2.5-<10%
CAS: 7779-90-0 EINECS: 231-944-3 Reg.nr.: 01-2119485044-40	Trizinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.25-<2.5%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	<2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Immediately rinse with water.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2023

Version number 20 (replaces version 19)

Revision: 30.01.2023

Trade name: Mipa AK 105-20 KH-Zinkphosphat-Dickschicht-Primer

(Contd. of page 2)

- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Use only in well ventilated areas.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2023

Version number 20 (replaces version 19)

Revision: 30.01.2023

Trade name: Mipa AK 105-20 KH-Zinkphosphat-Dickschicht-Primer

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

1330-20-7 Xylene

WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

108-65-6 2-Methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

112-07-2 2-Butoxyethyl acetate

WEL Short-term value: 332 mg/m³, 50 ppm
Long-term value: 133 mg/m³, 20 ppm
Sk

100-41-4 Ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm
Long-term value: 441 mg/m³, 100 ppm
Sk

Ingredients with biological limit values:

1330-20-7 Xylene

BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Respiratory protection: Filter A/P2 (EN 141, EN 143)

Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Fluorocarbon rubber (Viton)

Recommended thickness of the material: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material Value for the permeation: Level ≤ 2

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2023

Version number 20 (replaces version 19)

Revision: 30.01.2023

Trade name: Mipa AK 105-20 KH-Zinkphosphat-Dickschicht-Primer

(Contd. of page 4)

· **Eye/face protection**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state

Fluid

· Colour:

According to product specification

· Odour:

Characteristic

· Odour threshold:

Not determined.

· Melting point/freezing point:

Undetermined.

· Boiling point or initial boiling point and boiling range

137-143 °C (1330-20-7 Xylene)

· Flammability

Flammable.

· Lower and upper explosion limit

· Lower:

0.7 Vol %

· Upper:

7.5 Vol %

· Flash point:

29 °C (DIN 53213)

· Ignition temperature:

280 °C (DIN 51794, 112-07-2 2-Butoxyethyl acetate)

· Decomposition temperature:

Not determined.

· pH

Not determined.

· Viscosity:

· Kinematic viscosity at 20 °C

>60 s (ISO 6 mm)

· Dynamic:

Not determined.

· Solubility

· water:

Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value)

Not determined.

· Vapour pressure at 20 °C:

6.7-8.2 hPa (1330-20-7 Xylene)

· Density and/or relative density

· Density at 20 °C:

1.544 g/cm³ (DIN 53217)

· Relative density

Not determined.

· Vapour density

Not determined.

· 9.2 Other information

· Appearance:

· Form:

Fluid

· Important information on protection of health and environment, and on safety.

· Auto-ignition temperature:

Product is not selfigniting.

· Explosive properties:

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Solvent content:

· VOC (EC)

26.35 %

· Solids content (weight-%):

73.8 %

· Change in condition

· Evaporation rate

Not determined.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2023

Version number 20 (replaces version 19)

Revision: 30.01.2023

Trade name: Mipa AK 105-20 KH-Zinkphosphat-Dickschicht-Primer

(Contd. of page 5)

Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

Endocrine disrupting properties

78-93-3 Methyl ethyl ketone

List II

GB

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2023

Version number 20 (replaces version 19)

Revision: 30.01.2023

Trade name: Mipa AK 105-20 KH-Zinkphosphat-Dickschicht-Primer

(Contd. of page 6)


SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) : hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|---------------------------|
| · 14.1 UN number or ID number | |
| · ADR, IMDG, IATA | UN1263 |
| · 14.2 UN proper shipping name | |
| · ADR | UN1263 PAINT |
| · IMDG, IATA | PAINT |
| · 14.3 Transport hazard class(es) | |
| · ADR | |
|  | |
| · Class | 3 (F1) Flammable liquids. |
| · Label | 3 |

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2023

Version number 20 (replaces version 19)

Revision: 30.01.2023

Trade name: Mipa AK 105-20 KH-Zinkphosphat-Dickschicht-Primer

(Contd. of page 7)

· **IMDG, IATA**



· **Class** 3 Flammable liquids.
· **Label** 3

· **14.4 Packing group**
· **ADR, IMDG, IATA** III

· **14.5 Environmental hazards:**
· **Marine pollutant:** No

· **14.6 Special precautions for user** Warning: Flammable liquids.
· **Hazard identification number (Kemler code):** 30
· **EMS Number:** F-E, S-E
· **Stowage Category** A

· **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.

· **Transport/Additional information:**

· **ADR**
· **Limited quantities (LQ)** 5L
· **Transport category** 3
· **Tunnel restriction code** D/E
· **Remarks:** ≤ 450 l: 2.2.3.1.5 ADR

· **IMDG**
· **Limited quantities (LQ)** 5L
· **Remarks:** ≤ 30 l: 2.2.3.5 IMDG-Code

· **UN "Model Regulation":** UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials, Annex II:**

Class	Share in %
NK	25-50

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2023

Version number 20 (replaces version 19)

Revision: 30.01.2023

Trade name: Mipa AK 105-20 KH-Zinkphosphat-Dickschicht-Primer

(Contd. of page 8)

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Abbreviations and acronyms:

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * Data compared to the previous version altered.