

# Safety data sheet

according to 1907/2006/EC, Article 31 Version number 59 (replaces version 58)

Revision: 28.11.2023

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: <u>Mipa AK 200-90 KH-Spritzlack</u>
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- No further relevant information available.
- · Application of the substance / the mixture Paint
- 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: MIPA SE Am Oberen Moos 1 D-84051 Essenbach Tel.: +49 8703 92 20 Fax.: +49 8703 92 21 00 e-mail: sdb-registratur@mipa-paints.com www.mipa-paints.com
- 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

# SECTION 2: Hazards identification

• 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- · Hazard pictograms



· Signal word Warning

· Hazard-determining components of labelling: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 2-Methoxy-1-methylethyl acetate n-Butyl acetate · Hazard statements H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. Keep out of reach of children. P102 Read carefully and follow all instructions. P103 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 2)



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.11.2023

Version number 59 (replaces version 58)

Revision: 28.11.2023

#### Trade name: Mipa AK 200-90 KH-Spritzlack

	(Contd. of page 1)		
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.		
	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.		
	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].		
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
	Dispose of contents/container in accordance with local/regional/national/ international regulations.		
· Additional information:			
EUH066 Repeated exposure may cause skin dryness or cracking.			
EUH208 Contains Phthalic anhydride, Neodecansäure, Cobalsalz. May produce an allergic			
reaction.			
· 2.3 Other hazards			
. Deculto of DPT on	d v Dv P accoccoment		

Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

#### **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

<ul> <li>Dangerous components:</li> </ul>		
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	25-50%
	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336, EUH066	
CAS: 108-65-6	2-Methoxy-1-methylethyl acetate	2.5-<10%
EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	
CAS: 123-86-4	n-Butyl acetate	1-<2.5%
EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336, EUH066	
	Neodecansäure, Cobalsalz	<i>≥</i> 0.1-<1%
	STOT RE 1, H372; () Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 3, H412	
CAS: 85-44-9	Phthalic anhydride	<i>≥</i> 0.1-<1%
EINECS: 201-607-5 Reg.nr.: 01-2119457017-41	♦ Resp. Sens. 1, H334;  ♦ Eye Dam. 1, H318;  ♦ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
· Additional information: Fo	r the wording of the listed hazard phrases refer to section 16	

#### SECTION 4: First aid measures

• 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)

GB



# Safety data sheet

according to 1907/2006/EC, Article 31

Version number 59 (replaces version 58)

Revision: 28.11.2023

Trade name: Mipa AK 200-90 KH-Spritzlack

(Contd. of page 2)

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

# SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

# SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 7: Handling and storage

• **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

108-65-6 2-Methoxy-1-methylethyl acetate

- WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm Long-term value: 274 mg/m<sup>3</sup>, 50 ppm
  - Sk

(Contd. on page 4)

GB

# Professional Coating Systems

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.11.2023

#### Version number 59 (replaces version 58)

Revision: 28.11.2023

(Contd. of page 3)

#### Trade name: Mipa AK 200-90 KH-Spritzlack

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
- Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

• Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### · Hand protection

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### · Eye/face protection



Tightly sealed goggles

# SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Physical state
- · Colour:
- · Odour:
- · Odour threshold:
- · Melting point/freezing point:
- Boiling point or initial boiling point and boiling range
- Fluid According to product specification Characteristic Not determined. Undetermined.

155 °C (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics)

(Contd. on page 5)



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.11.2023

Version number 59 (replaces version 58)

Revision: 28.11.2023

# Trade name: Mipa AK 200-90 KH-Spritzlack

	(Contd. of page
Flammability	Flammable.
Lower and upper explosion limit	
Lower:	0.6 Vol %
Upper:	7 Vol %
Flash point:	29 °C (DIN 53213)
Auto-ignition temperature:	240 °C (DIN 51794)
Decomposition temperature:	Not determined.
рН	Not determined.
Viscosity:	
Kinematic viscosity at 20 °C	>60 s (ISO 6 mm)
Dynamic:	Not determined.
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log	
value)	Not determined.
Vapour pressure at 20 °C:	3 hPa (Hydrocarbons, C9-C11, n-alkanes
vapour pressure at 20°C.	
Donaity and/or relative danaity	isoalkanes, cyclics, < 2% aromatics)
Density and/or relative density	$0.096 \times (0.003)$ (DIN 52017)
Density at 20 °C:	0.986 g/cm <sup>3</sup> (DIN 53217)
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of hea	lth
and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
Solvent content:	
VOC (EC)	43.28 %
Solids content (weight-%):	56.7 %
Change in condition	00.7 /0
Evaporation rate	Not determined.
· ·	
Information with regard to physical haza	ard
classes Explosives	Void
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
conosive to metals	(Contd. on page



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.11.2023

Version number 59 (replaces version 58)

Revision: 28.11.2023

(Contd. of page 5)

Trade name: Mipa AK 200-90 KH-Spritzlack

· Desensitised explosives

Void

#### SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: Carbon monoxide

#### SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- · Acute toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.

#### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

#### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 7)

GB



# Safety data sheet

according to 1907/2006/EC, Article 31

Version number 59 (replaces version 58)

Revision: 28.11.2023

(Contd. of page 6)

#### Trade name: Mipa AK 200-90 KH-Spritzlack

**SECTION 14: Transport information** · 14.1 UN number or ID number · ADR, IMDG, IATA UN1263 · 14.2 UN proper shipping name UN1263 PAINT ·ADR · IMDG, IATA PAINT · 14.3 Transport hazard class(es) · ADR · Class 3 (F1) Flammable liquids. · Label 3 · IMDG, IATA · Class 3 Flammable liquids. · Label 3 · 14.4 Packing group · ADR, IMDG, IATA III· 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Flammable liquids. Hazard identification number (Kemler code): 30 · EMS Number: F-E,S-E Stowage Category Α · 14.7 Maritime transport in bulk according to IMO instruments Not applicable. · Transport/Additional information: ·ADR · Limited quantities (LQ) 5L 3 · Transport category · Tunnel restriction code D/E · Remarks: ≤ 450 I: -·IMDG · Limited quantities (LQ) 5L · Remarks: ≤ 30 l: -· UN "Model Regulation": UN 1263 PAINT, 3, III GB

(Contd. on page 8)



# Safety data sheet

according to 1907/2006/EC, Article 31 Version number 59 (replaces version 58)

Revision: 28.11.2023

# Trade name: Mipa AK 200-90 KH-Spritzlack

(Contd. of page 7)

#### SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

#### · National regulations:

• Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
Ι	<1
NK	25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

• Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

- Flam. Liq. 3: Flammable liquids Category 3
- Acute Tox. 4: Acute toxicity Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. on page 9)



# Safety data sheet according to 1907/2006/EC, Article 31

Revision: 28.11.2023

Printing date 28.11.2023

Version number 59 (replaces version 58)

Trade name: Mipa AK 200-90 KH-Spritzlack

(Contd. of page 8) STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 • \* **Data compared to the previous version altered.** 

GB