Revision: 02.03.2023



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.03.2023

Version number 46 (replaces version 45)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Mipa BC-Verdünnung lang
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Thinner, Diluent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0 Fax.: +49(0)8703-922-100

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

· 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



STOT SE 3

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms









GHS02 GHS07 GHS08 GHS09

· Signal word Danger

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 46 (replaces version 45) Revision: 02.03.2023

Trade name: Mipa BC-Verdünnung lang

(Contd. of page 1)

· Hazard-determining components of labelling:

Hydrocarbons, C9, aromatics

n-Butyl acetate

· Hazard statements

H226 Flammable liquid and vapour.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64742-95-6	Hydrocarbons, C9, aromatics	25-50%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H335-H336, EUH066	
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate ♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336, EUH066	25-50%
CAS: 112-07-2	2-Butoxyethyl acetate	5-<10%
EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	♠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Seek immediate medical advice.

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 46 (replaces version 45) Revision: 02.03.2023

Trade name: Mipa BC-Verdünnung lang

(Contd. of page 2)

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

ЗВ



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 46 (replaces version 45) Revision: 02.03.2023

Trade name: Mipa BC-Verdünnung lang

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

112-07-2 2-Butoxyethyl acetate

WEL Short-term value: 332 mg/m³, 50 ppm Long-term value: 133 mg/m³, 20 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 46 (replaces version 45) Revision: 02.03.2023

Trade name: Mipa BC-Verdünnung lang

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range 124-128 °C (123-86-4 n-Butyl acetate)

· Flammability Flammable.

Lower and upper explosion limit

· **Lower:** 0.7 Vol % (64742-95-6 Hydrocarbons, C9,

aromatics)

· **Upper:** 7.5 Vol % (64742-95-6 Hydrocarbons, C9,

aromatics)

• Flash point: 27 °C (DIN 53213)

· Ignition temperature: 280 °C (DIN 51794, 112-07-2 2-Butoxyethyl

acetate)

• Decomposition temperature: Not determined. • pH Not determined.

· Viscosity:

• Kinematic viscosity at 20 °C 10-15 s (DIN 53211/4)

· **Dynamic:** Not determined.

·Solubility

water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined.

· Vapour pressure at 20 °C: 10.7 hPa (123-86-4 n-Butyl acetate)

· Density and/or relative density

Density at 20 °C: 0.879 g/cm³ (DIN 53217)

Relative densityVapour densityNot determined.Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

· VOC (EC) 100.00 %
· Solids content (weight-%): 0.0 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard

classes

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure

Void

Void

· Flammable liquids Flammable liquid and vapour.

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 46 (replaces version 45) Revision: 02.03.2023

Trade name: Mipa BC-Verdünnung lang

		(Contd. of page 5)
· Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

64742-95-6 Hydrocarbons, C9, aromatics

Oral LD50 >2,000 mg/kg (rat)
Dermal LD50 >2,000 mg/kg (rabbit)

- STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.
- · Aspiration hazard May be fatal if swallowed and enters airways.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 46 (replaces version 45) Revision: 02.03.2023

Trade name: Mipa BC-Verdünnung lang

(Contd. of page 6)

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION	14:	Transpor	t int	format	tion
---------	-----	-----------------	-------	--------	------

	14.	1	UN	numbe	r or ID	number
--	-----	---	----	-------	---------	--------

· **ADR, IMDG, IATA** UN1263

· 14.2 UN proper shipping name

· ADR UN1263 PAINT RELATED MATERIAL,

ENVIRONMENTALLY HAZARDOUS

· IMDG PAINT RELATED MATERIAL (Solvent naphtha),

MARINE POLLUTANT

· IATA PAINT RELATED MATERIAL

- · 14.3 Transport hazard class(es)
- · ADR





· Class 3 (F1) Flammable liquids. · Label 3

·IMDG





· Class 3 Flammable liquids. · Label 3

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 46 (replaces version 45) Revision: 02.03.2023

Trade name: Mipa BC-Verdünnung lang

(Contd. of page 7)

·IATA



· Class 3 Flammable liquids.

· Label

· 14.4 Packing group · ADR, IMDG, IATA

· ADR, IMDG, IATA III
· 14.5 Environmental hazards: Product contains environmentally hazardous

substances: Solvent naphtha

· Marine pollutant: Yes

Symbol (fish and tree)
Special marking (ADR):
Symbol (fish and tree)

• 14.6 Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler code): 30

EMS Number: F-E,S-E

· Stowage Category A

• 14.7 Maritime transport in bulk according to
IMO instruments

Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)
 Transport category
 Tunnel restriction code

5L
5L
0
5L
0
5L

· IMDG

· Limited quantities (LQ) 5L

• UN "Model Regulation":

UN 1263 PAINT RELATED MATERIAL, 3, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	50-100

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 46 (replaces version 45) Revision: 02.03.2023

Trade name: Mipa BC-Verdünnung lang

(Contd. of page 8)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* * Data compared to the previous version altered.