Revision: 02.03.2023



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.03.2023

Version number 159 (replaces version 158)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Mipa EP 950-25 2K-EP-Härter
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC9a Coatings and paints, thinners, paint removers
- · Application of the substance / the mixture Hardening agent/ Curing agent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0

Fax.: +49(0)8703-922-100

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

• 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 159 (replaces version 158) Revision: 02.03.2023

Trade name: Mipa EP 950-25 2K-EP-Härter

(Contd. of page 1)

· Hazard pictograms









GHS02 GHS05 GHS07 GH

· Signal word Danger

· Hazard-determining components of labelling:

Polyaminoamide adduct

Butan-1-ol Xylene

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

| | Polyaminoamide adduct | |
|--|--|---------|
| | Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 | |
| CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32 | Xylene ♠ Flam. Liq. 3, H226; ♠ STOT RE 2, H373; Asp. Tox. 1, H304; ♠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | 25-50% |
| CAS: 71-36-3 EINECS: 200-751-6 Reg.nr.: 01-2119484630-38 | Butan-1-ol ♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ↑ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336 | ≥3-<10% |

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 159 (replaces version 158) Revision: 02.03.2023

Trade name: Mipa EP 950-25 2K-EP-Härter

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Revision: 02.03.2023 Printing date 02.03.2023 Version number 159 (replaces version 158)

Trade name: Mipa EP 950-25 2K-EP-Härter

(Contd. of page 3)

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

1330-20-7 Xvlene

WEL Short-term value: 441 mg/m³, 100 ppm

Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

71-36-3 Butan-1-ol

WEL | Short-term value: 154 mg/m³, 50 ppm

Ingredients with biological limit values:

1330-20-7 Xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

Filter A/P2 (EN 141, EN 143)



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Revision: 02.03.2023 Printing date 02.03.2023 Version number 159 (replaces version 158)

Trade name: Mipa EP 950-25 2K-EP-Härter

(Contd. of page 4)

· Material of gloves

Fluorocarbon rubber (Viton)

Recommended thickness of the material: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Breakthrough time of glove material Value for the permeation: Level \leq 6
- · Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state

· Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined. Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range 116-118 °C (71-36-3 Butan-1-ol)

· Flammability Flammable.

Lower and upper explosion limit

1.1 Vol % · Lower: Upper: 7 Vol %

27 °C (DIN 53213) Flash point: 340 °C (DIN 51794) · Ignition temperature: Not determined. Decomposition temperature: Not determined.

· pH

Viscosity:

· Kinematic viscosity Not determined. 800-2,200 mPas Dynamic at 20 °C:

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

Not determined. value) · Vapour pressure at 20 °C: 6.7-8.2 hPa

· Density and/or relative density

· Density at 20 °C: 0.941 g/cm3 (DIN 53217)

· Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

Auto-ignition temperature: Product is not selfigniting.

Product is not explosive. However, formation of • Explosive properties:

explosive air/vapour mixtures are possible.

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 159 (replaces version 158) Revision: 02.03.2023

Trade name: Mipa EP 950-25 2K-EP-Härter

(Contd. of page 5)

· Solvent content:

• **VOC (EC)** 40.00 % • **Solids content (weight-%):** 60.0 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

• Flammable liquids Flammable liquid and vapour.

· Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void Corrosive to metals Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability

· Desensitised explosives

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

| 1330-20-7 Xylene | | |
|------------------|----------|-----------------------|
| Oral | LD50 | 5,251 mg/kg (rat) |
| | | >5,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 29 mg/l (rat) |

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye damage.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · STOT-single exposure May cause respiratory irritation.
- · STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

Void

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 159 (replaces version 158) Revision: 02.03.2023

Trade name: Mipa EP 950-25 2K-EP-Härter

(Contd. of page 6)

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number

· **ADR, IMDG, IATA** UN1263

· 14.2 UN proper shipping name

ADR UN1263 PAINT RELATED MATERIAL

· IMDG, IATA PAINT RELATED MATERIAL

· 14.3 Transport hazard class(es)

· ADR



· Class 3 (F1) Flammable liquids.

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 159 (replaces version 158) Revision: 02.03.2023

Trade name: Mipa EP 950-25 2K-EP-Härter

| | (Contd. of page |
|---|--|
| Label | 3 |
| IMDG, IATA | |
| 3 | |
| Class | 3 Flammable liquids. |
| Label | 3 |
| 14.4 Packing group ADR, IMDG, IATA | III |
| 14.5 Environmental hazards: Marine pollutant: | No |
| 14.6 Special precautions for user Hazard identification number (Kemler code EMS Number: Stowage Category | Warning: Flammable liquids.): 30 F-E, <u>S-E</u> A |
| 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| Transport/Additional information: | |
| · ADR · Limited quantities (LQ) · Transport category · Tunnel restriction code · Remarks: | 5L 3 D/E ≤ 450 I: 2.2.3.1.5 ADR |
| · IMDG · Limited quantities (LQ) · Remarks: | 5L ≤ 30 l: 2.2.3.5 IMDG-Code |
| UN "Model Regulation": | UN 1263 PAINT RELATED MATERIAL, 3, III |

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

| Class | Share in % |
|-------|------------|
| NK | 25-50 |

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



according to 1907/2006/EC, Article 31

Printing date 02.03.2023 Version number 159 (replaces version 158) Revision: 02.03.2023

Trade name: Mipa EP 950-25 2K-EP-Härter

(Contd. of page 8)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

* Data compared to the previous version altered.