Revision: 01.02.2023



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 52 (replaces version 51)

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Mipa PU 240-05 2K-PU-Lack
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Paint
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0 Fax.: +49(0)8703-922-100

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

· 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3

H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

Hydrocarbons, C9, aromatics

2-Methoxy-1-methylethyl acetate

n-Butyl acetate

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 52 (replaces version 51) Revision: 01.02.2023

Trade name: Mipa PU 240-05 2K-PU-Lack

(Contd. of page 1)

#### · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

#### · Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains 2,3-epoxypropyl neodecanoate. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

#### SECTION 3: Composition/information on ingredients

#### · 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics  ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304;  ♦ Aquatic Chronic 2, H411; ↑ STOT SE 3, H335-H336, EUH066	≥2.5-<15%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate ♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	10-25%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate ♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336, EUH066	5-<10%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	2-Butoxyethyl acetate  Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	2.5-<5%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336, EUH066	2.5-<10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene ♦ Flam. Liq. 3, H226; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ↑ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1-<2.5%
CAS: 26761-45-5 EINECS: 247-979-2 Reg.nr.: 01-2119431597-33	2,3-epoxypropyl neodecanoate  Muta. 2, H341; Aquatic Chronic 2, H411; Skin Sens. 1, H317	≥0.1-<0.25%

Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 52 (replaces version 51) Revision: 01.02.2023

Trade name: Mipa PU 240-05 2K-PU-Lack

(Contd. of page 2)

· After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact: Immediately rinse with water.

- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 52 (replaces version 51) Revision: 01.02.2023

Trade name: Mipa PU 240-05 2K-PU-Lack

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

#### 108-65-6 2-Methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm

Sk

#### 123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

#### 112-07-2 2-Butoxyethyl acetate

WEL Short-term value: 332 mg/m³, 50 ppm Long-term value: 133 mg/m³, 20 ppm Sk

0.00.7.16.4

#### 1330-20-7 Xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

#### · Ingredients with biological limit values:

#### 1330-20-7 Xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### Hand protection

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 52 (replaces version 51) Revision: 01.02.2023

Trade name: Mipa PU 240-05 2K-PU-Lack

· Material of gloves

(Contd. of page 4)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range 124-128 °C (123-86-4 n-Butyl acetate)

Flammability Flammable.

Lower and upper explosion limit

Lower: 0.7 Vol % (64742-95-6 Hydrocarbons, C9,

aromatics)

· Upper: 10.8 Vol % (108-65-6 2-Methoxy-1-methylethyl

octob

acetate)

• Flash point: 30 °C (DIN 53213)

· Ignition temperature: 315 °C (DIN 51794)
· Decomposition temperature: Not determined.
· pH Not determined.

· Viscosity:

· Kinematic viscosity at 20 °C 140-160 s (DIN 53211/4)

Dynamic: Not determined.

· Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined.

· Vapour pressure at 20 °C: 10.7 hPa (123-86-4 n-Butyl acetate)

· Density and/or relative density

Density at 20 °C: 1.211 g/cm³ (DIN 53217)

Relative density
Not determined.
Vapour density
Not determined.

· 9.2 Other information

· Appearance:

Form: Fluid

· Important information on protection of health

and environment, and on safety.

Auto-ignition temperature: Product is not selfigniting.

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 52 (replaces version 51) Revision: 01.02.2023

Trade name: Mipa PU 240-05 2K-PU-Lack

(Contd. of page 5)

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

• **VOC (EC)** 41.22 % • **Solids content (weight-%):** 58.8 %

· Change in condition

· Evaporation rate Not determined.

Information with regard to physical hazard

classes

· Explosives
 · Flammable gases
 · Aerosols
 · Oxidising gases
 · Gases under pressure

Void

Void

Void

• Flammable liquids Flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures, which emit flammable gases in contact with water

flammable gases in contact with water
Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives
Void
Void
Void
Void
Void
Void

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

# SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards

· Endocrine disrupting properties	
78-93-3 Methyl ethyl ketone	List II
540-97-6 Dodecamethylcyclohexasiloxane	List II
541-02-6 Decamethylcyclopentasiloxane	List II

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 52 (replaces version 51) Revision: 01.02.2023

Trade name: Mipa PU 240-05 2K-PU-Lack

556-67-2 octamethylcyclotetrasiloxane

(Contd. of page 6)

List II, III

#### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

#### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

#### SECTION 14: Transport information

- · 14.1 UN number or ID number
- · ADR, IMDG, IATA UN1263
- · 14.2 UN proper shipping name
- · ADR UN1263 PAINT

· **IMDG, IATA** PAINT

- · 14.3 Transport hazard class(es)
- · ADR



· Class 3 (F1) Flammable liquids.

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 52 (replaces version 51) Revision: 01.02.2023

Trade name: Mipa PU 240-05 2K-PU-Lack

	(Contd. of page
Label	3
· IMDG, IATA	
3	
· Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids. : 30 F-E, <u>S-E</u> A
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	
· ADR · Limited quantities (LQ) · Transport category · Tunnel restriction code · Remarks:	5L 3 D/E ≤ 450 l: -
· IMDG · Limited quantities (LQ) · Remarks:	5L ≤ 30 l: -
UN "Model Regulation":	UN 1263 PAINT, 3, III

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 52 (replaces version 51) Revision: 01.02.2023

Trade name: Mipa PU 240-05 2K-PU-Lack

(Contd. of page 8)

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226	Flammable	liquid	and	vapour.

- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

#### · Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 2: Germ cell mutagenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* Data compared to the previous version altered.