



Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



· Signal word Warning

· Hazard-determining components of labelling: n-Butvl acetate 2-Methoxy-1-methylethyl acetate Hydrocarbons, C9, aromatics · Hazard statements H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

- · Precautionary statements
- Keep away from heat, hot surfaces, sparks, open flames and other ignition P210 sources. No smoking.

(Contd. on page 2) GB



according to 1907/2006/EC, Article 31

Revision: 30.01.2023

Printing date 30.01.2023

Version number 18 (replaces version 17)

Trade name: Mipa PU 240-90 2K-PU-Lack

	(Contd. of page 1)		
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.		
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.		
P303+P361+P35	53 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].		
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
P312	Call a POISON CENTER/doctor if you feel unwell.		
· Additional information:			
EUH066 Repeated exposure may cause skin dryness or cracking.			
EUH208 Contain	s 2,3-epoxypropyl neodecanoate. May produce an allergic reaction.		
2.3 Other hazards			
· Results of PBT and vPvB assessment			
· PBT: Not applicable.			
• vPvB: Not applic			
11			

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

CAS: 123-86-4	n-Butyl acetate	10-25%
EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336, EUH066	
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; () STOT SE 3, H336	2.5-<10%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	5-<10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<5%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	 2-Butoxyethyl acetate Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332 	2.5-<5%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	<2.5%
CAS: 26761-45-5 EINECS: 247-979-2 Reg.nr.: 01-2119431597-33	2,3-epoxypropyl neodecanoate Muta. 2, H341; Aquatic Chronic 2, H411; Skin Sens. 1, H317	<i>≥</i> 0.25-<1%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• General information: Immediately remove any clothing soiled by the product.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

GB



according to 1907/2006/EC, Article 31

Revision: 30.01.2023

Printing date 30.01.2023

Version number 18 (replaces version 17)

Trade name: Mipa PU 240-90 2K-PU-Lack

• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • For safety reasons unsuitable extinguishing agents: Water with full jet

- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- [•] 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)

GB

(Contd. of page 2)



Printing date 30.01.2023

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 18 (replaces version 17)

Revision: 30.01.2023

Trade name: Mipa PU 240-90 2K-PU-Lack

(Contd. of page 3)

Ingre	dients with limit values that require monitoring at the workplace:
123-8	6-4 n-Butyl acetate
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm
108-6	5-6 2-Methoxy-1-methylethyl acetate
WEL	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk
1330-	20-7 Xylene
WEL	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV
112-0	7-2 2-Butoxyethyl acetate
WEL	Short-term value: 332 mg/m³, 50 ppm Long-term value: 133 mg/m³, 20 ppm Sk
100-4	1-4 Ethylbenzene
WEL	Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk
Ingre	dients with biological limit values:
1330-	20-7 Xylene
BMG	V 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

· 8.2 Exposure controls

- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.
- **Respiratory protection:** Filter A/P2 (EN 141, EN 143)

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

⁻ GB



Printing date 30.01.2023

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 18 (replaces version 17)

Revision: 30.01.2023

Trade name: Mipa PU 240-90 2K-PU-Lack

(Contd. of page 4)

- · Material of gloves
- Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Breakthrough time of glove material Value for the permeation: Level ≤ 3
- · Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

 9.1 Information on basic physical and cheneral information 	mical properties
· Physical state	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and	ondetermined.
boiling range	124-128 °C (123-86-4 n-Butyl acetate)
· Flammability	Flammable.
· Lower and upper explosion limit	1.2 Val 9/ (122.96 4 n Buth(apotata)
· Lower:	1.2 Vol % (123-86-4 n-Butyl acetate)
· Upper:	7.5 Vol % (123-86-4 n-Butyl acetate)
Flash point:	30 °C (DIN 53213)
Ignition temperature:	315 °C (DIN 51794)
 Decomposition temperature: 	Not determined.
· pH	Not determined.
Viscosity:	
Kinematic viscosity at 20 °C	140-160 s (DIN 53211/4)
· Dynamic:	Not determined.
[.] Solubility	
· water:	Not miscible or difficult to mix.
 Partition coefficient n-octanol/water (log 	
value)	Not determined.
 Vapour pressure at 20 °C: 	10.7 hPa (123-86-4 n-Butyl acetate)
 Density and/or relative density 	
· Density at 20 °C:	1.09 g/cm³ (DIN 53217)
· Relative density	Not determined.
· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of hea	
and environment, and on safety.	arer -
· Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
Lapiosive properties.	explosive air/vapour mixtures are possible.
	(Contd. on page 6

____ GB



according to 1907/2006/EC, Article 31

Revision: 30.01.2023

Printing date 30.01.2023

Version number 18 (replaces version 17)

Trade name: Mipa PU 240-90 2K-PU-Lack

		(Contd. of page
Solvent content:		
VOC (EC)	42.79 %	
Solids content (weight-%):	57.2 %	
Change in condition		
Evaporation rate	Not determined.	
Information with regard to physical haz	ard	
classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Flammable liquid and vapour.	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

• **10.6 Hazardous decomposition products:** Carbon monoxide

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- · Acute toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- 11.2 Information on other hazards

· Endocrine disrupting properties		
541-02-6	Decamethylcyclopentasiloxane	List II
556-67-2	octamethylcyclotetrasiloxane	List II, III
540-97-6	Dodecamethylcyclohexasiloxane	List II

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 30.01.2023

Version number 18 (replaces version 17)

Revision: 30.01.2023

Trade name: Mipa PU 240-90 2K-PU-Lack

(Contd. of page 6)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

- **12.2 Persistence and degradability** No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties
- For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number		
ADR, IMDG, IATA	UN1263	
14.2 UN proper shipping name		
ADR	UN1263 PAINT	
IMDG, IATA	PAINT	
Class	3 (F1) Flammable liquids.	
Label	3	



Printing date 30.01.2023

Safety data sheet

according to 1907/2006/EC, Article 31

Version number 18 (replaces version 17)

Revision: 30.01.2023

Trade name: Mipa PU 240-90 2K-PU-Lack

	(Contd. of page
· IMDG, IATA	
Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
ADR, IMDG, IATA	III
[.] 14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	
EMS Number:	F-E, <u>S-E</u>
Stowage Category	A
[•] 14.7 Maritime transport in bulk according to	
IMO instruments	Not applicable.
• Transport/Additional information:	
ADR	
· Limited quantities (LQ)	5L
Transport category	3
 Tunnel restriction code 	D/E
· Remarks:	≤ 450 l: -
· IMDG	
· Limited quantities (LQ)	5L
Remarks:	<i>≤</i> 30 <i>l</i> : -
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	25-50

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 9)



according to 1907/2006/EC, Article 31

Revision: 30.01.2023

Printing date 30.01.2023

Version number 18 (replaces version 17)

Trade name: Mipa PU 240-90 2K-PU-Lack

(Contd. of page 8) Relevant phrases Highly flammable liquid and vapour. H225 H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H341 Suspected of causing genetic defects. May cause damage to organs through prolonged or repeated exposure. H373 H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. Classification according to Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation - Category 1 Muta. 2: Germ cell mutagenicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 ** Data compared to the previous version altered.