

1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** IK-Klarlack C 10
- **Application of the substance / the preparation** *Lacquer*
- **Manufacturer/Supplier:**
MIPA AG
Am Oberen Moos 1
D-84051 Essenbach
Tel.: +49(0)8703-922-0
Fax.: +49(0)8703-922-100
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com
- **Further information obtainable from:** *Laboratory*
- **Information in case of emergency:** +49(0)700 24112112 (MIP)

2 Hazards identification

- **Hazard description:**



Xn Harmful
F Highly flammable

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 11 Highly flammable.

R 20/21 Harmful by inhalation and in contact with skin.

R 36/38 Irritating to eyes and skin.

R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

- **Chemical characterization**

- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1	<i>n</i> -butyl acetate R 10-66-67	25-50%
CAS: 67-64-1 EINECS: 200-662-2	acetone ☒ Xi, ☒ F; R 11-36-66-67	10-25%
CAS: 1330-20-7 EINECS: 215-535-7	xylene ☒ Xn, ☒ Xi; R 10-20/21-38	10-25%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. ☒ Xn, ☒ Xi, ☒ N; R 10-37-51/53-65-66-67	≤ 2.5%
CAS: 108-10-1 EINECS: 203-550-1	4-methylpentan-2-one ☒ Xn, ☒ Xi, ☒ F; R 11-20-36/37-66	≤ 2.5%
CAS: 131-11-3 EINECS: 205-011-6	dimethyl phthalate	≤ 2.5%

(Contd. on page 2)

Trade name: 1K-Klarlack C 10

(Contd. of page 1)

CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate ☒ Xi; R 10-36	≤ 2.5%
CAS: 41556-26-7 EINECS: 255-437-1	Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacat ☒ Xi, ☒ N; R 43-50/53	<1.0%
CAS: 127519-17-9 ELINCS: 407-000-3	A mixture of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethyl-ethyl)-4-hydroxyphenyl]propionates ☒ N; R 51/53	<1.0%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

5 Fire-fighting measures

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

· **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.

· **Measures for environmental protection:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Measures for cleaning/collecting:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

7 Handling and storage

· **Handling:**

· **Information for safe handling:**

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 3)

Trade name: 1K-Klarlack C 10

(Contd. of page 2)

- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

123-86-4 n-butyl acetate

WEL () Short-term value: 966 mg/m³, 200 ppm
Long-term value: 724 mg/m³, 150 ppm

67-64-1 acetone

WEL () Short-term value: 3620 mg/m³, 1500 ppm
Long-term value: 1210 mg/m³, 500 ppm

1330-20-7 xylene

WEL () Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

108-10-1 4-methylpentan-2-one

WEL () Short-term value: 416 mg/m³, 100 ppm
Long-term value: 208 mg/m³, 50 ppm
Sk

131-11-3 dimethyl phthalate

WEL () Short-term value: 10 mg/m³
Long-term value: 5 mg/m³

108-65-6 2-methoxy-1-methylethyl acetate

WEL () Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

- **Additional information:** The lists valid during the making were used as basis.

- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

(Contd. on page 4)

Trade name: 1K-Klarlack C 10

(Contd. of page 3)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55°C

· **Flash point:** < 0°C (DIN 53213)

· **Ignition temperature:** 370°C (DIN 51794)

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower:	1.1 Vol %
Upper:	13.0 Vol %

· **Vapour pressure at 20°C:** 233 hPa

· **Density at 20°C:** 0.887 g/cm³ (DIN 53217)

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Viscosity:**

Kinematic at 20°C: 13 s (DIN 53211/4)

· **Solvent content:**

Organic solvents:	81.7 %
VOC (EC)	724.9 g/l

(Contd. on page 5)

Printing date 24.03.2010

Revision: 24.03.2010

Trade name: 1K-Klarlack C 10

(Contd. of page 4)

· Solids content (weight-%): 18.3 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** Carbon monoxide

11 Toxicological information· **Acute toxicity:**· **LD/LC50 values relevant for classification:****1330-20-7 xylene**

Oral LD50 4300 mg/kg (rat)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >6800 mg/kg (rat)

Dermal LD50 >3400 mg/kg (rab)

Inhalative LC50/4 h >10.2 mg/l (rat)

· **Primary irritant effect:**· **on the skin:** Irritant to skin and mucous membranes.· **on the eye:** Irritating effect.· **Sensitization:** No sensitizing effects known.· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

12 Ecological information· **Ecotoxicological effects:**· **Remark:** Harmful to fish· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

13 Disposal considerations· **Product:**· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 01 11 waste paint and varnish containing organic solvents or other dangerous substances

(Contd. on page 6)

Printing date 24.03.2010

Revision: 24.03.2010

Trade name: 1K-Klarlack C 10

(Contd. of page 5)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID (cross-border)



- **ADR/RID class:** 3 (F1) Flammable liquids.
- **Danger code (Kemler):** 33
- **UN-Number:** 1263
- **Packaging group:** II
- **Hazard label:** 3
- **Description of goods:** 1263 PAINT, special provision 640D

· Maritime transport IMDG:



- **IMDG Class:** 3
- **UN Number:** 1263
- **Label:** 3
- **Packaging group:** II
- **EMS Number:** F-E,S-E
- **Marine pollutant:** No
- **Proper shipping name:** PAINT

· Air transport ICAO-TI and IATA-DGR:



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1263
- **Label:** 3
- **Packaging group:** II
- **Proper shipping name:** PAINT

15 Regulatory information

- **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- **Code letter and hazard designation of product:**
Xn Harmful
F Highly flammable
- **Hazard-determining components of labelling:**
xylene

(Contd. on page 7)

Trade name: 1K-Klarlack C 10

(Contd. of page 6)

· **Risk phrases:**

- 11 *Highly flammable.*
- 20/21 *Harmful by inhalation and in contact with skin.*
- 36/38 *Irritating to eyes and skin.*
- 52/53 *Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*

· **Safety phrases:**

- 2 *Keep out of the reach of children.*
- 9 *Keep container in a well-ventilated place.*
- 13 *Keep away from food, drink and animal feedingstuffs.*
- 16 *Keep away from sources of ignition - No smoking.*
- 36/37 *Wear suitable protective clothing and gloves.*
- 46 *If swallowed, seek medical advice immediately and show this container or label.*

· **Special labelling of certain preparations:**

Contains Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacat. May produce an allergic reaction.

· **National regulations:**

· **Information about limitation of use:**

None of the ingredients is listed.

Class	Share in %
NK	50-100

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

- 10 *Flammable.*
- 11 *Highly flammable.*
- 20 *Harmful by inhalation.*
- 20/21 *Harmful by inhalation and in contact with skin.*
- 36 *Irritating to eyes.*
- 36/37 *Irritating to eyes and respiratory system.*
- 37 *Irritating to respiratory system.*
- 38 *Irritating to skin.*
- 43 *May cause sensitisation by skin contact.*
- 50/53 *Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*
- 51/53 *Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*
- 65 *Harmful: may cause lung damage if swallowed.*
- 66 *Repeated exposure may cause skin dryness or cracking.*
- 67 *Vapours may cause drowsiness and dizziness.*

· **Department issuing MSDS:** MIPA AG, Abteilung Umweltschutz

· **Contact:** Michaela Knall

· *** Data compared to the previous version altered.**