

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** *OC-Mischlack-Konzentrat*
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the preparation** *Lacquer*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
*MIPA AG
Am Oberen Moos 1
D-84051 Essenbach
Tel.: +49(0)8703-922-0
Fax.: +49(0)8703-922-100
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com*
- **Further information obtainable from:** *Laboratory*
- **Emergency telephone number:** *+49(0)700 24112112 (MIP)*

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
R10-66-67: Flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.
- **Information concerning particular hazards for human and environment:**
*The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
Has a narcotizing effect.*
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.
- **Label elements**
- **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- **Risk phrases:**
*10 Flammable.
66 Repeated exposure may cause skin dryness or cracking.
67 Vapours may cause drowsiness and dizziness.*
- **Safety phrases:**
*2 Keep out of the reach of children.
25 Avoid contact with eyes.
43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
46 If swallowed, seek medical advice immediately and show this container or label.
51 Use only in well-ventilated areas.*
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*

Trade name: OC-Mischlack-Konzentrat

(Contd. of page 1)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate R10-66-67 ----- ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	10-25%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate ⚠ Xi R36 R10 ----- ⚠ Flam. Liq. 3, H226; ⚠ Eye Irrit. 2, H319	2.5-10%
CAS: 1333-86-4 EINECS: 215-609-9	Carbon black	≤ 2.5%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. ⚠ Xn R65; ⚠ Xi R37; ⚠ N R51/53 R10-66-67 ----- ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335+H336	≤ 1.0%
CAS: 8052-41-3 EINECS: 232-489-3	Stoddard solvent ⚠ Xn R65; ⚠ N R51/53 R10-66 ----- ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411	≤ 1.0%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

Trade name: OC-Mischlack-Konzentrat

(Contd. of page 2)

- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Use only in well ventilated areas.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

123-86-4 n-butyl acetate

WEL ()	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
--------	---

108-65-6 2-methoxy-1-methylethyl acetate

WEL ()	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm .Sk
--------	---

1333-86-4 Carbon black

WEL ()	Short-term value: 7 mg/m ³ Long-term value: 3.5 mg/m ³
--------	---

- **Additional information:** The lists valid during the making were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:** Wash hands before breaks and at the end of work.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 4)

Trade name: OC-Mischlack-Konzentrat

(Contd. of page 3)

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid
Colour: According to product specification

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 124°C

· **Flash point:** 30°C (DIN 53213)

· **Ignition temperature:** 315°C (DIN 51794)

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower: 1.2 Vol %
Upper: 7.5 Vol %

· **Vapour pressure at 20°C:** 10.7 hPa

· **Density at 20°C:** 1.159 g/cm³ (DIN 53217)

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Segregation coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic: Not determined.
Kinematic at 20°C: 127 s (DIN 53211/4)

(Contd. on page 5)

Trade name: OC-Mischlack-Konzentrat

(Contd. of page 4)

· Solvent content:	
Organic solvents:	31.4 %
VOC (EC)	363.8 g/l
· Solids content (weight-%): 68.4 %	
· Other information No further relevant information available.	

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

12 Ecological information

- **Toxicity**
- **Acquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances

(Contd. on page 6)

Trade name: OC-Mischlack-Konzentrat

(Contd. of page 5)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID (cross-border)



- **ADR/RID class:** 3 (F1) Flammable liquids.
- **Danger code (Kemler):** 30
- **UN-Number:** 1263
- **Packaging group:** III
- **Hazard label:** 3
- **UN proper shipping name:** 1263 PAINT, special provision 640E
- **Tunnel restriction code** D/E
- **Remarks:** ≤ 450 l: -

· Maritime transport IMDG:



- **IMDG Class:** 3
- **UN Number:** 1263
- **Label** 3
- **Packaging group:** III
- **EMS Number:** F-E,S-E
- **Marine pollutant:** No
- **Proper shipping name:** PAINT
- **Remarks:** ≤ 30 l: -

· Air transport ICAO-TI and IATA-DGR:



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1263
- **Label** 3
- **Packaging group:** III
- **Proper shipping name:** PAINT

- **Special precautions for user** Warning: Flammable liquids.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

GB

(Contd. on page 7)

Trade name: OC-Mischlack-Konzentrat

(Contd. of page 6)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- National regulations:

· **Information about limitation of use:**

1333-86-4	Carbon black	3B
64-17-5	ethanol	5

Class	Share in %
NK	25-50

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- R10 Flammable.
- R36 Irritating to eyes.
- R37 Irritating to respiratory system.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

- **Department issuing MSDS:** MIPA AG, Abteilung Umweltschutz
- **Contact:** Michaela Knall
- *** Data compared to the previous version altered.**