

## 1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** OC-Mischlack-Konzentrat
- **Application of the substance / the preparation** *Lacquer*
- **Manufacturer/Supplier:**  
MIPA AG  
Am Oberen Moos 1  
D-84051 Essenbach  
Tel.: +49(0)8703-922-0  
Fax.: +49(0)8703-922-100  
e-mail: [sdb-registratur@mipa-paints.com](mailto:sdb-registratur@mipa-paints.com)  
[www.mipa-paints.com](http://www.mipa-paints.com)
- **Further information obtainable from:** *Laboratory*
- **Information in case of emergency:** +49(0)700 24112112 (MIP)







## 2 Hazards identification

- **Hazard description:** *Not applicable.*
- **Information concerning particular hazards for human and environment:**  
*The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.*  
*At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.*  
*Has a narcotizing effect.*  
*R 10 Flammable.*  
*R 66 Repeated exposure may cause skin dryness or cracking.*  
*R 67 Vapours may cause drowsiness and dizziness.*
- **Classification system:**  
*The classification is according to the latest editions of the EU-lists, and extended by company and literature data.*

## 3 Composition/information on ingredients

- **Chemical characterization**
- **Description:** *Mixture of substances listed below with nonhazardous additions.*

- **Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate R 10-66-67	10-25%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate  Xi; R 10-36	2.5-10%
CAS: 1333-86-4 EINECS: 215-609-9	Carbon black	≤ 2.5%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom.  Xn,  Xi,  N; R 10-37-51/53-65-66-67	<1.0%
CAS: 8052-41-3 EINECS: 232-489-3	Stoddard solvent  Xn,  N; R 10-51/53-65-66	<1.0%

- **Additional information:** *For the wording of the listed risk phrases refer to section 16.*

## 4 First aid measures

- **After inhalation:** *Supply fresh air; consult doctor in case of complaints.*
- **After skin contact:** *Generally the product does not irritate the skin.*
- **After eye contact:** *Rinse opened eye for several minutes under running water.*

(Contd. on page 2)

**Trade name: OC-Mischlack-Konzentrat**

(Contd. of page 1)

· *After swallowing: If symptoms persist consult doctor.*

### 5 Fire-fighting measures

- *Suitable extinguishing agents: CO<sub>2</sub>, sand, extinguishing powder. Do not use water.*
- *For safety reasons unsuitable extinguishing agents: Water with full jet*
- *Protective equipment: No special measures required.*

### 6 Accidental release measures

- *Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.*
- *Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.*
- *Measures for cleaning/collecting:*  
*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).*  
*Do not flush with water or aqueous cleansing agents*

### \* 7 Handling and storage

- *Handling:*
- *Information for safe handling: Use only in well ventilated areas.*
- *Information about fire - and explosion protection:*  
*Keep ignition sources away - Do not smoke.*  
*Protect against electrostatic charges.*
- *Storage:*
- *Requirements to be met by storerooms and receptacles: No special requirements.*
- *Information about storage in one common storage facility: Store away from foodstuffs.*
- *Further information about storage conditions: Keep container tightly sealed.*
- *Storage class: 3*

### \* 8 Exposure controls/personal protection

- *Additional information about design of technical facilities: No further data; see item 7.*

- *Ingredients with limit values that require monitoring at the workplace:*

#### 123-86-4 n-butyl acetate

WEL ()	Short-term value: 966 mg/m <sup>3</sup> , 200 ppm Long-term value: 724 mg/m <sup>3</sup> , 150 ppm
--------	---

#### 108-65-6 2-methoxy-1-methylethyl acetate

WEL ()	Short-term value: 548 mg/m <sup>3</sup> , 100 ppm Long-term value: 274 mg/m <sup>3</sup> , 50 ppm Sk
--------	--

#### 1333-86-4 Carbon black

WEL ()	Short-term value: 7 mg/m <sup>3</sup> Long-term value: 3.5 mg/m <sup>3</sup>
--------	---

- *Additional information: The lists valid during the making were used as basis.*

- *Personal protective equipment:*
- *General protective and hygienic measures: Wash hands before breaks and at the end of work.*
- *Respiratory protection:*  
*In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.*

(Contd. on page 3)

**Trade name: OC-Mischlack-Konzentrat**

(Contd. of page 2)

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **General Information**

<b>Form:</b>	Fluid
<b>Colour:</b>	According to product specification
<b>Odour:</b>	Characteristic

· **Change in condition**

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** 124°C

· **Flash point:** 30°C (DIN 53213)

· **Ignition temperature:** 315°C (DIN 51794)

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

**Lower:** 1.2 Vol %

**Upper:** 7.5 Vol %

· **Vapour pressure at 20°C:** 10.7 hPa

· **Density at 20°C:** 1.159 g/cm<sup>3</sup> (DIN 53217)

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Viscosity:**

**Kinematic at 20°C:** 127 s (DIN 53211/4)

· **Solvent content:**

**Organic solvents:** 31.6 %

**VOC (EC)** 367.8 g/l

(Contd. on page 4)

Printing date 15.03.2010

Revision: 15.03.2010

Trade name: OC-Mischlack-Konzentrat

(Contd. of page 3)

· Solids content (weight-%): 68.4 %

**10 Stability and reactivity**

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous decomposition products:** Carbon monoxide

**11 Toxicological information**

- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

**12 Ecological information**

- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

**13 Disposal considerations**

- **Product:**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 01 11 | waste paint and varnish containing organic solvents or other dangerous substances

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

- **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 3 (F1) Flammable liquids.
- **Danger code (Kemler):** 30
- **UN-Number:** 1263
- **Packaging group:** III
- **Hazard label:** 3
- **Description of goods:** 1263 PAINT, special provision 640E

(Contd. on page 5)

**Trade name: OC-Mischlack-Konzentrat**

(Contd. of page 4)

· **Remarks:** ≤ 450 l: -

· **Maritime transport IMDG:**



· **IMDG Class:** 3  
 · **UN Number:** 1263  
 · **Label** 3  
 · **Packaging group:** III  
 · **EMS Number:** F-E,S-E  
 · **Marine pollutant:** No  
 · **Proper shipping name:** PAINT  
 · **Remarks:** ≤ 30 l: -

· **Air transport ICAO-TI and IATA-DGR:**



· **ICAO/IATA Class:** 3  
 · **UN/ID Number:** 1263  
 · **Label** 3  
 · **Packaging group:** III  
 · **Proper shipping name:** PAINT

### 15 Regulatory information

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Risk phrases:**

10 Flammable.  
 66 Repeated exposure may cause skin dryness or cracking.  
 67 Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

2 Keep out of the reach of children.  
 25 Avoid contact with eyes.  
 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.  
 46 If swallowed, seek medical advice immediately and show this container or label.  
 51 Use only in well-ventilated areas.

· **National regulations:**

· **Information about limitation of use:**

1333-86-4	Carbon black	3B
64-17-5	ethanol	5

Class	Share in %
NK	25-50

GB

(Contd. on page 6)

**Trade name: OC-Mischlack-Konzentrat**

(Contd. of page 5)

### **16 Other information**

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Relevant R-phrases**

- 10 Flammable.
- 36 Irritating to eyes.
- 37 Irritating to respiratory system.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** MIPA AG, Abteilung Umweltschutz

· **Contact:** Michaela Knall

· **\* Data compared to the previous version altered.**