

1 Identification of substance

- **Product details**
- **Trade name:** EP-Grundierfiller grau
- **Application of the substance / the preparation** Primer
- **Manufacturer/Supplier:**
MIPA AG
Am Oberen Moos 1
D-84051 Essenbach
Tel.: 0049(0) 8703-922-0
Fax.: 0049(0) 8703-922-100
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com
- **Information department:** Laboratory
- **Emergency information:** 011 49(0)700 24112112 (MIP)

2 Composition/Data on components

- **Chemical characterization**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

25036-25-3	bisphenole	10-25%
108-65-6	2-methoxy-1-methylethyl acetate	10-25%
1330-20-7	xylene	2.5-10%
7779-90-0	Preparation based on zincphosphate (supplier's classification)	2.5-10%
108-10-1	4-methylpentan-2-one	2.5-10%
64742-95-6	Solvent naphtha (petroleum), light arom.	2.5-10%
107-98-2	1-methoxy-2-propanol	2.5-10%
123-86-4	n-butyl acetate	2.5-10%
1314-13-2	zinc oxide	<1.0%

3 Hazards identification

- **Hazard description:**



Irritant

- **Information pertaining to particular dangers for man and environment:**

The product has to be labelled due to the calculation procedure of international guidelines.

Flammable.

Irritating to eyes and skin.

May cause sensitisation by skin contact.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

Printing date 03/15/2010

Reviewed on 03/12/2010

Trade name: EP-Grundierfiller grau

(Contd. of page 1)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = 1
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

4 First aid measures

- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

5 Fire fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 3

USA

(Contd. on page 3)

Printing date 03/15/2010

Reviewed on 03/12/2010

Trade name: EP-Grundierfiller grau

(Contd. of page 2)

8 Exposure controls and personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Components with limit values that require monitoring at the workplace:**

108-65-6 2-methoxy-1-methylethyl acetate

WEEL () 50 ppm

1330-20-7 xylene

PEL () 435 mg/m³, 100 ppm

REL () Short-term value: 655 mg/m³, 150 ppm

Long-term value: 435 mg/m³, 100 ppm

TLV () Short-term value: 651 mg/m³, 150 ppm

Long-term value: 434 mg/m³, 100 ppm

BEI

108-10-1 4-methylpentan-2-one

PEL () 410 mg/m³, 100 ppm

REL () Short-term value: 300 mg/m³, 75 ppm

Long-term value: 205 mg/m³, 50 ppm

TLV () Short-term value: 307 mg/m³, 75 ppm

Long-term value: (205) 82 mg/m³, (50) NIC-20 ppm

(BEI);NIC-A3

107-98-2 1-methoxy-2-propanol

REL () Short-term value: 540 mg/m³, 150 ppm

Long-term value: 360 mg/m³, 100 ppm

TLV () Short-term value: 553 mg/m³, 150 ppm

Long-term value: 369 mg/m³, 100 ppm

123-86-4 n-butyl acetate

PEL () 710 mg/m³, 150 ppm

REL () Short-term value: 950 mg/m³, 200 ppm

Long-term value: 710 mg/m³, 150 ppm

TLV () Short-term value: 950 mg/m³, 200 ppm

Long-term value: 713 mg/m³, 150 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 4)

Trade name: EP-Grundierfiller grau

(Contd. of page 3)

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form:	Fluid
Color:	According to product specification
Odor:	Characteristic

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	137°C (279°F)

· **Flash point:** 24°C (75°F) (DIN 53213)

· **Ignition temperature:** 315°C (599°F) (DIN 51794)

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower:	1.5 Vol %
Upper:	10.8 Vol %

· **Vapor pressure at 20°C (68°F):** 6.7 hPa (5 mm Hg)

· **Density at 20°C (68°F):** 1.51 g/cm³ (DIN 53217)

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Viscosity:**

Dynamic at 20°C (68°F): 10000 mPas

· **Solvent content:**

Organic solvents:	33.8 %
VOC content:	33.8 %
	510.8 g/l / 4.26 lb/gl

· **Solids content (weight-%):** 66.2 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.

(Contd. on page 5)

Printing date 03/15/2010

Reviewed on 03/12/2010

Trade name: EP-Grundierfiller grau

(Contd. of page 4)

· **Dangerous products of decomposition:** Carbon monoxide

11 Toxicological information

· **Acute toxicity:**· **LD/LC50 values that are relevant for classification:**

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
------	------	------------------

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	> 6800 mg/kg (rat)
------	------	--------------------

Dermal	LD50	> 3400 mg/kg (rab)
--------	------	--------------------

Inhalative	LC50/4 h	> 10.2 mg/l (rat)
------------	----------	-------------------

· **Primary irritant effect:**· **on the skin:** Irritant to skin and mucous membranes.· **on the eye:** Irritating effect.· **Sensitization:** Sensitization possible through skin contact.· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

12 Ecological information

· **Ecotoxicological effects:**· **Aquatic toxicity:**

7779-90-0 Preparation based on zincphosphate (supplier's classification)

EC50	63.1 mg/kg (daphnia)
------	----------------------

· **Remark:** Harmful to fish· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

13 Disposal considerations

· **Product:**· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**· **Recommendation:** Disposal must be made according to official regulations.

USA

(Contd. on page 6)

Printing date 03/15/2010

Reviewed on 03/12/2010

Trade name: EP-Grundierfiller grau

(Contd. of page 5)

14 Transport information

· DOT regulations:



- Hazard class: 3
- Identification number: UN1263
- Packing group: III
- Proper shipping name (technical name): PAINT
- Label: 3

· Land transport ADR/RID (cross-border):



- ADR/RID class: 3 (F1) Flammable liquids
- Danger code (Kemler): 30
- UN-Number: 1263
- Packaging group: III
- Label: 3
- Description of goods: 1263 PAINT, special provision 640E
- Remarks: ≤ 450 l: -

· Maritime transport IMDG:



- IMDG Class: 3
- UN Number: 1263
- Label: 3
- Packaging group: III
- EMS Number: F-E, S-E
- Marine pollutant: No
- Proper shipping name: PAINT
- Remarks: ≤ 30 l: -

· Air transport ICAO-TI and IATA-DGR:



- ICAO/IATA Class: 3
- UN/ID Number: 1263
- Label: 3
- Packaging group: III
- Proper shipping name: PAINT

USA

(Contd. on page 7)

Printing date 03/15/2010

Reviewed on 03/12/2010

Trade name: EP-Grundierfiller grau

(Contd. of page 6)

15 Regulations

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
-----------	--------

108-10-1	4-methylpentan-2-one
----------	----------------------

1344-28-1	aluminium oxide
-----------	-----------------

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
-----------	--------	---

108-10-1	4-methylpentan-2-one	I
----------	----------------------	---

1314-13-2	zinc oxide	II
-----------	------------	----

· **IARC (International Agency for Research on Cancer)**

14807-96-6	Talk	3
------------	------	---

1330-20-7	xylene	3
-----------	--------	---

13463-67-7	titanium dioxide	2B
------------	------------------	----

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

14807-96-6	Talk	A4	25-50%
------------	------	----	--------

1330-20-7	xylene	A4	2,5-10%
-----------	--------	----	---------

13463-67-7	titanium dioxide	A4	2,5-10%
------------	------------------	----	---------

1344-28-1	aluminium oxide	A4	<1,0%
-----------	-----------------	----	-------

1314-23-4	zirconium dioxide	A4	<1,0%
-----------	-------------------	----	-------

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
------------	------------------

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

(Contd. on page 8)

Trade name: EP-Grundierfiller grau

(Contd. of page 7)

· Hazard symbols:

Irritant

· Hazard-determining components of labelling:

bisphenole

· Risk phrases:

Flammable.

Irritating to eyes and skin.

May cause sensitisation by skin contact.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Safety phrases:

Keep out of the reach of children.

Do not breathe fumes/aerosol.

Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Wear suitable gloves.

If swallowed, seek medical advice immediately and show this container or label.

· National regulations:

· Information about limitation of use:

14807-96-6	Talk	3B
13463-67-7	titanium dioxide	3A
1344-28-1	aluminium oxide	2

Class	Share in %
NK	25-50

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: MIPA AG, Abteilung Umweltschutz

· Contact: Michaela Knall

· * Data compared to the previous version altered.