

### Description

<b>Intended use:</b>	Mipa Abbeizer CHO is a low viscosity paint stripper without CHC and NMP to remove old and dried layers of paints and varnishes based on EP, PU, polyester, dispersion or synthetic resin from metal and other substrates. Due to its low viscosity and powerful solvents, it can be used also in immersion processes as tool cleansing agents for spray guns as well as for jigs for goods to be coated (hooks, rags, and so on).
<b>Properties:</b>	<ul style="list-style-type: none"><li>- free from CHC and NMP</li><li>- very powerful solvents</li><li>- easy to use</li><li>- economic, as it is reusable</li><li>- without harming the substrate</li></ul>
<b>Specifications:</b>	viscosity: approx. 10 sec / 4mm DIN specific weight: approx. 0,95 g / cm <sup>3</sup>
<b>Storage:</b>	At least 2 years in unopened original container

### Application

<b>Application :</b>	Apply the product by immersion or generously with a paintbrush, or roller uniformly on the lying substrate. In case of multilayer coatings, we recommend applying a second generous layer of the product. The solving time depends on the type and thickness of the paint layer to be removed as well as on the temperature. Do not apply at a temperature below 5°C or above max. 35°C. Prior to application, remove all dirt, dust, oil and releasing agents from the surface.
<b>Spreading rate:</b>	8-14 m <sup>2</sup> /l depending on the nature of the substrate

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

**Special note**

Before use, it is necessary to test the suitability of the product and the resistance of the substrate in an inconspicuous place. This product may cause loss of gloss on chromed surfaces.

**Safety advice**

Wear suitable protective clothing (eye protection and suitable gloves). Keep away from children. Do not breathe vapour /aerosol. In case of contact with eyes wash immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water and soap. Only use in well-ventilated areas (vapours are heavier than air). Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

**Cleaning of tools**

Clean tools immediately after use with a lot of water.

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update