

Intended use









Mipa 2K-HS-Löser is a special mixture of solvents (fade-out thinner) to dissolve edges of spot repairs and fade-out areas for Mipa 2K-HS topcoat systems. Mipa 2K-HS-Löser can be used as fade-out thinner in combination with following products:

Mipa PUR HS, Mipa OC, Mipa 2K-MS-Klarlacke (clearcoat), Mipa 2K-HS-Klarlacke (clearcoat)

After having applied one of these products, spray immediately Mipa 2K-HS-Löser over the border areas (overspray areas). Melt the overspray edges with a very uniform coat of Mipa 2K-HS-Löser until the rough overspray become visibly smooth. Do not apply too much, otherwise irregular dissolving or runs are to be expected.

Spreading rate: --

Processing instructions

	Colour colourless						
	Mixing ratio	Hardener		by weight (lacquer : hardener)	by volume (lacquer : hardener)		
	--	--	--	--	--		
	Hardener	for complete paintwork		for partial paintwork			
	--	--		--			
	Pot life	--					
	Thinner ready for use						
	Spray viscosity gravity spray gun				Airmix/Airless		
	--	--			--		
	Application mode	Application mode	Hardener	pressure (bar)	nozzle (mm)	spray passes	Thinner
	--	--	--	--	--	--	--
	Flash-off time	--					
Dry coat thickness		--					



Drying time
object
temperature

dust dry

set to
touch

ready for
assembly

sandable

recoatable

--

--

--

--

--

--

Note

Storage: at least 3 years in unopened original container

VOC Regulation : --

Processing conditions: From +10 °C and up to 80 % relative air humidity. Ensure an adequate supply and exhaust air ventilation.

Processing instructions: Do not apply on thermoplastic substrates.