

**Intended use**









Mipa 2K-Löser is a special mixture of solvents (fade-out thinner) to "melt" edges of spot repairs and fade-out areas. Mipa 2K-HS-Löser can also be used to dissolve an old paintworks (Attention: test suitability to avoid unwanted wrinkling/raising of old paintwork) in order to improve the adhesion of the subsequent coating. In this case, Mipa 2K-Löser must be applied uniformly on the old paintwork and recoated within a few minutes. Mipa 2K-Löser can be used as fade-out thinner in combination with following products:

Mipa AC, Mipa PUR, Mipa OC, Mipa 2K-MS-Klarlacke

After having applied one of these products, spray immediately Mipa 2K-Löser over the border areas (overspray areas). Melt the overspray edges with a very uniform coat of Mipa 2K-Löser until the rough overspray become visibly smooth. Do not apply too much, otherwise irregular dissolving or runs are to be expected.

Spreading rate: --

**Processing instructions**

	<b>Colour</b> colourless					
	<b>Mixing ratio</b>	<b>Hardener</b>		<b>by weight (lacquer : hardener)</b>	<b>by volume (lacquer : hardener)</b>	
	--	--	--	--	--	
	<b>Hardener</b>	<b>for complete paintwork</b>		<b>for partial paintwork</b>		
	--	--		--		
	<b>Pot life</b> --					
	<b>Thinner</b> ready for use					
	<b>Spray viscosity</b>	<b>Gravity spray gun</b>		<b>Airmix/Airless</b>		
	--	--		--		
	<b>Application method</b>	<b>Application method</b>	<b>Hardener</b>	<b>Pressure (bar)</b>	<b>Nozzle (mm)</b>	<b>spray passes</b>
	--	--	--	--	--	--
	<b>Flash-off time</b> --					

<b>Dry coat thickness</b>						
--						



**Drying time**

<b>Object temperature</b>	<b>dust dry</b>	<b>set to touch</b>	<b>ready for assembly</b>	<b>sandable</b>	<b>recoatable</b>
--	--	--	--	--	--

**Note**

- Storage:** at least 4 years in unopened original containers
- VOC Regulation :** --
- Processing conditions:** from +10 °C and up to 80 % relative air humidity. Ensure an adequate supply and exhaust air ventilation.
- Processing instructions:** Do not apply on thermoplastic substrates.