2K Structure Hardener A 61

Technical data sheet

Intended use

Mipa 2K Structure Hardener A 61 is a special 2K hardener for use with Mipa textured paints applied in interior and exterior areas.

Processing instructions

Mixing ratio

hardener	by weight (lacquer : hardener)	by volume (lacquer : hardener)
See basic product	--	--

Hardener

--

Pot life

See basic product

Thinner

See basic product

Processing viscosity

See basic product

gravity spray gun	Airmix/Airless
--	--

Application mode

application mode	hardener	pressure (bar)	nozzle (mm)	spray passes	dilution
See basic product	--	--	--	--	--

Drying time

hardener	object temperature	dust dry	set to touch	ready for assembly	sandable	recoatable
See basic product	--	--	--	--	--	--

Note

Characteristics:

binder base:	Polyisocyanate
solids content (% by weight):	~ 66
solids content (% by volume):	--
delivery viscosity DIN 53211 4 mm (in s):	24 - 26
density DIN EN ISO 2811 (kg/l):	~ 1,1
gloss level ISO 2813 at 60° (GU):	See basic product

Properties: See basic product

Theoretical spreading rate: See basic product

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

MIPA SE · Am Oberen Moos 1 · D-84051 Essenbach · Tel.: +49 8703 92 20 · Fax: +49 8703 92 21 00 · mipa@mipa-paints.com · www.mipa-paints.com

Storage:	For at least 2 years in the unopened original container. Optimum storage conditions between + 5 °C and + 25 °C, avoid direct sunlight. Other storage conditions may lead to undesirable properties of the material.
VOC:	See basic product
Processing conditions:	See basic product
Substrate preparation:	see basic product
Proposed coating structure:	See basic product
Special notes:	For professional use only. This hardener reacts with moisture, therefore the container must be closed immediately after taking out the material.
Cleaning of tools:	Clean tools immediately after use with Mipa Nitroverdünnung .

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

MIPA SE · Am Oberen Moos 1 · D-84051 Essenbach · Tel.: +49 8703 92 20 · Fax: +49 8703 92 21 00 · mipa@mipa-paints.com · www.mipa-paints.com