










### Intended use

Mipa 2K-Verdünnung kurz V 10 is a mixture of organic solvent with accelerated evaporation for use in Mipa 2K primers, 2K topcoats and 2K clearcoats. This thinner accelerates the drying when coating small objects and / or at lower ambient temperatures. For further information on use and recommended dosage, please refer to the respective technical data sheet of the basic products.

Spreading rate: --

### Processing instructions

	<b>Colour</b> colourless					
	<b>Mixing ratio</b> <b>Hardener</b>		<b>by weight (lacquer : hardener)</b>		<b>by volume (lacquer : hardener)</b>	
	--	--	--	--	--	--
	<b>Hardener</b> <b>for complete paintwork</b>				<b>for partial paintwork</b>	
	--	--	--	--	--	--
	<b>Pot life</b>					
	--	--	--	--	--	--
	<b>Thinner</b>					
	--	--	--	--	--	--
	<b>Spray viscosity</b> <b>gravity spray gun</b>				<b>Airmix/Airless</b>	
	--	--	--	--	--	--
	<b>Application mode</b> <b>Application mode</b>	<b>Hardener</b>	<b>pressure (bar)</b>	<b>nozzle (mm)</b>	<b>spray passes</b>	<b>Thinner</b>
	--	--	--	--	--	--
	<b>Flash-off time</b>					
	--	--	--	--	--	--
	<b>Dry coat thickness</b>					
	--	--	--	--	--	--
	<b>Drying time</b> <b>object temperature</b>	<b>dust dry</b>	<b>set to touch</b>	<b>ready for assembly</b>	<b>sandable</b>	<b>recoatable</b>
	--	--	--	--	--	--

---

### Note

---

- Storage:** at least 3 years in unopened original container
- VOC Regulation :** --
- Processing conditions:** From +10 °C and up to 80 % relative air humidity. Ensure an adequate air ventilation.
- Processing instructions:** Keep containers tightly closed.
- Do not process or store near open flames, sources of heat or ignition.
- The material may become electrostatically charged, therefore earth it properly before removing.