










### Intended use

Mipa 2K-Verdünnung lang V 40 is a mixture of organic solvent with delayed evaporation for use in Mipa 2K primers, 2K topcoats and 2K clearcoats. This thinner improves flow and spray mist absorption when coating objects with large surfaces and / or at higher ambient temperatures. For further information on use and recommended dosage, please refer to the respective technical data sheet of the basic products.

Spreading rate: --

### Processing instructions

	<b>Colour</b> colourless					
	<b>Mixing ratio</b>					
	<b>Hardener</b>		<b>by weight (lacquer : hardener)</b>	<b>by volume (lacquer : hardener)</b>		
	--	--	--	--		
	<b>Hardener</b>					
	<b>for complete paintwork</b>			<b>for partial paintwork</b>		
	--	--	--	--		
	<b>Pot life</b>					
	--					
	<b>Thinner</b>					
	--					
	<b>Spray viscosity</b>					
	<b>gravity spray gun</b>			<b>Airmix/Airless</b>		
	--	--	--	--		
	<b>Application mode</b>					
	<b>Application mode</b>	<b>Hardener</b>	<b>pressure (bar)</b>	<b>nozzle (mm)</b>	<b>spray passes</b>	<b>Thinner</b>
	--	--	--	--	--	--
	<b>Flash-off time</b>					
	--					
	<b>Dry coat thickness</b>					
	--					
	<b>Drying time</b>					
	<b>object temperature</b>	<b>dust dry</b>	<b>set to touch</b>	<b>ready for assembly</b>	<b>sandable</b>	<b>recoatable</b>
	--	--	--	--	--	--

---

### Note

---

- Storage:** at least 3 years in unopened original container
- VOC Regulation :** --
- Processing conditions:** From +10 °C and up to 80 % relative air humidity. Ensure an adequate air ventilation.
- Processing instructions:** Keep containers tightly closed.
- Do not process or store near open flames, sources of heat or ignition.
- The material may become electrostatically charged, therefore earth it properly before removing.