

### Intended use

Mipa Klebstoffentferner dissolves any kind of adhesive bonds such like wood glue, dispersion adhesive, glue for foam, universal adhesive, adhesive residues of floorings and tapes and so on. Furthermore Mipa Klebstoffentferner can also be used to remove oil and grease from metal, wood, stone or glass substrates.









Use:

In case of little adhesive residue use a cloth impregnated with Mipa Klebstoffentferner and remove any residue by wiping.

In case of larger adhesive residue apply Mipa Klebstoffentferner and allow to take effect for about 10-20 minutes. Then remove carefully the softened coats using a scraper. Repeat this procedure in case of stubborn contaminations. But ensure an adequate ventilation to avoid any formation of solvent vapour.

Spreading rate: --


### Processing instructions

	<b>Colour</b>	--				
	<b>Mixing ratio</b>					
	<b>Hardener</b>	<b>by weight (lacquer : hardener)</b>		<b>by volume (lacquer : hardener)</b>		
	--	--	--	--	--	
	<b>Hardener</b>					
	<b>for complete paintwork</b>	<b>for partial paintwork</b>				
	--	--				
	<b>Pot life</b>	--				
	<b>Thinner</b>	--				
	<b>Spray viscosity</b>					
	<b>Gravity spray gun</b>	<b>Airmix/Airless</b>				
	--	--				
	<b>Application method</b>					
	<b>Application method</b>	<b>Hardener</b>	<b>Pressure (bar)</b>	<b>Nozzle (mm)</b>	<b>spray passes</b>	<b>Thinner</b>
	--	--	--	--	--	--
	<b>Flash-off time</b>	--				

Version: en 0217

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

MIPA SE · Am Oberen Moos 1 · D-84051 Essenbach · Tel.: +49(0)87 03/922-0 · Fax: +49(0)87 03/922-100 · mipa@mipa-paints.com · www.mipa-paints.com

<b>Dry coat thickness</b>						
--						
	<b>Drying time</b>					
	<b>Object temperature</b>	<b>dust dry</b>	<b>set to touch</b>	<b>ready for assembly</b>	<b>sandable</b>	<b>recoatable</b>
	--	--	--	--	--	--

**Note**

**Storage:** at least 4 years in unopened original container

**VOC Regulation :**

**Processing conditions:** from +10 °C and up to 80 % relative air humidity. Ensure an adequate supply and exhaust air ventilation.

**Processing instructions:** Before starting the cleaning it is recommended to test the cleaning efficiency and the substrate resistance to Mipa Klebstoffentferner in an inconspicuous place. Allow surfaces that have been treated with Mipa Klebstoffentferner to dry for several hours before processing.