








Intended use

Mipa PU 955-25 (BAZ94-0007) is a special hardener for the application of selected Mipa 2K-PU paints.

Processing instructions

| | | | | | | | |
|---|---------------------------------|---------------------------|--------------------------------|--------------------------------|---------------------------|-----------------|-------------------|
|  | Mixing ratio hardener | | | | | | |
| | See basic product | | by weight (lacquer : hardener) | by volume (lacquer : hardener) | | | |
| | | | -- | -- | | | |
|  | Hardener | | | | | | |
| | -- | | | | | | |
|  | Pot life | | | | | | |
| | See basic product | | | | | | |
|  | Thinner | | | | | | |
| | See basic product | | | | | | |
|  | Processing viscosity | | | | | | |
| | See basic product | | | | | | |
| | gravity spray gun | | | Airmix/Airless | | | |
| | -- | | | -- | | | |
|  | Application mode | | | | | | |
| | application mode | hardener | pressure (bar) | nozzle (mm) | spray passes | dilution | |
| | See basic product | -- | -- | -- | -- | -- | |
|  | Drying time | | | | | | |
| | hardener | object temperature | dust dry | set to touch | ready for assembly | sandable | recoatable |
| | See basic product | -- | -- | -- | -- | -- | -- |

Note

| | | |
|-------------------------|---|-------------------|
| Characteristics: | binder base: | Polyisocyanate |
| | solids content (% by weight): | ~ 75 |
| | solids content (% by volume): | -- |
| | delivery viscosity DIN 53211 4 mm (in s): | 45 - 55 |
| | density DIN EN ISO 2811 (kg/l): | ~ 1,2 |
| | gloss level ISO 2813 at 60° (GU): | See basic product |

Properties: See basic product

Theoretical spreading rate: See basic product

| | |
|------------------------------------|---|
| Storage: | For at least 2 years in the unopened original container. Optimum storage conditions between + 5 °C and + 25 °C, avoid direct sunlight. Other storage conditions may lead to undesirable properties of the material. |
| VOC: | See basic product |
| Processing conditions: | See basic product |
| Substrate preparation: | See basic product |
| Proposed coating structure: | See basic product |
| Special notes: | For professional use only. |
| Cleaning of tools: | Clean tools immediately after use with Mipa Nitroverdünnung. |