



Mipa Acryl-Lackspray

Agricultural and Building Machinery Colours

Product Information

D - 2/0119

Art.Nr.: 21400 + Colour Ref. Nr.

Mipa Acryl-Lackspray is a fast drying high quality 1K-acrylic paint. Scratch and shock resistant. Available in various agricultural and building machinery colours as well as commercial vehicle colours. Especially suited for the perfect colour matched finish and for all repair work.



Substrate:

Fully hardened and sanded old paint work.
Thoroughly dry Mipa 1K and 2K Filler materials.



Pretreatment / Cleansing:

Vorreinigung mit Mipa Silikonentferner

Characteristics:

Fast drying, scratch and shock resistant.
Lightfast and non-yellowing,
Strong surface hardness
Excellent coverage and high opacity

Colour / Grade of Gloss:

Various standard colours - see product catalogue "MIPA Aerosols"

Preparation:



Shake can vigorously until the mixing balls move freely!

Application:



Spray to test - Spraying distance approx. 20 - 30 cm
2 - 3 coats, dry film thickness 40 - 50 µm.

Flash-off:



3 - 5 min. between each coating

After use:



Turn can upside down and spray until the valve is clean, this prevents the valve from clogging up.

Drying Times:



Drying:

Dust dry:

10 min. / 20°C

Set to touch:

1 - 2 h / 20°C

Full hardness:

12 h / 20°C

Processing Conditions:

From +10°C and up to 80% relative air humidity

Storage:

In tightly closed original containers at least 2 years shelf life

VOC- Regulation:

EU limiting value for the product (cat. B/e): 840 g/l (2007)
This product contains max. 840 g/l VOC [7.01 lbs/gal]

Safety Information:

Read the corresponding Material Safety Data Sheet

The data sheet is for information purpose only! The information given is in accordance to our knowledge up to the latest standards and is based on years of experience in the manufacture of our products. The information is non binding and without guarantee.