

# Mipa Converter-Prefilled-Spray

Item no 21209 0000

Technical data sheet

page 1 / 2

## Intended use

Mipa Converter-Prefilled-Spray is pre-filled with propellant gas and a converter. This allows direct filling with 2K topcoats without prior addition of a converter. Customary acrylic and polyurethane-based 2K topcoat systems are suitable for filling. Mipa Converter-Prefilled-Spray can be filled individually. The technical properties of the paint largely correspond to those of the paint filled in, with the exception of the chemical hardener cross-linking. Since this does not take place, the topcoat filled in corresponds to a 1K quality in terms of chemical and mechanical resistance. The specialist dealer (seller) is liable for the final product!

## Processing instructions



### Substrates

depends on the product, see processing instructions of the paint filled in

### Pre-treatment / cleansing

depends on the product, see processing instructions of the paint filled in

### Characteristics

Paint system is filled in the spray can by means of a filling machine  
Equipped with an adjustable sprayhead for fine atomisation  
Versatile application

## Colour / gloss level

depends on the product, see processing instructions of the paint filled in



### Preparation


Fill Mipa Converter-Prefilled-Spray with 100 ml basic paint of the selected paint quality

After having filled the can and before use, shake can vigorously for 1 - 2 min!



### Application

depends on the product, see processing instructions of the paint filled in



### Flash-off time

depends on the product, see processing instructions of the paint filled in



### After use

After use, turn can upside down and spray until the valve is clean, this prevents the valve from clogging up.

Version: en 0322

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

MIPA SE · Am Oberen Moos 1 · D-84051 Essenbach · Tel.: +49 8703 92 20 · Fax: +49 8703 92 21 00· mipa@mipa-paints.com · www.mipa-paints.com



## Drying time at 20 °C

depends on the product, see processing instructions of the paint filled in

**Processing conditions** depends on the product, see processing instructions of the paint filled in

**Storage** Can be stored for 2 years in cool and dry places.

**VOC-regulation** EU limit value for this product (cat. B/e): 840 g/l  
This product contains max. 840 g/l of VOC.

**Safety information** See safety data sheet