# Mipa Linienmarkierer Profi

Item no 68210 + Colour no **Technical data sheet** 



### Intended use

Mipa Linienmarkierer Profi is a fast-drying special paint for professional use. The excellent adhesion provides a durable and hard wearing line mark. Superior coverage and sharp edges can be achieved in conjunction with our line marking trolleys "Allround" and "Standard". Especially suitable for the marking and line marking of car parks, in the private sector as well as for safety markings in the industry.

### Processing conditions



#### Substrates

Stone, concrete, etc. Also suitable for absorbent and damp substrates.

# Pre-treatment / cleansing

If possible, the substrate should be clean and free of grease.

# Characteristics Highly opaque, fast

Highly opaque, fast-drying quality For permanent markings (durability of the marking depends on the substrate, location: e.g. indoors or outdoors, the daily stress, etc.) Highly resistant to abrasion

Colour / gloss level

White, traffic yellow, traffic blue, traffic red, traffic green / matt



Preparation Before use, shake can vigorously for 1 - 2 min!



Application Spray to test - spray distance approx. 20 - 30 cm

## Flash-off time

\_



After use Self-cleaning system, therefore the spray can can be emptied 100 %.

Version: en 0322

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

MIPA SE · Am Oberen Moos 1 · D-84051 Essenbach · Tel.: +49 8703 92 20 · Fax: +49 8703 92 21 00 · mipa@mipa-paints.com · www.mipa-paints.com



	Drying times at 20 °C	
	Dust dry after approx.	10 min
	Set to touch after approx.	30 min
	Resistant after approx.	24 h
	Overcoatable after approx.	24 h
Processing conditions	From +10 °C and up to 60 % relative humidity. Ensure adequate air ventilation.	
Storage	Can be stored for 5 years in cool and dry places.	
VOC-regulation	EU limit value for the product (cat. B/e): 840 g/l This product contains max. 800 g/l of VOC.	
Safety information	See safety data sheet	
Processing instructions		

Use our marking trolley (Markierungswagen Profi), the line marking applicator (Markierungsstock) or our marking pistol (Markierungspistole) for applying Mipa Linienmarkierer Profi.

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

MIPA SE · Am Oberen Moos 1 · D-84051 Essenbach · Tel.: +49 8703 92 20 · Fax: +49 8703 92 21 00 · mipa@mipa-paints.com · www.mipa-paints.com