

Product description

Operational Sector :	Water-based priming agent for insulation the gypsum substrates by subsequent use of paints on silicate basis Mipa Silikatfarben.		
Features :	<ul style="list-style-type: none"> - free of solvents, low emissions - free of plasticizers 		
Content :	Synthetic dispersion, water, additives, preserving agent.		
Colour :	transparent		
Specification :	gloss:	mat	DIN 67 530
	spec. weight:	1.00 g/cm ³	DIN 51 757
	viscosity:	15 s 4 mm	DIN 53 211
	pH-value:	7.6	DIN 53 785
Storage :	At least 2 years, if the tightly closed original packages are kept dry, protected against frost. Storage temperature: from +5°C till maximum +30°C.		
VOC legislation:	EU limiting value for the product (cat. A/g): 50 g/l (2007)/ 30 g/l (2010) This product contains max. 8 g/l VOC [0.06 lbs/gal]		

Application

Processing conditions :	Do not apply below + 5 °C and more than + 35° C temperature of the object or the environment. Avoid direct sunlight and strong wind.
Substrate preparation :	The substrate has to be clean, dry, firm and sound. In case of humid surfaces, find the leakage and wait till dry.
Dilution :	Ready for use;
Application process :	Brushing, rolling or spraying
Drying :	At 20° C and 65% relative air humidity after approx. 12 h set to touch and recoatable. Prolonged drying times after application due to lower temperature conditions.
Spreading rate :	Approx. 8 - 10 m ² / l on level, even surfaces; 4 - 6 m ² / l on rough, strong absorbing substrates.

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

Special remarks

Stir well before application. Apply in even, smooth coats. Avoid shiny spots.

Safety instructions

Mipa Silikat-Gipsgrundiermittel is slightly alkaline. Protect eyes and sensitive skin against product. In case of contact with skin, rinse immediately with plenty of water. Consider general hygienic rules.

Cleaning of tools

Tools should be cleaned immediately after use or after longer breaks with water.

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.