## Mipa WBS Reiniger

Technical data sheet

Page 1 / 2



ı	nto	nd	امطا	use
ı	IILG	ııu	CU	use

Mipa WBS Reiniger is a low-odour and VOC-compliant (less than 20 % solvent) waterborne degreasing agent for cleaning metal and plastic substrates, filled surfaces and slightly sanded old paintworks. It can be applied by paint brush, brush, cloth, sponge and by spraying. Use a clean and dry rag to remove Mipa WBS Reiniger after application.

Spreading rate: --

_			
Proce	ssina	instru	ctions
FIULE	วอแเน	แเจนน	GLIUII.



#### Colour

colourless



## Mixing ratio

Hardener by weight (lacquer : hardener) by volume (lacquer : hardener)



#### Hardener

for complete paintwork for partial paintwork

--



### Pot life

--



## **Thinner**

\_\_



# Spray viscosity

gravity spray gun Airmix/Airless

## **Application mode**

Application mode Hardener pressure nozzle (mm) spray Thinner (bar) passes

\_ \_ \_ \_ \_



### Flash-off time

--

## Dry coat thickness

--



# Drying time

object dust dry set to ready for sandable recoatable temperature touch assembly

Version: en 1219

# Mipa WBS Reiniger

### Technical data sheet

Page 2 / 2



Note

**Storage:** iat least 4 years in unopened original container.

**VOC Regulation :** EU limit value for this product (category B/a): 200 g/l

This product contains max. 189 g/l of VOC.

Processing conditions: -

**Processing instructions:** Don't allow Mipa WBS Reiniger to dry on the surface. Allow cleaned surfaces to

evaporate well before further processing. Use compressed air to blow away residual moisture in edges, crimps and grooves. Mipa WBS Reiniger may contain floating particles, which is not a quality defect as these particles are readily dissolved by

shaking the before use.