

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.07.2023

Version number 11 (replaces version 10)

Revision: 03.07.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Mipa 1K-UV-Füller**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Product category PC9a** Coatings and paints, thinners, paint removers
- **Application of the substance / the mixture** Filler
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
MIPA SE  
Am Oberen Moos 1  
D-84051 Essenbach  
Tel.: +49(0)8703-922-0  
Fax.: +49(0)8703-922-100  
e-mail: sdb-registratur@mipa-paints.com  
www.mipa-paints.com
- **1.4 Emergency telephone number:** International emergency number: +49(0)700 24112112 (MIP)

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 2      H225 Highly flammable liquid and vapour.



health hazard

Repr. 1B      H360 May damage fertility or the unborn child.



corrosion

Eye Dam. 1      H318 Causes serious eye damage.



Skin Sens. 1      H317 May cause an allergic skin reaction.

STOT SE 3      H336 May cause drowsiness or dizziness.

Aquatic Chronic 3      H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02



GHS05



GHS07



GHS08

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 03.07.2023

Version number 11 (replaces version 10)

Revision: 03.07.2023

**Trade name: Mipa 1K-UV-Füller**

(Contd. of page 1)

 · **Signal word** Danger

 · **Hazard-determining components of labelling:**

Dipropylenglocyl diacrylate

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid

Ethyl acetate

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

 · **Hazard statements**

H225 Highly flammable liquid and vapour.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H360 May damage fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

 · **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

 · **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

Restricted to professional users.

 · **2.3 Other hazards**

 · **Results of PBT and vPvB assessment**

 · **PBT:** Not applicable.

 · **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

 · **3.2 Mixtures**

 · **Description:** Mixture of substances listed below with nonhazardous additions.

 · **Dangerous components:**

CAS: 55818-57-0 NLP: 500-130-2 Reg.nr.: 01-2119490020-53	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid ⚠ Aquatic Chronic 2, H411; ⚠ Skin Sens. 1, H317	≥10-<25%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46	Ethyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-25%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≥10-<15%
CAS: 57472-68-1 EINECS: 260-754-3 Reg.nr.: 01-2119484629-21	Dipropylenglocyl diacrylate ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	≥3-<10%
CAS: 1187441-10-6 EC number: 810-703-1 Reg.nr.: 01-2120140608-57	2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide ⚠ Eye Dam. 1, H318; ⚠ Skin Sens. 1B, H317	≥3-<10%

(Contd. on page 3)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 03.07.2023

Version number 11 (replaces version 10)

Revision: 03.07.2023

**Trade name: Mipa 1K-UV-Füller**

		(Contd. of page 2)
CAS: 444649-70-1	Reaction mass of neo-Decanoic acid, 2-oxyranylmethylester and 2-propenoic acid ⚠ Aquatic Chronic 2, H411	2.5-<10%
CAS: 162881-26-7 ELINCS: 423-340-5 Reg.nr.: 01-2119489401-38	phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide ⚠ Skin Sens. 1A, H317; Aquatic Chronic 4, H413	≥1-<2.5%
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43	ethanol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50%	<2.5%
CAS: 75980-60-8 EINECS: 278-355-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide ⚠ Repr. 1B, H360; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Sens. 1B, H317	≥0.3-<1%
CAS: 52408-84-1 NLP: 500-114-5 Reg.nr.: 01-2119487948-12	Glycerol, propoxylated, esters with acrylic acid ⚠ Eye Irrit. 2, H319; Skin Sens. 1, H317	≥0.1-<1%
CAS: 7779-90-0 EINECS: 231-944-3 Reg.nr.: 01-2119485044-40	Trizinc bis(orthophosphate) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.025-<0.25%
CAS: 128-37-0 EINECS: 204-881-4 Reg.nr.: 01-2119555270-46	Butylated hydroxytoluene ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.025-<0.25%
CAS: 108-88-3 EINECS: 203-625-9 Reg.nr.: 01-2119471310-51	Toluene ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	<1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**  
 Supply fresh air and to be sure call for a doctor.  
 In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:**  
 Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**  
 No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
 No further relevant information available.

## SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
 CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
 No further relevant information available.

(Contd. on page 4)

**Trade name: Mipa 1K-UV-Füller**

(Contd. of page 3)

- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralising agent.  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
Keep away from heat and direct sunlight.  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**  
Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**141-78-6 Ethyl acetate**

WEL	Short-term value: 1468 mg/m <sup>3</sup> , 400 ppm Long-term value: 734 mg/m <sup>3</sup> , 200 ppm
-----	--

**67-64-1 acetone**

WEL	Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm
-----	--

(Contd. on page 5)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 03.07.2023

Version number 11 (replaces version 10)

Revision: 03.07.2023

**Trade name: Mipa 1K-UV-Füller**

(Contd. of page 4)

**64-17-5 ethanol**

 WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm

**128-37-0 Butylated hydroxytoluene**

 WEL Long-term value: 10 mg/m<sup>3</sup>
**108-88-3 Toluene**

 WEL Short-term value: 384 mg/m<sup>3</sup>, 100 ppm  
 Long-term value: 191 mg/m<sup>3</sup>, 50 ppm  
 Sk

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Hand protection**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Breakthrough time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Tightly sealed goggles

GB

(Contd. on page 6)

**Trade name: Mipa 1K-UV-Füller**

(Contd. of page 5)

**SECTION 9: Physical and chemical properties**

**· 9.1 Information on basic physical and chemical properties**

**· General Information**

· <b>Physical state</b>	Fluid
· <b>Colour:</b>	According to product specification
· <b>Odour:</b>	Characteristic
· <b>Odour threshold:</b>	Not determined.
· <b>Melting point/freezing point:</b>	Undetermined.
· <b>Boiling point or initial boiling point and boiling range</b>	56 °C (67-64-1 acetone)
· <b>Flammability</b>	Highly flammable.
· <b>Lower and upper explosion limit</b>	
· <b>Lower:</b>	2.1 Vol % (141-78-6 Ethyl acetate)
· <b>Upper:</b>	13 Vol % (67-64-1 acetone)
· <b>Flash point:</b>	-17 °C (DIN EN ISO 1523:2002, 67-64-1 acetone)
· <b>Auto-ignition temperature:</b>	460 °C (DIN 51794, 141-78-6 Ethyl acetate)
· <b>Decomposition temperature:</b>	Not determined.
· <b>pH</b>	Not determined.
· <b>Viscosity:</b>	
· <b>Kinematic viscosity at 20 °C</b>	20-30 s (DIN 53211/4)
· <b>Dynamic:</b>	Not determined.
· <b>Solubility</b>	
· <b>water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
· <b>Vapour pressure at 20 °C:</b>	233 hPa (67-64-1 acetone)
· <b>Vapour pressure at 50 °C:</b>	800 hPa
· <b>Density and/or relative density</b>	
· <b>Density at 20 °C:</b>	1.265 g/cm <sup>3</sup> (DIN EN ISO 2811-1)
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.

**· 9.2 Other information**

· <b>Appearance:</b>	
· <b>Form:</b>	Fluid
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Ignition temperature:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Solvent content:</b>	
· <b>Water:</b>	0.1 %
· <b>VOC (EC)</b>	28.61 %
· <b>Solids content (weight-%):</b>	71.2 %
· <b>Change in condition</b>	
· <b>Evaporation rate</b>	Not determined.

**· Information with regard to physical hazard classes**

· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Void
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Highly flammable liquid and vapour.
· <b>Flammable solids</b>	Void

(Contd. on page 7)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.07.2023

Version number 11 (replaces version 10)

Revision: 03.07.2023

Trade name: Mipa 1K-UV-Füller

(Contd. of page 6)

· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Reproductive toxicity** May damage fertility or the unborn child.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

#### · Endocrine disrupting properties

128-37-0 Butylated hydroxytoluene

List II

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**  
For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) : hazardous for water

(Contd. on page 8)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 03.07.2023

Version number 11 (replaces version 10)

Revision: 03.07.2023

**Trade name: Mipa 1K-UV-Füller**

(Contd. of page 7)

Do not allow product to reach ground water, water course or sewage system.  
 Must not reach sewage water or drainage ditch undiluted or unneutralised.  
 Danger to drinking water if even small quantities leak into the ground.  
 Harmful to aquatic organisms

**SECTION 13: Disposal considerations**
**13.1 Waste treatment methods**
**Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**Uncleaned packaging:**
**Recommendation:**

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

**SECTION 14: Transport information**
**14.1 UN number or ID number**
**ADR, IMDG, IATA**

UN1263

**14.2 UN proper shipping name**
**ADR**

UN1263 PAINT

**IMDG, IATA**

PAINT

**14.3 Transport hazard class(es)**
**ADR**

**Class**

3 (F1) Flammable liquids.

**Label**

3

**IMDG, IATA**

**Class**

3 Flammable liquids.

**Label**

3

**14.4 Packing group**
**ADR, IMDG, IATA**

II

**14.5 Environmental hazards:**

Not applicable.

**14.6 Special precautions for user**

Warning: Flammable liquids.

**Hazard identification number (Kemler code):**

33

**EMS Number:**

F-E, S-E

**Stowage Category**

B

**14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

(Contd. on page 9)



**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 03.07.2023

Version number 11 (replaces version 10)

Revision: 03.07.2023

**Trade name: Mipa 1K-UV-Füller**

(Contd. of page 8)

**· Transport/Additional information:**
**· ADR**

- Limited quantities (LQ) 5L
- Transport category 2
- Tunnel restriction code D/E

**· IMDG**

- Limited quantities (LQ) 5L

- UN "Model Regulation": UN 1263 PAINT, 3, II

**SECTION 15: Regulatory information**
**· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

**· National regulations:**

- Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	25-50

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H360 May damage fertility or the unborn child.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.
- EUH066 Repeated exposure may cause skin dryness or cracking.

**· Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

**· Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 10)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.07.2023

Version number 11 (replaces version 10)

Revision: 03.07.2023

**Trade name: Mipa 1K-UV-Füller**

(Contd. of page 9)

IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 VOC: Volatile Organic Compounds (USA, EU)  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Liq. 2: Flammable liquids – Category 2  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 Skin Sens. 1: Skin sensitisation – Category 1  
 Skin Sens. 1A: Skin sensitisation – Category 1A  
 Skin Sens. 1B: Skin sensitisation – Category 1B  
 Repr. 1B: Reproductive toxicity – Category 1B  
 Repr. 2: Reproductive toxicity – Category 2  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
 Asp. Tox. 1: Aspiration hazard – Category 1  
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1  
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3  
 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4  
 \* **Data compared to the previous version altered.**

GB