Revision: 20.11.2023



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.11.2023

Version number 6 (replaces version 5)

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Mipa 1K-UV-Klarlack
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Clear coating material, Varnish
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49 8703 92 20 Fax.: +49 8703 92 21 00

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

• 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 1B H360 May damage fertility or the unborn child.



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 20.11.2023 Version number 6 (replaces version 5) Revision: 20.11.2023

Trade name: Mipa 1K-UV-Klarlack

(Contd. of page 1)

#### · Hazard pictograms











GHS02 GHS05 GHS07 GHS08 GHS

### · Signal word Danger

#### · Hazard-determining components of labelling:

Hexane, 1,6-diisocyanato-, polymer with 2-Propenoic acid, reaction products with pentaerythritol, 2-hydroxyethyl acrylate-blocked

Ethyl acetate

diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide

2,2-bis(acryloyloxymethyl)butyl acrylate

#### Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

· Additional information:

Restricted to professional users.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

#### · 3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 141-78-6 EINECS: 205-500-4	Ethyl acetate  The property of the state of	25-50%
Reg.nr.: 01-2119475103-46	H336, EUH066 Hexane, 1,6-diisocyanato-, polymer with 2-Propenoic	>10-<25%
	acid, reaction products with pentaerythritol, 2-hydroxyethyl acrylate-blocked	210-1207
	<ul> <li>Eye Dam. 1, H318;</li> <li>Aquatic Chronic 2, H411;</li> <li>Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317</li> </ul>	

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 20.11.2023 Version number 6 (replaces version 5) Revision: 20.11.2023

Trade name: Mipa 1K-UV-Klarlack

	(C	contd. of page 2)
CAS: 13048-33-4	hexamethylene diacrylate	≥10-<25%
EINECS: 235-921-9	Aquatic Acute 1, H400; Aquatic Chronic 2, H411;	
Reg.nr.: 01-2119484737-22		
	H317	
CAS: 15625-89-5	2,2-bis(acryloyloxymethyl)butyl acrylate	2.5-<10%
EINECS: 239-701-3	Carc. 2, H351; 鉖 Aquatic Acute 1, H400; Aquatic	
Reg.nr.: 01-2119489896-11		
	Skin Sens. 1, H317	
CAS: 75980-60-8	diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide	2.5-<10%
EINECS: 278-355-8	Repr. 1B, H360; Aquatic Chronic 2, H411; Skin Sens. 1B, H317	
CAS: 1065336-91-5	Reaction mass of pentamethyl-piperidylsebacate	≥0.25-<1%
EC number: 915-687-0	♦ Repr. 2, H361f; ♦ Aquatic Acute 1, H400; Aquatic	
Reg.nr.: 01-2119491304-40	Chronic 1, H410; ( ) Skin Sens. 1A, H317	
· Additional information: Fo	r the wording of the listed hazard phrases refer to section 1	6.

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 20.11.2023 Version number 6 (replaces version 5) Revision: 20.11.2023

Trade name: Mipa 1K-UV-Klarlack

(Contd. of page 3)

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

### · 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

### 141-78-6 Ethyl acetate

WEL Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Revision: 20.11.2023 Printing date 20.11.2023 Version number 6 (replaces version 5)

Trade name: Mipa 1K-UV-Klarlack

(Contd. of page 4)

#### · Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range 77-78 °C (141-78-6 Ethyl acetate) · Flammability Highly flammable.

· Lower and upper explosion limit

· Lower: 2.1 Vol % (141-78-6 Ethyl acetate) Upper: 11.5 Vol % (141-78-6 Ethyl acetate) -4 °C (DIN EN ISO 1523:2002) · Flash point:

235 °C (DIN 51794, 13048-33-4 hexamethylene · Auto-ignition temperature:

diacrylate) Not determined.

· Decomposition temperature: Not determined. · pH

· Viscosity:

15-20 s (DIN 53211/4) · Kinematic viscosity at 20 °C Not determined. · Dynamic:

· Solubility

· water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log

value) Not determined.

· Vapour pressure at 20 °C: 97 hPa (141-78-6 Ethyl acetate)

· Vapour pressure at 50 °C: 360 hPa

· Density and/or relative density

· Density at 20 °C: 1.021 g/cm3 (DIN EN ISO 2811-1)

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Printing date 20.11.2023 Version number 6 (replaces version 5) Revision: 20.11.2023

Trade name: Mipa 1K-UV-Klarlack

(Contd. of page 5)

• Relative density Not determined. • Vapour density Not determined.

9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

• **Ignition temperature:** Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

• **VOC (EC)** 37.60 % • **Solids content (weight-%):** 62.4 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard

classes

· Explosives

· Flammable gases

· Aerosols

· Oxidising gases

· Gases under pressure

Void

Void

Flammable liquids Highly flammable liquid and vapour.

Flammable solids
Self-reactive substances and mixtures
Pyrophoric liquids
Void
Pyrophoric solids
Void
Self-heating substances and mixtures
Substances and mixtures, which emit

flammable gases in contact with water

Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Oxidised explosives
Void
Void

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Carbon monoxide

### **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye damage.

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 20.11.2023 Version number 6 (replaces version 5) Revision: 20.11.2023

Trade name: Mipa 1K-UV-Klarlack

(Contd. of page 6)

- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Carcinogenicity Suspected of causing cancer.
- · Reproductive toxicity May damage fertility or the unborn child.
- STOT-single exposure May cause drowsiness or dizziness.

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information				
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1263			
· 14.2 UN proper shipping name				
ADR	UN1263 PAINT, ENVIRONMENTALL HAZARDOUS			
· IMDG	PAINT (hexamethylene diacrylate), MARIN POLLUTANT			
·IATA	PAINT			

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 20.11.2023 Version number 6 (replaces version 5) Revision: 20.11.2023

Trade name: Mipa 1K-UV-Klarlack

(Contd. of page 7) · 14.3 Transport hazard class(es) · ADR · Class 3 (F1) Flammable liquids. · Label · IMDG 3 Flammable liquids. · Class · Label ·IATA · Class 3 Flammable liquids. · Label 3 · 14.4 Packing group · ADR, IMDG, IATA II· 14.5 Environmental hazards: Product contains environmentally hazardous substances: diphenyl(2,4,6- trimethylbenzoyl) phosphine oxide Symbol (fish and tree) · Marine pollutant: Symbol (fish and tree) Special marking (ADR): · 14.6 Special precautions for user Warning: Flammable liquids. · Hazard identification number (Kemler code): 33 · EMS Number: F-E,<u>S-E</u> · Stowage Category В · 14.7 Maritime transport in bulk according to **IMO** instruments Not applicable. · Transport/Additional information: · ADR Limited quantities (LQ) 5L 2 · Transport category Tunnel restriction code D/E · IMDG · Limited quantities (LQ) 5L UN 1263 PAINT, 3, II, ENVIRONMENTALLY · UN "Model Regulation": **HAZARDOUS** 



according to 1907/2006/EC, Article 31

Revision: 20.11.2023 Printing date 20.11.2023 Version number 6 (replaces version 5)

Trade name: Mipa 1K-UV-Klarlack

(Contd. of page 8)

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H225	Highly	flammable	liquid	and	vapour.	
------	--------	-----------	--------	-----	---------	--

H302 Harmful if swallowed.

H315 Causes skin irritation.

May cause an allergic skin reaction. H317

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

May damage fertility or the unborn child. H360

Suspected of damaging fertility. H361f

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

#### Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

(Contd. on page 10)





# **Safety data sheet** according to 1907/2006/EC, Article 31

Printing date 20.11.2023 Version number 6 (replaces version 5) Revision: 20.11.2023

Trade name: Mipa 1K-UV-Klarlack

(Contd. of page 9)

Skin Sens. 1A: Skin sensitisation – Category 1A Skin Sens. 1B: Skin sensitisation – Category 1B Carc. 2: Carcinogenicity – Category 2
Repr. 1B: Reproductive toxicity – Category 1B
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

\* Data compared to the previous version altered.