Revision: 14.03.2024



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.03.2024

Version number 2 (replaces version 1)

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: Mipa 2K-HS-Express-Klarlack ECX 21 NR
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Clear coating material, Varnish
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49 8703 92 20 Fax.: +49 8703 92 21 00

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

· 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



flame

H226 Flammable liquid and vapour. Flam. Liq. 3



Skin Sens. 1

H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

Reaction mass of pentamethyl-piperidylsebacate Pentaerythritol tetrakis(3-mercaptopropionate) triisotridecyl phosphite dibutyltin dilaurate

Hazard statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 14.03.2024 Version number 2 (replaces version 1) Revision: 14.03.2024

Trade name: Mipa 2K-HS-Express-Klarlack ECX 21 NR

(Contd. of page 1)

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P233 Keep container tightly closed.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P403+P235 Store in a well-ventilated place. Keep cool.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

#### · 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components:  |   |             |
|--|---|-------------|
| CAS: 123-92-2<br>EINECS: 204-662-3<br>Reg.nr.: 01-2119548408-32        | isopentyl acetate<br>♦ Flam. Liq. 3, H226, EUH066   | 10-25%      |
| CAS: 123-86-4<br>EINECS: 204-658-1<br>Reg.nr.: 01-2119485493-29        | n-Butyl acetate<br>♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336, EUH066  | ≤20%        |
| CAS: 763-69-9<br>EINECS: 212-112-9<br>Reg.nr.: 01-2119463267-34        | Ethyl 3-ethoxypropionate  Flam. Liq. 3, H226, EUH066  | 2.5-<10%    |
| CAS: 110-12-3<br>EINECS: 203-737-8<br>Reg.nr.: 01-2119472300-51        | 5-methylhexan-2-one<br>♠ Flam. Liq. 3, H226; ♦ Repr. 2, H361; ♠ Acute Tox.<br>4, H332   | <2.5%       |
| CAS: 1065336-91-5<br>EC number: 915-687-0<br>Reg.nr.: 01-2119491304-40 | Reaction mass of pentamethyl-piperidylsebacate  Repr. 2, H361f; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317   | ≥0.25-<1%   |
| CAS: 77745-66-5<br>EINECS: 278-758-9                                   | triisotridecyl phosphite  Skin Sens. 1, H317  | ≥0.1-<1%    |
| CAS: 77-99-6<br>EINECS: 201-074-9                                      | 1,1,1-Trimethylolpropane<br>Repr. 2, H361fd   | <1%         |
| CAS: 77-58-7<br>EINECS: 201-039-8<br>Reg.nr.: 01-2119496068-27         | dibutyltin dilaurate  Muta. 2, H341; Repr. 1B, H360FD; STOT SE 1, H370; STOT RE 1, H372; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Eye Irrit. 2, H319; Skin Sens. 1, H317 | ≥0.1-<0.25% |
| CAS: 7575-23-7<br>EINECS: 231-472-8<br>Reg.nr.: 01-2119486981-23       | Pentaerythritol tetrakis(3-mercaptopropionate)  Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10); Acute Tox. 4, H302; Skin Sens. 1A, H317                           | ≥0.1-<0.25% |

Additional information: For the wording of the listed hazard phrases refer to section 16.



according to 1907/2006/EC, Article 31

Printing date 14.03.2024 Version number 2 (replaces version 1) Revision: 14.03.2024

Trade name: Mipa 2K-HS-Express-Klarlack ECX 21 NR

(Contd. of page 2)

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Revision: 14.03.2024 Printing date 14.03.2024 Version number 2 (replaces version 1)

Trade name: Mipa 2K-HS-Express-Klarlack ECX 21 NR

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

#### 123-92-2 isopentyl acetate

WEL | Short-term value: 541 mg/m³, 100 ppm Long-term value: 270 mg/m<sup>3</sup>, 50 ppm

#### 123-86-4 n-Butyl acetate

WEL | Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

#### 110-12-3 5-methylhexan-2-one

WEL Short-term value: 475 mg/m³, 100 ppm Long-term value: 95 mg/m³, 20 ppm Sk

#### 77-58-7 dibutyltin dilaurate

WEL | Short-term value: 0.2 mg/m3 Long-term value: 0.1 mg/m<sup>3</sup>

as Sn; Sk

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

## Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Revision: 14.03.2024 Printing date 14.03.2024 Version number 2 (replaces version 1)

Trade name: Mipa 2K-HS-Express-Klarlack ECX 21 NR

(Contd. of page 4)

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles

#### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined. • Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

124-128 °C (123-86-4 n-Butyl acetate) boiling range

· Flammability Flammable.

Lower and upper explosion limit

1 Vol % (123-92-2 isopentyl acetate) · Lower: · Upper: 10 Vol % (123-92-2 isopentyl acetate)

27 °C (DIN EN ISO 1523:2002, 123-86-4 n-Butyl · Flash point:

acetate)

Not miscible or difficult to mix.

370 °C (DIN 51794, 123-86-4 n-Butyl acetate) Auto-ignition temperature:

Not determined. Decomposition temperature: · pH Not determined.

· Viscosity:

· Kinematic viscosity at 20 °C 20-23 s (DIN 53211/4)

· Dvnamic: Not determined.

· Solubility · water:

· Partition coefficient n-octanol/water (log

Not determined. value)

10.7 hPa (123-86-4 n-Butyl acetate) · Vapour pressure at 20 °C:

Density and/or relative density

0.996 g/cm3 (DIN EN ISO 2811-1) · Density at 20 °C:

Not determined. · Relative density Not determined. · Vapour density

· 9.2 Other information

· Appearance:

Fluid · Form:

· Important information on protection of health

and environment, and on safety.

Ignition temperature: Product is not selfigniting.

Product is not explosive. However, formation of · Explosive properties:

explosive air/vapour mixtures are possible.

· Solvent content:

43.29 % · VOC (EC) · Solids content (weight-%): 56.7 %

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Printing date 14.03.2024 Version number 2 (replaces version 1) Revision: 14.03.2024

Trade name: Mipa 2K-HS-Express-Klarlack ECX 21 NR

(Contd. of page 5)

|  |  |  | tion |
|--|--|--|------|
|  |  |  |      |
|  |  |  |      |
|  |  |  |      |
|  |  |  |      |

· Evaporation rate Not determined.

# · Information with regard to physical hazard classes

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure

Void
Void
Void

· Flammable liquids Flammable liquid and vapour.

· Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void Void · Organic peroxides Corrosive to metals Void Void · Desensitised explosives

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

## **SECTION 11: Toxicological information**

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation May cause an allergic skin reaction.

#### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 14.03.2024 Version number 2 (replaces version 1) Revision: 14.03.2024

Trade name: Mipa 2K-HS-Express-Klarlack ECX 21 NR

(Contd. of page 6)

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

| SECTION 14: Trail | nsport information |
|-------------------|--------------------|
|-------------------|--------------------|

· 14.1 UN number or ID number

· **ADR, IMDG, IATA** UN1263

· 14.2 UN proper shipping name

· **ADR** UN1263 PAINT

· **IMDG, IATA** PAINT

- · 14.3 Transport hazard class(es)
- · ADR



· Class 3 (F1) Flammable liquids.

· Label

· IMDG, IATA



· Class 3 Flammable liquids.

Label

· 14.4 Packing group

· ADR, IMDG, IATA |||

• 14.5 Environmental hazards: Not applicable.

• 14.6 Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler code): 30

EMS Number: F-E,S-E

· Segregation groups (SGG1) Acids

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 14.03.2024 Version number 2 (replaces version 1) Revision: 14.03.2024

Trade name: Mipa 2K-HS-Express-Klarlack ECX 21 NR

|  | (Contd. of page 7     |
|--|-----------------------|
| · Stowage Category   | Α                     |
| · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable.       |
| · Transport/Additional information:                            |                       |
| · ADR  |                       |
| · Limited quantities (LQ)                                      | 5L                    |
| Transport category   | 3                     |
| Tunnel restriction code  | D/E                   |
| · IMDG   |                       |
| Limited quantities (LQ)  | 5L                    |
| · UN "Model Regulation":                                       | UN 1263 PAINT, 3, III |

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

| Class | Share in % |  |
|-------|------------|--|
| NK    | 25-50      |  |

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

(Contd. on page 9)



according to 1907/2006/EC, Article 31

Printing date 14.03.2024 Version number 2 (replaces version 1) Revision: 14.03.2024

Trade name: Mipa 2K-HS-Express-Klarlack ECX 21 NR

(Contd. of page 8)

H341 Suspected of causing genetic defects.

H360FD May damage fertility. May damage the unborn child. H361 Suspected of damaging fertility or the unborn child.

H361f Suspected of damaging fertility.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

H370 Causes damage to organs.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

#### Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A

Muta. 2: Germ cell mutagenicity – Category 2

Repr. 1B: Reproductive toxicity - Category 1B

Repr. 2: Reproductive toxicity - Category 2

Repr. 2: Reproductive toxicity - Category 2

Repr. 2: Reproductive toxicity - Category 2

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 \* \* Data compared to the previous version altered.