

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.02.2023

Version number 11 (replaces version 10)

Revision: 28.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Mipa 2K-HS-Fillprimer**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Filler and surfacer
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MIPA SE
Am Oberen Moos 1
D-84051 Essenbach
Tel.: +49(0)8703-922-0
Fax.: +49(0)8703-922-100
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com
- **1.4 Emergency telephone number:** International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
n-Butyl acetate
maleic anhydride
Methyl ethyl ketone
2-Methoxy-1-methylethyl acetate
- **Hazard statements**
H225 Highly flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.02.2023

Version number 11 (replaces version 10)

Revision: 28.02.2023

Trade name: Mipa 2K-HS-Fillprimer

(Contd. of page 1)

- P103 Read carefully and follow all instructions.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards
Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients
3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	≤20%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43	Methyl ethyl ketone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	2.5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	2.5-<10%
CAS: 85711-46-2 EINECS: 288-306-2 Reg.nr.: 01-2119976378-19	Fatty acids, C14-18 and C16-18-unsatd., maleated Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317	≥0.1-<1%
CAS: 108-31-6 EINECS: 203-571-6 Reg.nr.: 01-2119472428-31	maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥0.001 %	≥0.001-<0.1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures
4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately rinse with water.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.02.2023

Version number 11 (replaces version 10)

Revision: 28.02.2023

Trade name: Mipa 2K-HS-Fillprimer

(Contd. of page 2)

- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)

Trade name: Mipa 2K-HS-Fillprimer

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-Butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm
	Long-term value: 724 mg/m ³ , 150 ppm

78-93-3 Methyl ethyl ketone

WEL	Short-term value: 899 mg/m ³ , 300 ppm
	Long-term value: 600 mg/m ³ , 200 ppm
	Sk, BMGV

108-65-6 2-Methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm
	Sk

108-31-6 maleic anhydride

WEL	Short-term value: 3 mg/m ³
	Long-term value: 1 mg/m ³
	Sen

· Ingredients with biological limit values:

78-93-3 Methyl ethyl ketone

BMGV	70 µmol/L
	Medium: urine
	Sampling time: post shift
	Parameter: butan-2-one

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Hand protection**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.02.2023

Version number 11 (replaces version 10)

Revision: 28.02.2023

Trade name: Mipa 2K-HS-Fillprimer

(Contd. of page 4)

- **Breakthrough time of glove material**
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye/face protection**



Tightly sealed goggles

SECTION 9: Physical and chemical properties
9.1 Information on basic physical and chemical properties
General Information
Physical state

Fluid

Colour:

According to product specification

Odour:

Characteristic

Odour threshold:

Not determined.

Melting point/freezing point:

Undetermined.

Boiling point or initial boiling point and boiling range

124-128 °C (123-86-4 n-Butyl acetate)

Flammability

Highly flammable.

Lower and upper explosion limit
Lower:

1.2 Vol %

Upper:

7.5 Vol %

Flash point:

9 °C (DIN EN ISO 1523:2002)

Ignition temperature:

370 °C (DIN 51794)

Decomposition temperature:

Not determined.

pH

Not determined.

Viscosity:
Kinematic viscosity at 20 °C

170 s (DIN 53211/4)

Dynamic:

Not determined.

Solubility
water:

Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)

Not determined.

Vapour pressure at 20 °C:

10.7 hPa

Density and/or relative density
Density at 20 °C:

 1.563 g/cm³ (DIN EN ISO 2811-1)

Relative density

Not determined.

Vapour density

Not determined.

9.2 Other information
Appearance:
Form:

Fluid

Important information on protection of health and environment, and on safety.
Auto-ignition temperature:

Product is not selfigniting.

Explosive properties:

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Solvent content:
VOC (EC)

28.79 %

Solids content (weight-%):

71.2 %

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.02.2023

Version number 11 (replaces version 10)

Revision: 28.02.2023

Trade name: Mipa 2K-HS-Fillprimer

(Contd. of page 5)

- **Change in condition**
- **Evaporation rate** Not determined.
- **Information with regard to physical hazard classes**
- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Highly flammable liquid and vapour.
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

· Endocrine disrupting properties

78-93-3 Methyl ethyl ketone

List II

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.02.2023

Version number 11 (replaces version 10)

Revision: 28.02.2023

Trade name: Mipa 2K-HS-Fillprimer

(Contd. of page 6)

12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects
Additional ecological information:
General notes:

Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations
13.1 Waste treatment methods
Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information
14.1 UN number or ID number

- **ADR, IMDG, IATA** UN1263

14.2 UN proper shipping name

- **ADR** UN1263 PAINT
- **IMDG, IATA** PAINT

14.3 Transport hazard class(es)
ADR


- **Class** 3 (F1) Flammable liquids.
- **Label** 3

IMDG, IATA


- **Class** 3 Flammable liquids.
- **Label** 3

14.4 Packing group

- **ADR, IMDG, IATA** II

14.5 Environmental hazards:

- **Marine pollutant:** No

14.6 Special precautions for user

- **Hazard identification number (Kemler code):** 33

Warning: Flammable liquids.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.02.2023

Version number 11 (replaces version 10)

Revision: 28.02.2023

Trade name: Mipa 2K-HS-Fillprimer

(Contd. of page 7)

· EMS Number:	<u>F-E,S-E</u>
· Stowage Category	B
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	

· ADR	
· Limited quantities (LQ)	5L
· Transport category	2
· Tunnel restriction code	D/E

· IMDG	
· Limited quantities (LQ)	5L
· UN "Model Regulation":	UN 1263 PAINT, 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
 - **Directive 2012/18/EU**
 - **Named dangerous substances - ANNEX I** None of the ingredients is listed.
 - **Seveso category P5c** FLAMMABLE LIQUIDS
 - **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
 - **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
 - **National regulations:**
 - **Additional classification according to Decree on Hazardous Materials, Annex II:**
- | Class | Share in % |
|-------|------------|
| NK | 25-50 |
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H336 May cause drowsiness or dizziness.
- H372 Causes damage to organs through prolonged or repeated exposure.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- EUH071 Corrosive to the respiratory tract.
- **Classification according to Regulation (EC) No 1272/2008**
- The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.02.2023

Version number 11 (replaces version 10)

Revision: 28.02.2023

Trade name: Mipa 2K-HS-Fillprimer

(Contd. of page 8)

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

· * **Data compared to the previous version altered.**

GB