

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 24 (replaces version 23)

Revision: 01.03.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

- · Trade name: Mipa 2K-HS-Härter HS 10
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- No further relevant information available.
- · Application of the substance / the mixture Hardening agent/ Curing agent
- **1.3 Details of the supplier of the safety data sheet** • **Manufacturer/Supplier:** MIPA SE Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0 Fax.: +49(0)8703-922-100 e-mail: sdb-registratur@mipa-paints.com www.mipa-paints.com
- **1.4 Emergency telephone number:** International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

• 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008

flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Acute Tox. 4 H332Harmful if inhaled.Skin Sens. 1 H317May cause an allergic skin reaction.STOT SE 3H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

· 2.2 Label elements

• Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



· Signal word Warning

 Hazard-determining components of labelling: Hexamethylene diisocyanate, oligomers n-Butyl acetate
 2-Ethoxy-1-methylethyl acetate
 hexamethylene-di-isocyanate
 Hazard statements
 H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H317 May cause an allergic skin reaction.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 01.03.2023

Version number 24 (replaces version 23)

Revision: 01.03.2023

Trade name: Mipa 2K-HS-Härter HS 10

(Contd. of page 1) Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell. • Additional information: EUH066 Repeated exposure may cause skin dryness or cracking. EUH204 Contains isocyanates. May produce an allergic reaction. Restricted to professional users. · 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

CAS: 28182-81-2	Hexamethylene diisocyanate, oligomers	50-100%
NLP: 500-060-2 Reg.nr.: 01-2119485796-17	Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE	
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate line Flam. Liq. 3, H226; () STOT SE 3, H336, EUH066	25-50%
CAS: 54839-24-6 EINECS: 259-370-9 Reg.nr.: 01-2119475116-39	2-Ethoxy-1-methylethyl acetate ♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	10-25%
CAS: 77-58-7 EINECS: 201-039-8 Reg.nr.: 01-2119496068-27	dibutyltin dilaurate ♣ Muta. 2, H341; Repr. 1B, H360FD; STOT SE 1, H370; STOT RE 1, H372; ♠ Skin Corr. 1C, H314; Eye Dam. 1, H318; ♠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ♠ Skin Sens. 1, H317	<i>≥</i> 0.1-<0.25%
CAS: 822-06-0 EINECS: 212-485-8 Reg.nr.: 01-2119457571-37	 hexamethylene-di-isocyanate Acute Tox. 2, H330; Resp. Sens. 1, H334; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C ≥0.5 % Skin Sens. 1; H317: C ≥ 0.5 % 	<0.1%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

(Contd. on page 3)

GB



according to 1907/2006/EC, Article 31

Revision: 01.03.2023

Printing date 01.03.2023

Version number 24 (replaces version 23)

Trade name: Mipa 2K-HS-Härter HS 10

(Contd. of page 2)

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately rinse with water.

• After eye contact: Rinse opened eye for several minutes under running water.

• After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

• **5.2 Special hazards arising from the substance or mixture** In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Hydrogen cyanide (HĆN)

5.3 Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Contain and collect spillages with non-combustible absorbent materials (e.g. sand, earth, diatomaceous earth) and place in a suitable container.

Decontaminate immediately with suitable mixture (flammable):

- as such usable (inflammatory!):

water	45 Vol.%
ethanol or isopropanol	50 Vol.%
ammonia solution (Density= 0.88)	5 Vol.%
- alternatively (non-flammable):	
sodium carbonate	5 Vol.%
water	95 Vol.%

Add the same decontaminant to any residues and allow to stand for several days in an non-sealed container until no further reaction occurs. Once this stage is reached, close the container and dispose of in accordance with the waste regulations (see Section 13).

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

GE



according to 1907/2006/EC, Article 31

Printing date 01.03.2023 Version number 24 (replaces version 23)

Revision: 01.03.2023

Trade name: Mipa 2K-HS-Härter HS 10

See Section 13 for disposal information.

(Contd. of page 3)

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols. Persons with a history of asthma, allergies or chronic or recurrent respiratory diseases should only

- be employed in processes in which this product is used under appropriate medical supervision. • Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.
- Store away from foodstuffs. • **Further information about storage conditions:** Keep container tightly sealed. Store separately from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohol and water.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

28182-81-2 Hexamethylene diisocyanate, oligomers

EBW Short-term value: 0.5 mg/m³ exposition evaluation valu TRGS 430 (EBW)

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

77-58-7 dibutyltin dilaurate

WEL Short-term value: 0.2 mg/m³ Long-term value: 0.1 mg/m³ as Sn; Sk

822-06-0 hexamethylene-di-isocyanate

WEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO

· Ingredients with biological limit values:

822-06-0 hexamethylene-di-isocyanate

BMGV 1 µmol creatinine/mol Medium: urine Sampling time: At the end of the period od exposure Parameter: isocyanate-derived diamine

• Additional information: The lists valid during the making were used as basis.

(Contd. on page 5)

⁻ GB -



Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 01.03.2023

(Contd. of page 4)

· 8.2 Exposure controls

Version number 24 (replaces version 23)

All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH

Trade name: Mipa 2K-HS-Härter HS 10

General protective and hygienic measures:

· Appropriate engineering controls No further data; see item 7.

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

· Individual protection measures, such as personal protective equipment

Respiratory protection:

Filter A/P2 (EN 141, EN 143)



Regulations.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Breakthrough time of glove material** Value for the permeation: Level ≤ 3

Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Physical state
- · Colour:
- · Odour:
- · Odour threshold:
- · Meltina point/freezina point:
- · Boiling point or initial boiling point and boiling range
- · Flammabilitv
- · Lower and upper explosion limit
- · Lower:
- · Upper:

Fluid According to product specification Characteristic Not determined. Undetermined.

124-128 °C (123-86-4 n-Butyl acetate) Flammable.

1.2 Vol % (123-86-4 n-Butyl acetate) 7.5 Vol % (123-86-4 n-Butyl acetate)

(Contd. on page 6)



Safety data sheet according to 1907/2006/EC, Article 31

Version number 24 (replaces version 23)

Revision: 01.03.2023

Trade name: Mipa 2K-HS-Härter HS 10

	(Contd. of page
Flash point:	27 °C (DIN 53213, 123-86-4 n-Butyl acetate)
Ignition temperature:	370 °C (DIN 51794, 123-86-4 n-Butyl acetate)
Decomposition temperature:	Not determined.
рН	Not determined.
Viscosity:	
Kinematic viscosity at 20 °C	10-15 s (DIN 53211/4)
Dynamic:	Not determined.
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log	
value)	Not determined.
Vapour pressure at 20 °C:	10.7 hPa (123-86-4 n-Butyl acetate)
Density and/or relative density	
Density at 20 °C:	1.029 g/cm³ (DIN 53217)
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Appearance: Form:	Fluid
-	
Important information on protection of hea	
and environment, and on safety.	Draduct is not colfigurities
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
Solvent content:	
VOC (EC)	45.50 %
Solids content (weight-%):	54.5 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical haza	ard
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

(Contd. on page 7)

GB



Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 01.03.2023

Version number 24 (replaces version 23)

Trade name: Mipa 2K-HS-Härter HS 10

(Contd. of page 6)

10.2 Chemical stability

- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products:

Possible in traces. Nitrogen oxides Hydrogen chloride (HCl) Hydrogen cyanide (prussic acid) Carbon monoxide

Nitrogen oxides (NOx)

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- · Acute toxicity Harmful if inhaled.
- · LD/LC50 values relevant for classification:
- 28182-81-2 Hexamethylene diisocyanate, oligomers

Inhalative LC50/4 h 1.5 mg/l (rat)

- Respiratory or skin sensitisation May cause an allergic skin reaction.
- STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

GB -

(Contd. of page 7)



Printing date 01.03.2023

Safety data sheet according to 1907/2006/EC, Article 31

Version number 24 (replaces version 23) Revision: 01.03.2023

Trade name: Mipa 2K-HS-Härter HS 10

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

<i>14.1 UN number or ID number ADR, IMDG, IATA</i>	UN1263
14.2 UN proper shipping name	
ADR	UN1263 PAINT RELATED MATERIAL
IMDG, IATA	PAINT RELATED MATERIAL
14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
<i>14.4 Packing group ADR, IMDG, IATA</i>	<i>III</i>
14.5 Environmental hazards: Marine pollutant:	No
· ·	
14.6 Special precautions for user Hazard identification number (Kemler code):	Warning: Flammable liquids.
EMS Number:	F-E,S-E
Segregation groups	(SGG1) Acids
Stowage Category	A
14.7 Maritime transport in bulk according to	
IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Transport category Tunnel restriction code	3 D/E
IMDG Limited quantities (LQ)	5L
UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III

(Contd. on page 9)



according to 1907/2006/EC, Article 31

Printing date 01.03.2023 Vers

Version number 24 (replaces version 23)

Revision: 01.03.2023

Trade name: Mipa 2K-HS-Härter HS 10

(Contd. of page 8)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations:

• Additional classification according to Decree on Hazardous Materials, Annex II:

Class Share in %

NK 25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.

H360FD May damage fertility. May damage the unborn child.

- H370 Causes damage to organs.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH204 Contains isocyanates. May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 10)



according to 1907/2006/EC, Article 31

Revision: 01.03.2023

Printing date 01.03.2023

Version number 24 (replaces version 23)

Trade name: Mipa 2K-HS-Härter HS 10

(Contd. of page 9) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 2: Acute toxicity – Category 2 Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1C: Skin corrosion/irritation – Category 1C Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation – Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Muta. 2: Germ cell mutagenicity – Category 2 Repr. 1B: Reproductive toxicity – Category 1B STOT SE 1: Specific target organ toxicity (single exposure) – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 * Data compared to the previous version altered.

GB -