Revision: 09.11.2023



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.01.2024

Version number 51 (replaces version 50)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: Mipa 2K-HS-Klarlack CC 8
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Clear coating material, Varnish
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49 8703 92 20 Fax.: +49 8703 92 21 00

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

· 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms







GHS02 GHS07

· Signal word Warning

· Hazard-determining components of labelling:

5-methylhexan-2-one

n-Butyl acetate

2-Ethoxy-1-methylethyl acetate

2-Methoxy-1-methylethyl acetate

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 10.01.2024 Version number 51 (replaces version 50) Revision: 09.11.2023

Trade name: Mipa 2K-HS-Klarlack CC 8

(Contd. of page 1)

· Hazard statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate The Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	10-25%
CAS: 110-12-3 EINECS: 203-737-8 Reg.nr.: 01-2119472300-51	5-methylhexan-2-one ♦ Flam. Liq. 3, H226; ♦ Repr. 2, H361; ♦ Acute Tox. 4, H332	≥3-<10%
CAS: 54839-24-6 EINECS: 259-370-9 Reg.nr.: 01-2119475116-39	2-Ethoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	2.5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate ♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	<2.5%
CAS: 1065336-91-5 EC number: 915-687-0 Reg.nr.: 01-2119491304-40	Reaction mass of pentamethyl-piperidylsebacate Repr. 2, H361f; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317	≥0.25-<1%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately rinse with water.

(Contd. on page 3)

(Contd. of page 2)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.01.2024 Version number 51 (replaces version 50) Revision: 09.11.2023

Trade name: Mipa 2K-HS-Klarlack CC 8

· After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Alcohol resistant foam
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 10.01.2024 Version number 51 (replaces version 50) Revision: 09.11.2023

Trade name: Mipa 2K-HS-Klarlack CC 8

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

110-12-3 5-methylhexan-2-one

WEL Short-term value: 475 mg/m³, 100 ppm Long-term value: 95 mg/m³, 20 ppm

Sk

108-65-6 2-Methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

For the mixture of chemicals the penetration time has to be at least 60 minutes (Permeation according to EN 374 Part 3: Level 3).

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

(Contd. of page 4)



Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 09.11.2023 Printing date 10.01.2024 Version number 51 (replaces version 50)

Trade name: Mipa 2K-HS-Klarlack CC 8

· Eye/face protection

Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state

· Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined. Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

124-128 °C (123-86-4 n-Butyl acetate) boiling range

Flammable. · Flammability

· Lower and upper explosion limit

· Lower: 1.2 Vol % (123-86-4 n-Butyl acetate) · Upper: 7.5 Vol % (123-86-4 n-Butyl acetate) · Flash point: 27 °C (DIN EN ISO 1523:2002)

370 °C (DIN 51794, 123-86-4 n-Butyl acetate) · Auto-ignition temperature:

Not determined. Decomposition temperature: · pH Not determined.

· Viscosity:

Kinematic viscosity at 20 °C 32-35 s (DIN 53211/4) Not determined. · Dynamic:

· Solubility

Not miscible or difficult to mix. · water:

· Partition coefficient n-octanol/water (log

value)

Not determined. 10.7 hPa (123-86-4 n-Butyl acetate) · Vapour pressure at 20 °C:

Vapour pressure at 50 °C: 55 hPa

Density and/or relative density

Density at 20 °C: 1.006 g/cm3 (DIN EN ISO 2811-1)

Not determined. · Relative density Not determined. · Vapour density

· 9.2 Other information

· Appearance:

Fluid · Form:

· Important information on protection of health

and environment, and on safety.

· Ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

40.49 % · VOC (EC) · Solids content (weight-%): 59.5 %

· Change in condition

Not determined. · Evaporation rate

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Printing date 10.01.2024 Version number 51 (replaces version 50) Revision: 09.11.2023

Trade name: Mipa 2K-HS-Klarlack CC 8

(Contd. of page 5)

Information with regard to physical hazard

classes

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure

Void
Void

• Flammable liquids Flammable liquid and vapour.

Flammable solids
Self-reactive substances and mixtures
Void
Pyrophoric liquids
Void
Self-heating substances and mixtures
Substances and mixtures
Substances and mixtures, which emit
flammable gases in contact with water
Void

Oxidising liquids
 Oxidising solids
 Organic peroxides
 Corrosive to metals
 Desensitised explosives

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- Reproductive toxicity Suspected of damaging fertility or the unborn child.
- STOT-single exposure May cause drowsiness or dizziness.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 10.01.2024 Version number 51 (replaces version 50) Revision: 09.11.2023

Trade name: Mipa 2K-HS-Klarlack CC 8

(Contd. of page 6)

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14:	Transpor	t int	format	tion
	Hullspol		Offilla	

14 1	IIN	number	or ID	number
17.1	\mathbf{U}	HUHHNEI	u ib	HUHHDEI

· ADR, IMDG, IATA UN1263

· 14.2 UN proper shipping name

· ADR UN1263 PAINT

· **IMDG, IATA** PAINT

- · 14.3 Transport hazard class(es)
- · ADR



· Class 3 (F1) Flammable liquids.

·Label

· IMDG, IATA



· Class 3 Flammable liquids.

· Label 3

· 14.4 Packing group

· ADR, IMDG, IATA ||||

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler code): 30

· EMS Number: F-E,S-E

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 10.01.2024 Version number 51 (replaces version 50) Revision: 09.11.2023

Trade name: Mipa 2K-HS-Klarlack CC 8

	(Contd. of page 7)
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	D/E
·IMDG	
Limited quantities (LQ)	5L
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H361f Suspected of damaging fertility.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 9)



according to 1907/2006/EC, Article 31

Printing date 10.01.2024 Version number 51 (replaces version 50) Revision: 09.11.2023

Trade name: Mipa 2K-HS-Klarlack CC 8

(Contd. of page 8)

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Repr. 2: Reproductive toxicity – Category 2

Repr. 2: Reproductive toxicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard — Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard — Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard — Category 3

* Data compared to the previous version altered.

GB