

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 30 (replaces version 29)

Revision: 17.01.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

- · Trade name: Mipa 2K-HS-Klarlack CS 44
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Clear coating material, Varnish
- 1.3 Details of the supplier of the safety data sheet • Manufacturer/Supplier: MIPA SE Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0 Fax.: +49(0)8703-922-100 e-mail: sdb-registratur@mipa-paints.com www.mipa-paints.com
- 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

flame

Flam. Liq. 3

H226 Flammable liquid and vapour.

health hazard

H361 Suspected of damaging fertility or the unborn child.



Repr. 2

Skin Sens. 1	H317 May cause an allergic skin reaction.
STOT SE 3	H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

- The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



· Signal word Warning

• Hazard-determining components of labelling: 5-methylhexan-2-one n-Butyl acetate 2-Ethoxy-1-methylethyl acetate 2-Methoxy-1-methylethyl acetate



Safety data sheet

according to 1907/2006/EC, Article 31 Version number 30 (replaces version 29)

Revision: 17.01.2023

Printing date 17.01.2023

Trade name: Mipa 2K-HS-Klarlack CS 44

	(Contd. of page 1)
Hazard staten	nents
H226 Flammal	ble liquid and vapour.
H317 May cau	se an allergic skin reaction.
H361 Suspecte	ed of damaging fertility or the unborn child.
H336 May cau	se drowsiness or dizziness.
H412 Harmful	to aquatic life with long lasting effects.
Precautionary	/ statements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P	353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340 P312	
Additional inf	ormation:
EUH066 Repe	ated exposure may cause skin dryness or cracking.
2.3 Other haza	
Results of PB	T and vPvB assessment
• PBT: Not applicable.	
vPvB: Not app	

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

n-Butyl acetate 🚸 Flam. Liq. 3, H226; 🐠 STOT SE 3, H336, EUH066	10-25%
5-methylhexan-2-one Flam. Liq. 3, H226;	<i>≥</i> 3-<10%
2-Ethoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	2.5-<10%
2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; (1) STOT SE 3, H336	<2.5%
Reaction mass of pentamethyl-piperidyl sebacate Repr. 2, H361f; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Askin Sens. 1A, H317	<i>≥</i> 0.25-<1%
	 Flam. Liq. 3, H226; STOT SE 3, H336, EUH066 5-methylhexan-2-one Flam. Liq. 3, H226; Repr. 2, H361; Acute Tox. 4, H332 2-Ethoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336 2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336 Reaction mass of pentamethyl-piperidyl sebacate Repr. 2, H361; Aguatic Acute 1, H400; Aguatic

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• General information: Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately rinse with water.

(Contd. on page 3)

GB



Safety data sheet

according to 1907/2006/EC, Article 31 Version number 30 (replaces version 29)

Revision: 17.01.2023

(Contd. of page 2)

Trade name: Mipa 2K-HS-Klarlack CS 44

· After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing: If symptoms persist consult doctor.

- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available. • **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Use only in well ventilated areas. Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- *Information about fire and explosion protection:* Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3

(Contd. on page 4)

GB



Safety data sheet

according to 1907/2006/EC, Article 31

Version number 30 (replaces version 29)

Revision: 17.01.2023

Trade name: Mipa 2K-HS-Klarlack CS 44

· 7.3 Specific end use(s) No further relevant information available.

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

110-12-3 5-methylhexan-2-one

WEL Short-term value: 475 mg/m³, 100 ppm Long-term value: 95 mg/m³, 20 ppm Sk

108-65-6 2-Methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

• Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

· Appropriate engineering controls No further data; see item 7.

- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately.
- Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

GB



Safety data sheet according to 1907/2006/EC, Article 31

Version number 30 (replaces version 29)

Revision: 17.01.2023

(Contd. of page 4)

Trade name: Mipa 2K-HS-Klarlack CS 44

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

 9.1 Information on basic physical and che General Information 	emical properties
· Physical state	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
• Boiling point or initial boiling point and	104 100 °C (102 06 1 = But 1 acatata)
boiling range	124-128 °C (123-86-4 n-Butyl acetate)
· Flammability	Flammable.
· Lower and upper explosion limit	
· Lower:	1.2 Vol % (123-86-4 n-Butyl acetate)
· Upper:	7.5 Vol % (123-86-4 n-Butyl acetate)
· Flash point:	36 °C (DIN 53213)
· Ignition temperature:	370 °C (DIN 51794)
 Decomposition temperature: 	Not determined.
· pH	Not determined.
Viscosity:	
· Kinematic viscosity at 20 °C	20-25 s (DIN 53211/4)
· Dynamic:	Not determined.
Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log	
value)	Not determined.
· Vapour pressure at 20 °C:	10.7 hPa (123-86-4 n-Butyl acetate)
· Density and/or relative density	10.7 m a (125-00-4 m-Duly) acelale)
	$1.006 a/cm^3 (DIN 52217)$
· Density at 20 °C: Balative density	1.006 g/cm ³ (DIN 53217)
· Relative density	Not determined.
· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of he	ealth
and environment, and on safety.	
• Auto-ignition temperature:	Product is not selfigniting.
• Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
· Solvent content:	
· VOC (EC)	40.81 %
	59.2 %
· Solids content (weight-%): · Change in condition	JJ.2 /0
	Not determined
· Evaporation rate	Not determined.
·Information with regard to physical ha	zard
classes	



Safety data sheet

according to 1907/2006/EC, Article 31 Version number 30 (replaces version 29)

Revision: 17.01.2023

-

Trade name: Mipa 2K-HS-Klarlack CS 44

	(Contd. o	f page 5
· Flammable gases	Void	
Aerosols	Void	
· Oxidising gases	Void	
· Gases under pressure	Void	
· Flammable liquids	Flammable liquid and vapour.	
Flammable solids	Void	
• Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
[·] Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
• Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Reproductive toxicity Suspected of damaging fertility or the unborn child.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards

· Endocrine disrupting properties

556-67-2 octamethylcyclotetrasiloxane

List II, III

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

(Contd. on page 7)

GB



Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 17.01.2023

Version number 30 (replaces version 29)

Trade name: Mipa 2K-HS-Klarlack CS 44

(Contd. of page 6)

· 12.7 Other adverse effects

• Remark: Harmful to fish

· Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) : slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name · ADR · IMDG, IATA	UN1263 PAINT PAINT
 14.3 Transport hazard class(es) 	
ADR	
· Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	<i>III</i>
 14.5 Environmental hazards: Marine pollutant: 	No
14.6 Special precautions for user	Warning: Flammable liquids.
 Hazard identification number (Kemler code). EMS Number: 	- 30 F-E, <u>S-E</u>
	(Contd. on page 8)



Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 17.01.2023

Printing date 17.01.2023

Version number 30 (replaces version 29)

Trade name: Mipa 2K-HS-Klarlack CS 44

	(Contd. of page 7)
· Stowage Category	A
 14.7 Maritime transport in bulk according to IMO instruments 	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	D/E
·IMDG	
· Limited quantities (LQ)	5L
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

• National regulations:

• Additional classification according to Decree on Hazardous Materials, Annex II:

Class Share in %

25-50

NK

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H226 Flammable liquid and vapour.
- H317 May cause an allergic skin reaction.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H361 Suspected of damaging fertility or the unborn child.
- H361f Suspected of damaging fertility.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 9)



Safety data sheet according to 1907/2006/EC, Article 31

Revision: 17.01.2023

Printing date 17.01.2023

Version number 30 (replaces version 29)

Trade name: Mipa	2K-HS-Klarlack CS 44
------------------	----------------------

	(Contd. of page 8)
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
VOC: Volatile Organic Compounds (USA, EU)	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Liq. 3: Flammable liquids – Category 3	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Sens. 1: Skin sensitisation – Čategory 1	
Skin Sens. 1A: Skin sensitisation – Category 1A	
Repr. 2: Reproductive toxicity – Category 2	
Repr. 2: Reproductive toxicity – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1	
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1	
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	
* Data compared to the previous version altered.	
····· p····· p····· p·····	GB —