

according to 1907/2006/EC, Article 31

Printing date 16.06.2023 Version number 82 (replaces

Version number 82 (replaces version 81) Revision: 16.06.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Mipa 2K-Löser
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Thinner, Diluent
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0 Fax.: +49(0)8703-922-100

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

• 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Dam. 1 H318 Causes serious eye damage.



Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS02 GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Cyclohexanone

- 2-Butoxyethyl acetate
- 2-Methoxy-1-methylethyl acetate

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 16.06.2023 Version number 82 (replaces version 81) Revision: 16.06.2023

Trade name: Mipa 2K-Löser

(Contd. of page 1)

acetone

Hazard statements

H225 Highly flammable liquid and vapour. H312+H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
EINECS: 203-631-1 Reg.nr.: 01-2119453616-35	Cyclohexanone ♠ Flam. Liq. 3, H226; ♠ Eye Dam. 1, H318; ♠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H335	25-50%
	2-Methoxy-1-methylethyl acetate This is a second of the s	25-50%
EINECS: 203-933-3	2-Butoxyethyl acetate Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	<15%
	acetone ♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	5-<10%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 16.06.2023 Version number 82 (replaces version 81) Revision: 16.06.2023

Trade name: Mipa 2K-Löser

(Contd. of page 2)

· After skin contact: Immediately rinse with water.

· After eve contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class: 3

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 16.06.2023 Version number 82 (replaces version 81) Revision: 16.06.2023

Trade name: Mipa 2K-Löser

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

108-94-1 Cyclohexanone

WEL Short-term value: 82 mg/m³, 20 ppm Long-term value: 41 mg/m³, 10 ppm

Sk, BMGV

108-65-6 2-Methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm

Sk

112-07-2 2-Butoxyethyl acetate

WEL Short-term value: 332 mg/m³, 50 ppm Long-term value: 133 mg/m³, 20 ppm

Sk

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

· Ingredients with biological limit values:

108-94-1 Cyclohexanone

BMGV 2 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: cyclohexanol

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Revision: 16.06.2023 Printing date 16.06.2023 Version number 82 (replaces version 81)

Trade name: Mipa 2K-Löser

(Contd. of page 4)

· Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Breakthrough time of glove material Value for the permeation: Level \leq 6
- · Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state

· Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined. Undetermined.

Melting point/freezing point:

· Boiling point or initial boiling point and

boiling range 56 °C (67-64-1 acetone) · Flammability Highly flammable.

Lower and upper explosion limit

1.3 Vol % · Lower: Upper: 10.8 Vol % Flash point: 9 °C (DIN 53213) Auto-ignition temperature: 280 °C (DIN 51794) · Decomposition temperature: Not determined.

· pH · Viscosity:

Kinematic viscosity at 20 °C 15 s (DIN 53211/4) Not determined. · Dynamic:

· Solubility

Not miscible or difficult to mix. · water:

· Partition coefficient n-octanol/water (log

Not determined. value) · Vapour pressure at 20 °C: 233 hPa

· Density and/or relative density

· Density at 20 °C: 0.936 g/cm3 (DIN 53217)

· Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and environment, and on safety.

Ignition temperature: Product is not selfigniting.

Product is not explosive. However, formation of • Explosive properties:

Not determined.

explosive air/vapour mixtures are possible.

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Printing date 16.06.2023 Version number 82 (replaces version 81) Revision: 16.06.2023

Trade name: Mipa 2K-Löser

(Contd. of page 5)

· Solvent content:

• **VOC (EC)** 99.84 % • **Solids content (weight-%):** 0.2 %

· Change in condition

· Evaporation rate Not determined.

Information with regard to physical hazard

classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

· Flammable liquids Highly flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures, which emit
 flammable gases in contact with water

Substances and mixtures, which emit flammable gases in contact with water
 Oxidising liquids
 Oxidising solids
 Organic peroxides
 Corrosive to metals
 Desensitised explosives

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Harmful in contact with skin or if inhaled.
- · LD/LC50 values relevant for classification:

108-94-1 Cyclohexanone

Oral LD50 1,620 mg/kg (rat)

- Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye damage.
- · STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

GB



according to 1907/2006/EC, Article 31

Printing date 16.06.2023 Version number 82 (replaces version 81) Revision: 16.06.2023

Trade name: Mipa 2K-Löser

(Contd. of page 6)

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN number or ID number
- · ADR, IMDG, IATA UN1263
- · 14.2 UN proper shipping name
- · **ADR** UN1263 PAINT RELATED MATERIAL

· IMDG, IATA PAINT RELATED MATERIAL

- · 14.3 Transport hazard class(es)
- · ADR



· Class 3 (F1) Flammable liquids.

·Label

· IMDG, IATA



· Class 3 Flammable liquids.

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 16.06.2023 Version number 82 (replaces version 81) Revision: 16.06.2023

Trade name: Mipa 2K-Löser

	(Contd. of page
Label	3
14.4 Packing group	
ADR, IMDG, IATA	II .
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33
EMS Number:	F-E,S-E
Stowage Category	В
14.7 Maritime transport in bulk according to	
IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	50-100

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

(Contd. on page 9)



according to 1907/2006/EC, Article 31

Printing date 16.06.2023 Version number 82 (replaces version 81) Revision: 16.06.2023

Trade name: Mipa 2K-Löser

(Contd. of page 8)

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.