

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.04.2024

Version number 5 (replaces version 4)

Revision: 08.04.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Mipa Bremssattelack-Spray**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Paint
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MIPA SE
Am Oberen Moos 1
D-84051 Essenbach
Tel.: +49 8703 92 20
Fax.: +49 8703 92 21 00
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com
- **1.4 Emergency telephone number:** International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
acetone
Ethyl acetate
n-Butyl acetate
2-Methoxy-1-methylethyl acetate
- **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

(Contd. on page 2)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.04.2024

Version number 5 (replaces version 4)

Revision: 08.04.2024

Trade name: Mipa Bremssattellack-Spray

(Contd. of page 1)

- P103 Read carefully and follow all instructions.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.
 Buildup of explosive mixtures possible without sufficient ventilation.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37	dimethyl ether ⚠ Flam. Gas 1A, H220; Press. Gas (Liq.), H280	25-50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≥10-≤20%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46	Ethyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-25%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336, EUH066	5-<10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<5%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	<2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

(Contd. on page 3)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.04.2024

Version number 5 (replaces version 4)

Revision: 08.04.2024

Trade name: Mipa Bremssattelack-Spray

(Contd. of page 2)

- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Do not seal receptacle gas tight.
Keep container tightly sealed.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.04.2024

Version number 5 (replaces version 4)

Revision: 08.04.2024

Trade name: Mipa Bremssattellack-Spray

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Ingredients with limit values that require monitoring at the workplace:
115-10-6 dimethyl ether

WEL	Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm
-----	---

67-64-1 acetone

WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
-----	--

141-78-6 Ethyl acetate

WEL	Short-term value: 1468 mg/m ³ , 400 ppm Long-term value: 734 mg/m ³ , 200 ppm
-----	--

123-86-4 n-Butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
-----	---

1330-20-7 Xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

108-65-6 2-Methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
-----	--

Ingredients with biological limit values:
1330-20-7 Xylene

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 5)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.04.2024

Version number 5 (replaces version 4)

Revision: 08.04.2024

Trade name: Mipa Bremssattellack-Spray

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection

Safety glasses



Tightly sealed goggles

SECTION 9: Physical and chemical properties
9.1 Information on basic physical and chemical properties
General Information

· Physical state	Aerosol
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	-24.9 °C
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	1.2 Vol % (123-86-4 n-Butyl acetate)
· Upper:	18.6 Vol % (115-10-6 dimethyl ether)
· Flash point:	<0 °C (DIN 53213)
· Auto-ignition temperature:	235 °C (DIN 51794, 115-10-6 dimethyl ether)
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	5,200 hPa (115-10-6 dimethyl ether)
· Density and/or relative density	
· Density at 20 °C:	0.822 g/cm ³ (DIN 53217)
· Relative density	Not determined.

(Contd. on page 6)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.04.2024

Version number 5 (replaces version 4)

Revision: 08.04.2024

Trade name: Mipa Bremssattelack-Spray

(Contd. of page 5)

· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· VOC (EC)	83.35 %
· Solids content (weight-%):	16.6 %
· Change in condition	
· Evaporation rate	Not applicable.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Causes serious eye irritation.

(Contd. on page 7)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.04.2024

Version number 5 (replaces version 4)

Revision: 08.04.2024

Trade name: Mipa Bremssattellack-Spray

(Contd. of page 6)

- **STOT-single exposure** May cause drowsiness or dizziness.


SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) : slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|---------------------|
| · 14.1 UN number or ID number | |
| · ADR, IMDG, IATA | UN1950 |
| · 14.2 UN proper shipping name | |
| · ADR | UN1950 AEROSOLS |
| · IMDG | AEROSOLS |
| · IATA | AEROSOLS, flammable |
| · 14.3 Transport hazard class(es) | |
| · ADR | |
|  | |
| · Class | 2 5F Gases. |

(Contd. on page 8)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.04.2024

Version number 5 (replaces version 4)

Revision: 08.04.2024

Trade name: Mipa Bremssattellack-Spray

(Contd. of page 7)

 · **Label** 2.1

 · **IMDG, IATA**

 · **Class** 2.1 Gases.
 · **Label** 2.1

 · **14.4 Packing group**
 · **ADR, IMDG, IATA** Void

 · **14.5 Environmental hazards:**
 · **Marine pollutant:** No

 · **14.6 Special precautions for user** Warning: Gases.
 · **Hazard identification number (Kemler code):** -
 · **EMS Number:** F-D, S-U
 · **Stowage Code** SW1 Protected from sources of heat.
 SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
 · **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre:
 Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
 For AEROSOLS with a capacity above 1 litre:
 Segregation as for the appropriate subdivision of class 2.
 For WASTE AEROSOLS:
 Segregation as for the appropriate subdivision of class 2.

 · **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.

 · **Transport/Additional information:**

 · **ADR**
 · **Limited quantities (LQ)** 1L
 · **Transport category** 2
 · **Tunnel restriction code** D

 · **IMDG**
 · **Limited quantities (LQ)** 1L

 · **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

 · **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
 · **Poisons Act**

 · **Regulated explosives precursors**

None of the ingredients is listed.

(Contd. on page 9)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.04.2024

Version number 5 (replaces version 4)

Revision: 08.04.2024

Trade name: Mipa Bremssattellack-Spray

(Contd. of page 8)

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

67-64-1	acetone	Listed
---------	---------	--------

· Directive 2012/18/EU
· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P3a FLAMMABLE AEROSOLS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations:
· Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	50-100

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Abbreviations and acronyms:

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organisation
- ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Gas 1A: Flammable gases – Category 1A
- Aerosol 1: Aerosols – Category 1
- Press. Gas (Liq.): Gases under pressure – Liquefied gas
- Flam. Liq. 2: Flammable liquids – Category 2

(Contd. on page 10)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.04.2024

Version number 5 (replaces version 4)

Revision: 08.04.2024

Trade name: Mipa Bremssattellack-Spray

(Contd. of page 9)

*Flam. Liq. 3: Flammable liquids – Category 3**Acute Tox. 4: Acute toxicity – Category 4**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2**Asp. Tox. 1: Aspiration hazard – Category 1***· * Data compared to the previous version altered.**

GB