

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.02.2023

Version number 29 (replaces version 28)

Revision: 14.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Mipa HV-Hohlraumversiegelung Aerosol**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Protective coating
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MIPA SE
Am Oberen Moos 1
D-84051 Essenbach
Tel.: +49(0)8703-922-0
Fax.: +49(0)8703-922-100
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com
- **1.4 Emergency telephone number:** International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Skin Irrit. 2	H315	Causes skin irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics
- **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Trade name: Mipa HV-Hohlraumversiegelung Aerosol

(Contd. of page 1)

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P103 Read carefully and follow all instructions.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

- EUH208 Contains Sulfonic acids, petroleum, calcium salts. May produce an allergic reaction.
 Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards
Results of PBT and vPvB assessment

- **PBT:** Not applicable.
 · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients
3.2 Mixtures

- **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	≥10-<25%
EC number: 918-481-9 Reg.nr.: 01-2119457273-39	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics ⚠ Asp. Tox. 1, H304, EUH066	10-25%
EC number: 927-241-2 Reg.nr.: 01-2119471843-32	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336; Aquatic Chronic 3, H412, EUH066	≥10-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-21194869440-21	propane ⚠ Flam. Gas 1A, H220; ⚠ Press. Gas (Liq.), H280	10-25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-31	butane, pure ⚠ Flam. Gas 1A, H220; ⚠ Press. Gas (Comp.), H280	10-25%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	isobutane ⚠ Flam. Gas 1A, H220; ⚠ Press. Gas (Comp.), H280	2.5-<10%
CAS: 64742-48-9 EINECS: 265-150-3	Naphtha (petroleum), hydrotreated heavy, benzene content < 0,1% ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304, EUH066	2.5-<10%
CAS: 61789-86-4 EINECS: 263-093-9 Reg.nr.: 01-2119488992-18	Sulfonic acids, petroleum, calcium salts ⚠ Skin Sens. 1B, H317 Specific concentration limit: Skin Sens. 1B; H317: C ≥10 %	≥0.1-<2.5%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.02.2023

Version number 29 (replaces version 28)


Revision: 14.02.2023

Trade name: Mipa HV-Hohlraumversiegelung Aerosol

CAS: 68526-86-3

EINECS: 271-235-6

alcohols, C11-14-iso-, C13-rich

 Aquatic Acute 1, H400; Aquatic Chronic 2, H411

(Contd. of page 2)

≥0.25-<1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Seek immediate medical advice.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.02.2023

Version number 29 (replaces version 28)

Revision: 14.02.2023

Trade name: Mipa HV-Hohlraumversiegelung Aerosol

(Contd. of page 3)

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities
· Storage:
· Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility: Store away from foodstuffs.

· Further information about storage conditions: Keep container tightly sealed.

· Storage class: 2 B

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection
· 8.1 Control parameters
· Ingredients with limit values that require monitoring at the workplace:
106-97-8 butane, pure

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls
· Appropriate engineering controls No further data; see item 7.

· Individual protection measures, such as personal protective equipment
· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:


In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.02.2023

Version number 29 (replaces version 28)

Revision: 14.02.2023

Trade name: Mipa HV-Hohlraumversiegelung Aerosol

(Contd. of page 4)

· **Eye/face protection** Not required.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· Physical state	Aerosol
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	-44.5 °C (74-98-6 propane)
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	1.5 Vol % (106-97-8 butane, pure)
· Upper:	10.9 Vol % (74-98-6 propane)
· Flash point:	<0 °C (DIN 53213)
· Ignition temperature:	365 °C (DIN 51794, 106-97-8 butane, pure)
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	8,300 hPa (74-98-6 propane)
· Density and/or relative density	
· Density at 20 °C:	0.714 g/cm ³ (DIN 53217)
· Relative density	Not determined.
· Vapour density	Not determined.

· **9.2 Other information**

· Appearance:	
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· VOC (EC)	84.40 %
· Solids content (weight-%):	15.6 %
· Change in condition	
· Evaporation rate	Not applicable.

· **Information with regard to physical hazard classes**

· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.02.2023

Version number 29 (replaces version 28)

Revision: 14.02.2023

Trade name: Mipa HV-Hohlraumversiegelung Aerosol

(Contd. of page 5)

· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Skin corrosion/irritation** Causes skin irritation.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **Aspiration hazard** May be fatal if swallowed and enters airways.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.02.2023

Version number 29 (replaces version 28)

Revision: 14.02.2023

Trade name: Mipa HV-Hohlraumversiegelung Aerosol



(Contd. of page 6)

- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) : hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR · IMDG · IATA	UN1950 AEROSOLS AEROSOLS AEROSOLS, flammable
· 14.3 Transport hazard class(es) · ADR	
	
· Class · Label	2 5F Gases. 2.1
· IMDG, IATA	
	
· Class · Label	2.1 Gases. 2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	Yes
· 14.6 Special precautions for user · Hazard identification number (Kemler code): - · EMS Number: · Stowage Code	Warning: Gases. F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.02.2023

Version number 29 (replaces version 28)

Revision: 14.02.2023

Trade name: Mipa HV-Hohlraumversiegelung Aerosol

(Contd. of page 7)

· Segregation Code

AEROSOLS: Category C, Clear of living quarters.
 SG69 For AEROSOLS with a maximum capacity of 1 litre:
 Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
 For AEROSOLS with a capacity above 1 litre:
 Segregation as for the appropriate subdivision of class 2.
 For WASTE AEROSOLS:
 Segregation as for the appropriate subdivision of class 2.

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

· Transport/Additional information:
· ADR

· Limited quantities (LQ)	1L
· Transport category	2
· Tunnel restriction code	D

· IMDG

· Limited quantities (LQ)	1L
---------------------------	----

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information
· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- National regulations:
- Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	50-100

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H336 May cause drowsiness or dizziness.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.02.2023

Version number 29 (replaces version 28)

Revision: 14.02.2023

Trade name: Mipa HV-Hohlraumversiegelung Aerosol

(Contd. of page 8)

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· **Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Press. Gas (Liq.): Gases under pressure – Liquefied gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**