


according to UK REACH

Printing date 22.08.2024

Version number 27 (replaces version 26)

Revision: 22.08.2024





according to UK REACH

Revision: 22.08.2024

Printing date 22.08.2024

Version number 27 (replaces version 26)

Trade name: Mipa Kunststofflack-Spray

	(Contd. of page 1)
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P305+P351+P33	8 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/ international regulations.
· Additional infor	nation:

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

[•] 2.3 Other hazards

· Results of PBT and vPvB assessment

- · PBT: Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

 Dangerous components: 		
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37	Dimethyl ether	25-50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	Acetone	_ <i>≥</i> 10- <i>≤</i> 20%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46	Ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-25%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate	<15%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	<2.5%
· Additional information: Fo	r the wording of the listed hazard phrases refer to section 1	6.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing: If symptoms persist consult doctor.

• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

GB -



Safety data sheet

according to UK REACH Version number 27 (replaces version 26)

Revision: 22.08.2024

Trade name: Mipa Kunststofflack-Spray

(Contd. of page 2)

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. **5.2 Special hazards arising from the substance or mixture**

- No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device. Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• **6.3 Methods and material for containment and cleaning up:** Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

• **7.1 Precautions for safe handling** Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Do not seal receptacle gas tight. Keep container tightly sealed.
- Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)



Safety data sheet

according to UK REACH Version number 27 (replaces version 26)

Revision: 22.08.2024

Trade name: Mipa Kunststofflack-Spray

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

115-10-6 Dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

67-64-1 Acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

141-78-6 Ethyl acetate

WEL Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

108-65-6 2-Methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)



Safety data sheet according to UK REACH

Revision: 22.08.2024

Printing date 22.08.2024 Version number 27 (replaces version 26)

Trade name: Mipa Kunststofflack-Spray

(Contd. of page 4)

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye/face protection Safety glasses



Tightly sealed goggles

SECTION 9: Physical and chemical properties			
• 9.1 Information on basic physical and chem	nical properties		
· General Information			
· Physical state	Aerosol		
· Colour:	According to product specification		
· Odour:	Characteristic		
· Odour threshold:	Not determined.		
 Melting point/freezing point: 	Undetermined.		
Boiling point or initial boiling point and			
boiling range	-24.9 °C		
· Flammability	Not applicable.		
Lower and upper explosion limit			
· Lower:	1.2 Vol % (123-86-4 n-Butyl acetate)		
· Upper:	18.6 Vol % (115-10-6 Dimethyl ether)		
Flash point:	<0 °C (DIN 53213)		
Auto-ignition temperature:	235 °C (DIN 51794, 115-10-6 Dimethyl ether)		
Decomposition temperature:	Not determined.		
· pH	Not determined.		
· Viscosity:			
· Kinematic viscosity	Not determined.		
· Dynamic:	Not determined.		
· Solubility			
· water:	Not miscible or difficult to mix.		
 Partition coefficient n-octanol/water (log 			
value)	Not determined.		
Vapour pressure at 20 °C:	5,200 hPa (115-10-6 Dimethyl ether)		
Density and/or relative density			
Density at 20 °C:	0.814 g/cm³ (DIN 53217)		
· Relative density	Not determined.		
· Vapour density	Not determined.		
· 9.2 Other information			
· Appearance:			
· Form:	Aerosol		
· Important information on protection of heat			
and environment, and on safety.			
Ignition temperature:	Product is not selfigniting.		
• Explosive properties:	Product is not explosive. However, formation of		
	explosive air/vapour mixtures are possible.		
· Solvent content:			
· VOC (EC)	83.87 %		
· Solids content (weight-%):	16.1 %		
	(Contd. on page 6)		



according to UK REACH

Revision: 22.08.2024

Printing date 22.08.2024

18.2024 Version number 27 (replaces version 26)

Trade name: Mipa Kunststofflack-Spray

	(Contd. of page s
· Change in condition	
· Evaporation rate	Not applicable.
 Information with regard to physical haz classes 	ard
· Explosives	Void
· Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurise container: May burst if heated.
• Oxidising gases	Void
· Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
• Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- [•] 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 7)

GB



Safety data sheet

according to UK REACH

Revision: 22.08.2024

Version number 27 (replaces version 26)

Trade name: Mipa Kunststofflack-Spray

(Contd. of page 6)

12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

· 12.7 Other adverse effects

· Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information · 14.1 UN number or ID number · ADR, IMDG, IATA UN1950 14.2 UN proper shipping name UN1950 AEROSOLS · ADR ·IMDG **AEROSOLS** AEROSOLS, flammable ·IATA · 14.3 Transport hazard class(es) · ADR · Class 2 5F Gases. · Label 2.1 · IMDG, IATA · Class 2.1 Gases. · Label 2.1 · 14.4 Packing group · ADR, IMDG, IATA Void · 14.5 Environmental hazards: · Marine pollutant: No 14.6 Special precautions for user Warning: Gases. · Hazard identification number (Kemler code): -· EMS Number: F-D.S-U Stowage Code SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity

(Contd. on page 8)



according to UK REACH

Revision: 22.08.2024

Printing date 22.08.2024

Version number 27 (replaces version 26)

Trade name: Mipa Kunststofflack-Spray

	(Contd. of page
· · Segregation Code	of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision o class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision o class 2.
 14.7 Maritime transport in bulk accord IMO instruments 	ling to Not applicable.
· Transport/Additional information:	
• ADR • Limited quantities (LQ) • Transport category • Tunnel restriction code	1L 2 D
· IMDG · Limited quantities (LQ)	1L

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

67-64-1 Acetone

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

· Seveso category P3a FLAMMABLE AEROSOLS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

• National regulations:

• Additional classification according to Decree on Hazardous Materials, Annex II:

Class Share in %

NK 50-100

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Listed

(Contd. on page 9)



Safety data sheet

according to UK REACH Version number 27 (replaces version 26)

Revision: 22.08.2024

Trade name: Mipa Kunststofflack-Spray

(Contd. of page 8)

SECTION 16: Other information This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. Relevant phrases Extremely flammable gas. H220 H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H280 Contains gas under pressure; may explode if heated. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. EUH066 Repeated exposure may cause skin dryness or cracking. Classification according to Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols - Category 1 Press. Gas (Liq.): Gases under pressure - Liquefied gas Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 ** Data compared to the previous version altered.