Revision: 01.03.2024



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.03.2024

Version number 13 (replaces version 12)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Mipa Kunststoffprimer-Spray
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- Product category PC9a Coatings and paints, thinners, paint removers
- · Application of the substance / the mixture Priming
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49 8703 92 20 Fax.: +49 8703 92 21 00

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

• 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



| Skin Irrit. 2 | H315 | Causes skin irritation. |
|---------------|------|------------------------------------|
| Eye Irrit. 2 | H319 | Causes serious eye irritation. |
| STOT SE 3 | H336 | May cause drowsiness or dizziness. |

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- Hazard-determining components of labelling: acetone

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 01.03.2024 Version number 13 (replaces version 12) Revision: 01.03.2024

Trade name: Mipa Kunststoffprimer-Spray

(Contd. of page 1)

Ethyl acetate

Solvent naphtha (petroleum), light arom.

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|--|--|---------------|
| CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49 | acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 | 25-50% |
| CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-21194869440-21 | propane Flam. Gas 1A, H220; Press. Gas (Liq.), H280 | 10-25% |
| CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46 | Ethyl acetate ♠ Flam. Liq. 2, H225; ♠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 | 10-25% |
| CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32 | Xylene ♠ Flam. Liq. 3, H226; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ♠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | 5-<10% |
| CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27 | isobutane Flam. Gas 1A, H220; Press. Gas (Comp.), H280 | 2.5-<10% |
| | | Contd. on pag |



according to 1907/2006/EC, Article 31

Printing date 01.03.2024 Version number 13 (replaces version 12) Revision: 01.03.2024

Trade name: Mipa Kunststoffprimer-Spray

| 0.10 100 07 0 | | (Contd. of page 2 |
|---|--|-------------------|
| CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-31 | butane, pure ♦ Flam. Gas 1A, H220; Press. Gas (Comp.), H280 | 2.5-<10% |
| CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119486773-24 | Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336 | 2.5-<5% |
| CAS: 123-42-2 EINECS: 204-626-7 Reg.nr.: 01-2119473975-21 | 4-hydroxy-4-methylpentan-2-one | ≥2.5-<3% |
| CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35 | Ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412 | <2.5% |
| CAS: 95-63-6 EINECS: 202-436-9 | 1,2,4-trimethylbenzene Flam. Liq. 3, H226; Aquatic Chronic 2, H411; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | ≥0.25-<2.5% |
| CAS: 108-90-7 EINECS: 203-628-5 | chlorobenzene Flam. Liq. 3, H226; Aquatic Chronic 2, H411; Acute Tox. 4, H332; Skin Irrit. 2, H315 | <0.25% |

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.



according to 1907/2006/EC, Article 31

Printing date 01.03.2024 Version number 13 (replaces version 12) Revision: 01.03.2024

Trade name: Mipa Kunststoffprimer-Spray

(Contd. of page 3)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Do not seal receptacle gas tight.

Keep container tightly sealed.

- Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

| · Ingredients with limit values that requ | iire monitoring at the workp | lace: |
|---|------------------------------|-------|
|---|------------------------------|-------|

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

141-78-6 Ethyl acetate

WEL Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm

1330-20-7 Xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk: BMGV

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 01.03.2024 Version number 13 (replaces version 12) Revision: 01.03.2024

Trade name: Mipa Kunststoffprimer-Spray

| | | (Contd. of pa |
|-------|---|---------------|
| 106-9 | 7-8 butane, pure | • |
| WEL | Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene) | |
| 123-4 | 2-2 4-hydroxy-4-methylpentan-2-one | |
| WEL | Short-term value: 362 mg/m³, 75 ppm Long-term value: 241 mg/m³, 50 ppm | |
| 100-4 | 11-4 Ethylbenzene | |
| WEL | Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk | |
| 95-63 | -6 1,2,4-trimethylbenzene | |
| WEL | Long-term value: 125 mg/m³, 25 ppm ILV | |
| 108-9 | 0-7 chlorobenzene | |
| WEL | Short-term value: 14 mg/m³, 3 ppm Long-term value: 4.7 mg/m³, 1 ppm Sk | |
| Ingre | dients with biological limit values: | |
| 1330- | -20-7 Xylene | |
| | V 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid | |
| 108-9 | 00-7 chlorobenzene | |
| BMG | V 5 mmol/mol creatinine Medium: urin Sampling time: Post shift Parameter: 4-chlorocatechol | |

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Revision: 01.03.2024 Printing date 01.03.2024 Version number 13 (replaces version 12)

Trade name: Mipa Kunststoffprimer-Spray

(Contd. of page 5)



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Breakthrough time of glove material Value for the permeation: Level ≤ 1
- Eye/face protection

Safety glasses



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Aerosol

· Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined.

· Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range -44.5 °C

· Flammability Not applicable.

· Lower and upper explosion limit

· Lower: 1.7 Vol % (74-98-6 propane) · Upper: 13 Vol % (67-64-1 acetone) · Flash point: <0 °C (DIN 53213)

Auto-ignition temperature: 365 °C (DIN 51794, 106-97-8 butane, pure)

Not miscible or difficult to mix.

Not determined. · Decomposition temperature: Not determined.

· Viscosity:

· Kinematic viscosity Not determined.

· Solubility

· Dynamic: Not determined.

· water: Partition coefficient n-octanol/water (log

value) Not determined.

Vapour pressure at 20 °C: 8,300 hPa (74-98-6 propane)

Vapour pressure at 50 °C: 800 hPa

Density and/or relative density

Density at 20 °C: 0.755 g/cm3 (DIN 53217)

Relative density Not determined. · Vapour density Not determined.

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 01.03.2024 Version number 13 (replaces version 12) Revision: 01.03.2024

Trade name: Mipa Kunststoffprimer-Spray

(Contd. of page 6)

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health

and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

• **VOC (EC)** 98.42 % • **Solids content (weight-%):** 1.4 %

· Change in condition

• Evaporation rate Not applicable.

Information with regard to physical hazard

classes
• Explosives Void
• Flammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised

container: May burst if heated.

· Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit Void Void

flammable gases in contact with water
Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives
Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 01.03.2024 Version number 13 (replaces version 12) Revision: 01.03.2024

Trade name: Mipa Kunststoffprimer-Spray

(Contd. of page 7)

· 11.2 Information on other hazards

· Endocrine disrupting properties

108-90-7 chlorobenzene List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR UN1950 AEROSOLS

· **IMDG** AEROSOLS

· IATA AEROSOLS, flammable

· 14.3 Transport hazard class(es)

· ADR



· Class 2 5F Gases.

(Contd. on page 9)



according to 1907/2006/EC, Article 31

Printing date 01.03.2024 Version number 13 (replaces version 12) Revision: 01.03.2024

Trade name: Mipa Kunststoffprimer-Spray

(Contd. of page 8) ·Label 2.1 · IMDG, IATA 2.1 Gases. · Class ·Label 2.1 · 14.4 Packing group · ADR, IMDG, IATA Void · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Gases. Hazard identification number (Kemler code): -· EMS Number: F-D.S-U · Stowage Code SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. · Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Maritime transport in bulk according to IMO instruments Not applicable. · Transport/Additional information: · Limited quantities (LQ) 1L · Transport category 2 · Tunnel restriction code D · Limited quantities (LQ) UN "Model Regulation": UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

(Contd. on page 10)



according to 1907/2006/EC, Article 31

Printing date 01.03.2024 Version number 13 (replaces version 12) Revision: 01.03.2024

Trade name: Mipa Kunststoffprimer-Spray

| | (Contd. of page 9) |
|------------------------------------|--------------------|
| · Regulated poisons | |
| None of the ingredients is listed. | |
| Reportable explosives precursors | |
| 67-64-1 acetone | Listed |
| · Reportable poisons | |
| None of the ingredients is listed. | |

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

| Class | Share in % | |
|-------|------------|--|
| NK | 50-100 | |

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

| H220 | Extremely | ∕ flammal | ole gas. |
|------|-----------|-----------|----------|
|------|-----------|-----------|----------|

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 11)



according to 1907/2006/EC, Article 31

Version number 13 (replaces version 12) Revision: 01.03.2024 Printing date 01.03.2024

Trade name: Mipa Kunststoffprimer-Spray

(Contd. of page 10)

vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure – Compressed gas Press. Gas (Liq.): Gases under pressure – Liquefied gas

Flam. Liq. 2: Flammable liquids — Category 2
Flam. Liq. 3: Flammable liquids — Category 3
Acute Tox. 4: Acute toxicity — Category 4
Skin Irrit. 2: Skin corrosion/irritation — Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* * Data compared to the previous version altered.