

Printing date 20.08.2024

Safety data sheet

according to UK REACH Version number 5 (replaces version 4)

Revision: 25.04.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

- · Trade name: Mipa P 118 Ultra PE-Leichtspachtel
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Knife filler/ Surfacer
- · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: MIPA SE Am Oberen Moos 1 D-84051 Essenbach Tel.: +49 8703 92 20 Fax.: +49 8703 92 21 00 e-mail: sdb-registratur@mipa-paints.com www.mipa-paints.com
- 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

health hazard

H361d Suspected of damaging the unborn child. Repr. 2

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation. Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling: Styrene Maleic anhydride

(Contd. on page 2)

GB

Professional Goating Systems

Printing date 20.08.2024

Version number 5 (replaces version 4)

Safety data sheet according to UK REACH

Revision: 25.04.2024

Trade name: Mipa P 118 Ultra PE-Leichtspachtel

	(Contd. of page 1)			
2,2'-(m-Tolylimino)diethanol				
Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl]				
(4-methylphenyl)amino]-				
· Hazard statemer				
H226 Flammabl	e liquid and vapour.			
H315 Causes sk				
	erious eye irritation.			
	e an allergic skin reaction.			
	d of damaging the unborn child.			
	amage to the hearing organs through prolonged or repeated exposure.			
· Precautionary st				
P101	If medical advice is needed, have product container or label at hand.			
P102	Keep out of reach of children.			
P102 P103				
	Read carefully and follow all instructions.			
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition			
DOCO	sources. No smoking.			
P260	Do not breathe dust/fume/gas/mist/vapours/spray.			
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing			
	protection.			
P303+P361+P35	3 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin			
	with water [or shower].			
P305+P351+P33	8 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact			
	lenses, if present and easy to do. Continue rinsing.			
P501	Dispose of contents/container in accordance with local/regional/national/			
	international regulations.			
· 2.3 Other hazards				
· Results of PBT and vPvB assessment				
· PBT: Not applicable.				

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Г

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 91-99-6 2,2'-(m-Tolylimino)diethanol ≥0.1-<1% EINECS: 202-114-8 STOT RE 2, H373; Eye Dam. 1, H318; ≥0.1-<1% Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1B, H317	Reg.nr.: 01-2119457861-32	Styrene Flam. Liq. 3, H226; Sepr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	≥10-≤20%
		 STOT RE 2, H373; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 	<i>≥</i> 0.1-<1%



according to UK REACH

Revision: 25.04.2024

Printing date 20.08.2024

Version number 5 (replaces version 4)

Trade name: Mipa P 118 Ultra PE-Leichtspachtel

EC number: 911-490-9	Reaction mass of 2,2'-[(4-methylphenyl)imino] bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl] (4-methylphenyl)amino]- È Eye Dam. 1, H318; (1) Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	(Contd. of page 2) ≥0.1-<1%
CAS: 108-31-6 EINECS: 203-571-6 Reg.nr.: 01-2119472428-31	 Maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥0.001 % r the wording of the listed bazard phrases refer to section 	≥0.001-<0.1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing: If symptoms persist consult doctor.

• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

6.4 Reference to other sections See Section 7 for information on safe handling.

(Contd. on page 4)

GB

Professional Goating Systems

Safety data sheet

according to UK REACH

Printing date 20.08.2024

Version number 5 (replaces version 4)

Revision: 25.04.2024

(Contd. of page 3)

Trade name: Mipa P 118 Ultra PE-Leichtspachtel

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

• *Information about fire - and explosion protection:* Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

100-42-5 Styrene

WEL Short-term value: 1080 mg/m³, 250 ppm Long-term value: 430 mg/m³, 100 ppm

108-31-6 Maleic anhydride

WEL Short-term value: 3 mg/m³ Long-term value: 1 mg/m³ Sen

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes. Avoid contact with the eyes and skin.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

GB -



according to UK REACH

Revision: 25.04.2024

(Contd. of page 4)

Printing date 20.08.2024

Version number 5 (replaces version 4)

Trade name: Mipa P 118 Ultra PE-Leichtspachtel

· Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

General Information Physical state	Fluid
Colour:	According to product
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and	endetermined.
boiling range	145.2 °C (100-42-5 S
Flammability	Flammable.
Lower and upper explosion limit	r lammable.
Lower:	1.2 Vol % (100-42-5 \$
Upper:	8.9 Vol % (100-42-5 \$
Flash point:	31 °C (DIN EN ISO 1
Auto-ignition temperature:	480 °C (DIN 51794, 1
Decomposition temperature:	Not determined.
ЭН	Not determined.
/iscosity:	
Kinematic viscosity	Not determined.
Dynamic at 20 °C:	50,000-60,000 mPas
Solubility	
water:	Not miscible or difficu
Partition coefficient n-octanol/water (log	
value)	Not determined.
<i>Vapour pressure at 20 °C:</i>	6 hPa (100-42-5 Styr
<i>Vapour pressure at 50 °C:</i>	35 hPa
Density and/or relative density	
Density at 20 °C:	1.209 g/cm³ (DIN EN
Relative density	Not determined.

specification

Styrene)

Styrene) Styrene) 523:2002) 100-42-5 Styrene)

ult to mix.

rene)

ISO 2811-1)

(Contd. on page 6)

GB



according to UK REACH

Revision: 25.04.2024

Printing date 20.08.2024

Version number 5 (replaces version 4)

Trade name: Mipa P 118 Ultra PE-Leichtspachtel

	(Contd. of page 5	
· Vapour density	Not determined.	
9.2 Other information		
Appearance:		
Form:	Fluid	
 Important information on protection of heat 	alth	
and environment, and on safety.		
Ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product is not explosive. However, formation o	
	explosive air/vapour mixtures are possible.	
· Solvent content:		
· VOC (EC)	1.28 %	
· Solids content (weight-%):	82.9 %	
Change in condition		
Evaporation rate	Not determined.	
Information with regard to physical haz	ard	
classes		
[.] Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
[.] Oxidising gases	Void	
Gases under pressure	Void	
[.] Flammable liquids	Flammable liquid and vapour.	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• **10.3 Possibility of hazardous reactions** No dangerous reactions known.

• **10.4 Conditions to avoid** No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Causes serious eye irritation.

· Respiratory or skin sensitisation May cause an allergic skin reaction.

(Contd. on page 7)

GB

Professional Goating Systems

Printing date 20.08.2024

Safety data sheet

according to UK REACH Version number 5 (replaces version 4)

Revision: 25.04.2024

(Contd. of page 6)

Trade name: Mipa P 118 Ultra PE-Leichtspachtel

- · Reproductive toxicity Suspected of damaging the unborn child.
- · STOT-repeated exposure

Causes damage to the hearing organs through prolonged or repeated exposure.

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties
- For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

<i>14.1 UN number or ID number ADR, IMDG, IATA</i>	UN3269	
14.2 UN proper shipping name		
ADR	UN3269 POLYESTER RESIN KIT	
IMDG, IATA	POLYESTER RESIN KIT	
14.3 Transport hazard class(es)		
ADR		
Class	3 (F3) Flammable liquids.	



according to UK REACH

Revision: 25.04.2024

Printing date 20.08.2024

Version number 5 (replaces version 4)

Trade name: Mipa P 118 Ultra PE-Leichtspachtel

	(Contd. of page
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemle	
EMS Number:	F-E,S-D
Stowage Category	A
14.7 Maritime transport in bulk acco	
IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	5L
UN "Model Regulation":	UN 3269 POLYESTER RESIN KIT, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated	explosives	precursors
-------------	------------	------------

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

 \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 9)

GB



Printing date 20.08.2024

Safety data sheet

according to UK REACH Version number 5 (replaces version 4)

Revision: 25.04.2024

Trade name: Mipa P 118 Ultra PE-Leichtspachtel

(Contd. of page 8)

• National regulations:

· Additional classification according to Decree on Hazardous Materials, Annex II:

Class Share in %

NK 10-25

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H361d Suspected of damaging the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.
- EUH071 Corrosive to the respiratory tract.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A Skin Sens. 1B: Skin sensitisation - Category 1B Repr. 2: Reproductive toxicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 * * Data compared to the previous version altered.