

according to UK REACH

Printing date 06.08.2024 Version number 15 (replaces version 14) Revision: 06.08.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: Mipa P 27 Crystal PE-Transparentspachtel
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Knife filler/ Surfacer
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49 8703 92 20 Fax.: +49 8703 92 21 00

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

· 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated

exposure.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

Aguatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

(Contd. on page 2)



according to UK REACH

Printing date 06.08.2024 Version number 15 (replaces version 14) Revision: 06.08.2024

Trade name: Mipa P 27 Crystal PE-Transparentspachtel

(Contd. of page 1)

· Hazard-determining components of labelling:

Stvrene

Maleic anhydride

Reaction mass of pentamethyl-piperidylsebacate

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H361d Suspected of damaging the unborn child.

H335 May cause respiratory irritation.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:			
CAS: 100-42-5 EINECS: 202-851-5 Reg.nr.: 01-2119457861-32	Styrene ♠ Flam. Liq. 3, H226; ♦ Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304; ♠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	25-50%	
CAS: 67-56-1 EINECS: 200-659-6	methanol	<2.5%	
CAS: 1065336-91-5 EC number: 915-687-0 Reg.nr.: 01-2119491304-40	Reaction mass of pentamethyl-piperidylsebacate Repr. 2, H361f; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317	≥0.25-<1%	
CAS: 108-31-6 EINECS: 203-571-6 Reg.nr.: 01-2119472428-31	Maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥0.001 %	<i>≥</i> 0.001-<0.1%	
		(Contd. on page 3	



according to UK REACH

Printing date 06.08.2024 Version number 15 (replaces version 14) Revision: 06.08.2024

Trade name: Mipa P 27 Crystal PE-Transparentspachtel

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

(Contd. on page 4)



according to UK REACH

Printing date 06.08.2024 Version number 15 (replaces version 14) Revision: 06.08.2024

Trade name: Mipa P 27 Crystal PE-Transparentspachtel

(Contd. of page 3)

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

100-42-5 Styrene			
WEL	Short-term value: 1080 mg/m³, 250 ppm Long-term value: 430 mg/m³, 100 ppm		
67-56	-1 methanol		
	Short-term value: 333 mg/m³, 250 ppm Long-term value: 266 mg/m³, 200 ppm Sk		
108-3	1-6 Maleic anhydride		
WEL	Short-term value: 3 mg/m³ Long-term value: 1 mg/m³		

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls

Sen

- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)



according to UK REACH

Printing date 06.08.2024 Version number 15 (replaces version 14) Revision: 06.08.2024

Trade name: Mipa P 27 Crystal PE-Transparentspachtel

(Contd. of page 4)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· **Physical state** Flui

• Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range 145.2 °C (100-42-5 Styrene)

Flammability Flammable.

Lower and upper explosion limit

 Lower:
 1.2 Vol % (100-42-5 Styrene)

 Upper:
 8.9 Vol % (100-42-5 Styrene)

 Flash point:
 31 °C (DIN EN ISO 1523:2002)

Auto-ignition temperature: 480 °C (DIN 51794, 100-42-5 Styrene)

Decomposition temperature: Not determined. PH Not determined.

Viscosity:
Kinematic viscosity
Dynamic at 20 °C:
Not determined.
30,000-35,000 mPas

Solubility

· water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log

value) Not determined.

· Vapour pressure at 20 °C: 6 hPa (100-42-5 Styrene)

Vapour pressure at 50 °C: 35 hPa

Density and/or relative density

Density at 20 °C: 1.13 g/cm³ (DIN EN ISO 2811-1)

Relative densityVapour densityNot determined.Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

• **Ignition temperature:** Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

(Contd. on page 6)



according to UK REACH

Printing date 06.08.2024 Version number 15 (replaces version 14) Revision: 06.08.2024

Trade name: Mipa P 27 Crystal PE-Transparentspachtel

(Contd. of page 5)

· Solvent content:

• VOC (EC) 2.66 % • Solids content (weight-%): 71.3 %

· Change in condition

· Evaporation rate Not determined.

Information with regard to physical hazard

classes

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure

Void
Void

· Flammable liquids Flammable liquid and vapour.

Flammable solids
Self-reactive substances and mixtures
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which emit flammable gases in contact with water
Oxidising liquids
Oxidising solids

Oxidising liquids
 Oxidising solids
 Organic peroxides
 Corrosive to metals
 Desensitised explosives

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

100-42-5	100-42-5 Styrene			
Oral	LD50	5,000 mg/kg (rat)		
Dermal	LD50	5,000 mg/kg (rat) >2,000 mg/kg (rat)		
Inhalative	LC50/4 h	11.8 mg/l (rat)		

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- Reproductive toxicity Suspected of damaging the unborn child.
- · STOT-single exposure May cause respiratory irritation.

(Contd. on page 7)



according to UK REACH

Printing date 06.08.2024 Version number 15 (replaces version 14) Revision: 06.08.2024

Trade name: Mipa P 27 Crystal PE-Transparentspachtel

(Contd. of page 6)

· STOT-repeated exposure

Causes damage to the hearing organs through prolonged or repeated exposure.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN3269

· 14.2 UN proper shipping name

· **ADR** UN3269 POLYESTER RESIN KIT

· IMDG, IATA POLYESTER RESIN KIT

· 14.3 Transport hazard class(es)

· ADR



· Class 3 (F3) Flammable liquids.

(Contd. on page 8)



according to UK REACH

Printing date 06.08.2024 Version number 15 (replaces version 14) Revision: 06.08.2024

Trade name: Mipa P 27 Crystal PE-Transparentspachtel

(Contd. of page 7) · Label 3 · IMDG, IATA 3 Flammable liquids. · Class ·Label · 14.4 Packing group · ADR, IMDG, IATA III· 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Flammable liquids. Hazard identification number (Kemler code): -· EMS Number: F-E,S-D · Stowage Category Α · 14.7 Maritime transport in bulk according to IMO instruments Not applicable. · Transport/Additional information: · Limited quantities (LQ) 5L · Transport category 3 · Tunnel restriction code Ε · IMDG · Limited quantities (LQ) 5L UN "Model Regulation": UN 3269 POLYESTER RESIN KIT, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 9)



according to UK REACH

Revision: 06.08.2024 Printing date 06.08.2024 Version number 15 (replaces version 14)

Trade name: Mipa P 27 Crystal PE-Transparentspachtel

(Contd. of page 8)

- National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
1	<2.5
NK	25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases			
Highly flammable liquid and vapour.			
Flammable liquid and vapour.			
Toxic if swallowed.			
Harmful if swallowed.			
May be fatal if swallowed and enters airways.			
Toxic in contact with skin.			
Causes severe skin burns and eye damage.			
Causes skin irritation.			
May cause an allergic skin reaction.			
Causes serious eye damage.			
Causes serious eye irritation.			
Toxic if inhaled.			
Harmful if inhaled.			
May cause allergy or asthma symptoms or breathing difficulties if inhaled.			
May cause respiratory irritation.			
Suspected of damaging the unborn child.			
Suspected of damaging fertility.			
Causes damage to organs.			
May cause damage to organs.			
Causes damage to organs through prolonged or repeated exposure.			
Very toxic to aquatic life.			

EUH071 Corrosive to the respiratory tract. · Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

H410

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

Very toxic to aquatic life with long lasting effects.

Harmful to aquatic life with long lasting effects.

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 3: Acute toxicity - Category 3 Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

(Contd. on page 10)



according to UK REACH

Revision: 06.08.2024 Printing date 06.08.2024 Version number 15 (replaces version 14)

Trade name: Mipa P 27 Crystal PE-Transparentspachtel

(Contd. of page 9)

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Repr. 2: Reproductive toxicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard — Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard — Category 3

* Data compared to the previous version altered.