

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 10 (replaces version 9)

Revision: 28.02.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

- · Trade name: Mipa P 67 S PE-Spritzfüller
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- No further relevant information available. • Application of the substance / the mixture Filler and surfacer
- **1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:**

 MIPA SE

 Am Oberen Moos 1

 D-84051 Essenbach

 Tel.: +49(0)8703-922-0

 Fax.: +49(0)8703-922-100

 e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

• 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

health hazard

Repr. 2H361d Suspected of damaging the unborn child.STOT RE 1H372Causes damage to the hearing organs through prolonged or repeated
exposure.



Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335	May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

- The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



· Signal word Danger

(Contd. on page 2)

GB



Safety data sheet

according to 1907/2006/EC, Article 31 Version number 10 (replaces version 9)

Revision: 28.02.2023

Trade name: Mipa P 67 S PE-Spritzfüller

(Contd. of page 1) · Hazard-determining components of labelling: Stvrene Hydrocarbons, C9, aromatics Reaction mass of pentamethyl-piperidyl sebacate Benzotriazole derivate Hazard statements H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H361d Suspected of damaging the unborn child. H335 May cause respiratory irritation. H372 Causes damage to the hearing organs through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects. Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition P210 sources. No smoking. P260 Do not breathe dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. · 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

CAS: 100-42-5	Styrene	25-50%
	♦ Flam. Liq. 3, H226; Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	
CAS: 141-78-6	Ethyl acetate	<2.5%
EINECS: 205-500-4 Reg.nr.: 01-2119475103-46	� Flam. Liq. 2, H225; ⟨) Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	
CAS: 64742-95-6	Hydrocarbons, C9, aromatics	1-<2.5%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	 ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H335- H336, EUH066 	
ELINCS: 400-830-7	Benzotriazole derivate	<i>≥</i> 0.25-<1%
Reg.nr.: 01-0000015075-76	🚸 Aquatic Chronic 2, H411; 🚸 Skin Sens. 1, H317	



Safety data sheet

according to 1907/2006/EC, Article 31 Version number 10 (replaces version 9)

Revision: 28.02.2023

Printing date 28.02.2023

Trade name: Mipa P 67 S PE-Spritzfüller

EQ www.haw.odf.coz.o. Departies were af newtowerthy divised with a head to be a final state of the second	age 2)
EC number: 915-687-0 Reaction mass of pentamethyl-piperidyl sebacate ≥0.1-<0.2	25%
Reg.nr.: 01-2119491304-40 🚯 Repr. 2, H361f; 🚯 Aquatic Acute 1, H400; Aquatic Chronic 1, H410; 🅎 Skin Sens. 1A, H317	
CAS: 136-52-7 Cobalt bis(2-ethylhexanoate) <0.1%	6
EINECS: 205-250-6 🚯 Repr. 1B, H360Fd; 🚯 Aquatic Acute 1, H400;	
EINECS: 205-250-6 Reg.nr.: 01-2119524678-29 Eye Irrit. 2, H319; Skin Sens. 1A, H317; Aquatic	
Čhronic 3, H412	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately rinse with water.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing: If symptoms persist consult doctor.

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

(Contd. on page 4)

— GB



Safety data sheet

according to 1907/2006/EC, Article 31 Version number 10 (replaces version 9)

Revision: 28.02.2023

(Contd. of page 3)

Trade name: Mipa P 67 S PE-Spritzfüller

See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:
- Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

100-42-5 Styrene

WEL Short-term value: 1080 mg/m³, 250 ppm Long-term value: 430 mg/m³, 100 ppm

141-78-6 Ethyl acetate

WEL Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm

136-52-7 Cobalt bis(2-ethylhexanoate)

WEL Long-term value: 0.1 mg/m³ as Co; Carc, Sen

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes. Avoid contact with the eyes and skin.

(Contd. on page 5)

BB -



Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 28.02.2023

Printing date 28.02.2023

Version number 10 (replaces version 9)

Trade name: Mipa P 67 S PE-Spritzfüller

(Contd. of page 4)

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties · General Information · Physical state Fluid · Colour: According to product specification · Odour: Characteristic · Odour threshold: Not determined. • Melting point/freezing point: Undetermined. · Boiling point or initial boiling point and boiling range 145.2 °C (100-42-5 Styrene) Highly flammable. · Flammability Lower and upper explosion limit 1.2 Vol % (100-42-5 Styrene) · Lower: · Upper: 8.9 Vol % (100-42-5 Styrene) · Flash point: 15 °C (DIN EN ISO 1523:2002) · Ignition temperature: 480 °C (DIN 51794, 100-42-5 Styrene) · Decomposition temperature: Not determined. · pH Not determined. · Viscosity: · Kinematic viscosity Not determined. · Dynamic at 20 °C: 10,000 mPas · Solubility Not miscible or difficult to mix. · water:

(Contd. on page 6)

GB



Safety data sheet according to 1907/2006/EC, Article 31

Revision: 28.02.2023

Printing date 28.02.2023

Version number 10 (replaces version 9)

Trade name:	Mipa P	67 S I	PE-Spritzfüller
-------------	--------	--------	-----------------

	(Contd. of page
Partition coefficient n-octanol/water (log	
value)	Not determined.
Vapour pressure at 20 °C:	6 hPa (100-42-5 Styrene)
Density and/or relative density	
Density at 20 °C:	1.109 g/cm³ (DIN EN ISO 2811-1)
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of hea	lth
and environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
Solvent content:	
VOC (EC)	3.20 %
Solids content (weight-%):	68.4 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical haza	ard
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Carbon monoxide

(Contd. on page 7)

GB



Safety data sheet

according to 1907/2006/EC, Article 31 Version number 10 (replaces version 9)

Revision: 28.02.2023

Trade name: Mipa P 67 S PE-Spritzfüller

(Contd. of page 6)

SECTION 11: Toxicological information

• **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008** • **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50	values rel	evant for classification:
100-42-5	Styrene	
Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	11.8 mg/l (rat)
Skin corre	osion/irrit	ation Causes skin irritation.
· Serious e	ye damag	e/irritation Causes serious eye irritation.
· Respirato	ry or skin	sensitisation May cause an allergic skin reaction.
· Reproduc	tive toxic	ity Suspected of damaging the unborn child.

- · STOT-single exposure May cause respiratory irritation.
- STOT-repeated exposure
- Causes damage to the hearing organs through prolonged or repeated exposure.
- 11.2 Information on other hazards
- Endocrine disrupting properties
- 128-37-0 Butylated hydroxytoluene

List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties
- For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

GB



Safety data sheet according to 1907/2006/EC, Article 31

Version number 10 (replaces version 9)

Revision: 28.02.2023

Trade name: Mipa P 67 S PE-Spritzfüller

(Contd. of page 7)

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number	
ADR, IMDG, IATA	UN3269
14.2 UN proper shipping name	
ADR	UN3269 POLYESTER RESIN KIT
IMDG, IATA	POLYESTER RESIN KIT
14.3 Transport hazard class(es)	
ADR	
Class Label	3 (F3) Flammable liquids. 3
IMDG, IATA	
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR, IMDG, IATA	11
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	
	F-E,S-D
Stowage Category	В
<i>14.7 Maritime transport in bulk according to IMO instruments</i>	Not applicable.
Transport/Additional information:	
ADR	
	5L
Transport category	2
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	5L
UN "Model Regulation":	UN 3269 POLYESTER RESIN KIT, 3, II

(Contd. on page 9)



Safety data sheet

according to 1907/2006/EC, Article 31 Version number 10 (replaces version 9)

Revision: 28.02.2023

(Contd. of page 8)

Trade name: Mipa P 67 S PE-Spritzfüller

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations:

Additional classification according to Decree on Hazardous Materials, Annex II:

Class Share in %

NK 25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H360Fd May damage fertility. Suspected of damaging the unborn child.
- H361d Suspected of damaging the unborn child.
- H361f Suspected of damaging fertility.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

- EINECS: European Inventory of Existing Commercial Ch ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3



Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 28.02.2023

Printing date 28.02.2023

Version number 10 (replaces version 9)

Trade name: Mipa P 67 S PE-Spritzfüller

(Contd. of page 9) Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1: Skin sensitisation – Category 1 Repr. 1B: Reproductive toxicity – Category 1B Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 * *** Data compared to the previous version altered**.