

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Mipa P 80 PE-Kaltmetall**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Knife filler/ Surfacer
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MIPA SE
Am Oberen Moos 1
D-84051 Essenbach
Tel.: +49 8703 92 20
Fax.: +49 8703 92 21 00
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com
- **1.4 Emergency telephone number:** International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

(Contd. on page 2)

GB

Trade name: Mipa P 80 PE-Kaltmetall

(Contd. of page 1)

Hazard-determining components of labelling:

Styrene

Maleic anhydride

2,2'-(m-Tolylimino)diethanol

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl] (4-methylphenyl)amino]-

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H361d Suspected of damaging the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P235 Store in a well-ventilated place. Keep cool.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 100-42-5 EINECS: 202-851-5 Reg.nr.: 01-2119457861-32	Styrene ⚠ Flam. Liq. 3, H226; ⚠ Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	≥10-≤20%
CAS: 7429-90-5 EINECS: 231-072-3 Reg.nr.: 01-2119529243-45	aluminium powder (stabilized)/ manufacturer classification ⚠ Flam. Sol. 1, H228	2.5-<10%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336, EUH066	1-<2.5%

(Contd. on page 3)

Safety data sheet

according to UK REACH

Printing date 31.10.2024

Version number 62 (replaces version 61)

Revision: 22.08.2024

Trade name: Mipa P 80 PE-Kaltmetall

CAS: 91-99-6 EINECS: 202-114-8	2,2'-(m-Tolylimino)diethanol STOT RE 2, H373; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1B, H317	(Contd. of page 2) ≥0.1-<1%
EC number: 911-490-9	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]- Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<1%
CAS: 108-31-6 EINECS: 203-571-6 Reg.nr.: 01-2119472428-31	Maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥0.001 %	≥0.001-<0.1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately rinse with water.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters

Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 4)

Safety data sheet

according to UK REACH

Printing date 31.10.2024

Version number 62 (replaces version 61)

Revision: 22.08.2024

Trade name: Mipa P 80 PE-Kaltmetall

(Contd. of page 3)

Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** No special requirements.

· **Information about storage in one common storage facility:** Store away from foodstuffs.

· **Further information about storage conditions:** Keep container tightly sealed.

· **Storage class:** 3

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

100-42-5 Styrene

WEL Short-term value: 1080 mg/m³, 250 ppm

Long-term value: 430 mg/m³, 100 ppm

7429-90-5 aluminium powder (stabilized)/ manufacturer classification

WEL Long-term value: 10* 4** mg/m³

*inhalable dust **respirable dust

108-31-6 Maleic anhydride

WEL Short-term value: 3 mg/m³

Long-term value: 1 mg/m³

Sen

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

(Contd. on page 5)

Trade name: Mipa P 80 PE-Kaltmetall

(Contd. of page 4)

Avoid contact with the eyes and skin.

Respiratory protection:

Filter A/P2 (EN 141, EN 143)



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Fluorocarbon rubber (Viton)

Recommended thickness of the material: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

Value for the permeation: Level ≤ 6

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state

Fluid

Colour:

According to product specification

Odour:

Characteristic

Odour threshold:

Not determined.

Melting point/freezing point:

Undetermined.

Boiling point or initial boiling point and boiling range

145.2 °C (100-42-5 Styrene)

Flammability

Flammable.

Lower and upper explosion limit

Lower:

1.2 Vol % (100-42-5 Styrene)

Upper:

8.9 Vol % (100-42-5 Styrene)

Flash point:

34 °C (DIN 53213)

Auto-ignition temperature:

480 °C (DIN 51794, 100-42-5 Styrene)

Decomposition temperature:

Not determined.

pH

Not determined.

(Contd. on page 6)

Safety data sheet

according to UK REACH

Printing date 31.10.2024

Version number 62 (replaces version 61)

Revision: 22.08.2024

Trade name: Mipa P 80 PE-Kaltmetall

(Contd. of page 5)

· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic at 20 °C:	90,000-100,000 mPas
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	6 hPa (100-42-5 Styrene)
· Vapour pressure at 50 °C:	35 hPa
· Density and/or relative density	
· Density at 20 °C:	1.53 g/cm ³ (DIN 53217)
· Relative density	Not determined.
· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· VOC (EC)	2.57 %
· Solids content (weight-%):	81.6 %
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.

(Contd. on page 7)

Safety data sheet

according to UK REACH

Printing date 31.10.2024

Version number 62 (replaces version 61)

Revision: 22.08.2024

Trade name: Mipa P 80 PE-Kaltmetall

(Contd. of page 6)

- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Reproductive toxicity** Suspected of damaging the unborn child.
- **STOT-repeated exposure**
Causes damage to the hearing organs through prolonged or repeated exposure.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) : hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information



- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN3269

(Contd. on page 8)

GB

Trade name: Mipa P 80 PE-Kaltmetall

(Contd. of page 7)

<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG, IATA 		UN3269 POLYESTER RESIN KIT POLYESTER RESIN KIT
<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR 		
		
<ul style="list-style-type: none"> · Class · Label 		3 (F3) Flammable liquids. 3
<ul style="list-style-type: none"> · IMDG, IATA 		
		
<ul style="list-style-type: none"> · Class · Label 		3 Flammable liquids. 3
<ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA 		III
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: 		No
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category 		Warning: Flammable liquids. - F-E,S-D A
<ul style="list-style-type: none"> · 14.7 Maritime transport in bulk according to IMO instruments 		Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: 		
<ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Transport category · Tunnel restriction code 		5L 3 E
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) 		5L
<ul style="list-style-type: none"> · UN "Model Regulation": 		UN 3269 POLYESTER RESIN KIT, 3, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**
- **Regulated explosives precursors**
None of the ingredients is listed.
- **Regulated poisons**
None of the ingredients is listed.

(Contd. on page 9)

Safety data sheet

according to UK REACH

Printing date 31.10.2024

Version number 62 (replaces version 61)

Revision: 22.08.2024

Trade name: Mipa P 80 PE-Kaltmetall

(Contd. of page 8)

· **Reportable explosives precursors**

7429-90-5 aluminium powder (stabilized)/ manufacturer classification

Listed

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category P5c** FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials, Annex II:**

Class	Share in %
NK	10-25

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226 Flammable liquid and vapour.

H228 Flammable solid.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH071 Corrosive to the respiratory tract.

· **Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 10)

Safety data sheet

according to UK REACH

Printing date 31.10.2024

Version number 62 (replaces version 61)

Revision: 22.08.2024

Trade name: Mipa P 80 PE-Kaltmetall

(Contd. of page 9)

VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Flam. Sol. 1: Flammable solids – Category 1
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Skin Sens. 1B: Skin sensitisation – Category 1B
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
* **Data compared to the previous version altered.**

GB