

Safety data sheet

according to UK REACH Version number 6 (replaces version 5)

Revision: 05.11.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

- · Trade name: Mipa Quick-Primer-Spray
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- No further relevant information available.
- · Application of the substance / the mixture Priming
- · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: MIPA SE Am Oberen Moos 1
- D-84051 Essenbach Tel.: +49 8703 92 20 Fax.: +49 8703 92 21 00 e-mail: sdb-registratur@mipa-paints.com www.mipa-paints.com
- 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



Aerosol 1	H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H336	May cause drowsiness or dizziness.
Aquatic Chronic	3 H412	Harmful to aquatic life with long lasting effects.

Aquatic Chronic 3 H412

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation. • Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling: Acetone Maleic anhydride Hydrocarbons, C9, aromatics 1-methoxy-2-propanol Hazard statements H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. H319 Causes serious eye irritation.

⁽Contd. on page 2)



Safety data sheet according to UK REACH

according to UK REACH Version number 6 (replaces version 5)

Revision: 05.11.2024

Printing date 05.11.2024

Trade name: Mipa Quick-Primer-Spray

	(Contd. of page 1)
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
· Precaution	ary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P305+P351	+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/
	international regulations.
· Additional	information:
EUH066 Re	epeated exposure may cause skin dryness or cracking.
Buildup of e	explosive mixtures possible without sufficient ventilation.
EUH205 Co	ontains epoxy constituents. May produce an allergic reaction.
· 2.3 Other h	
D	

Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

 Dangerous components: 		
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37	Dimethyl ether أن Flam. Gas 1A, H220; Press. Gas (Liq.), H280	25-50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	Acetone	25-50%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H335- H336, EUH066	5-<10%
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35	1-methoxy-2-propanol	2.5-<10%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate Flam. Liq. 3, H226;	2.5-<5%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene ♦ Flam. Liq. 3, H226; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1-<2.5%
CAS: 7779-90-0 EINECS: 231-944-3 Reg.nr.: 01-2119485044-40	Trizinc bis(orthophosphate) � Aquatic Acute 1, H400; Aquatic Chronic 1, H410	<i>≥</i> 0.25-<2.5%



Safety data sheet

according to UK REACH

Revision: 05.11.2024

Printing date 05.11.2024

Version number 6 (replaces version 5)

Trade name: Mipa Quick-Primer-Spray

CAS: 85711-46-2 Fatty acids, C14-18 and C16-18-unsatd., maleated ≥0.1-<1%
EINECS: 288-306-2 () Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. Reg.nr.: 01-2119976378-19 1B, H317
CAS: 162627-17-0 Fatty acids,C18-unsatd., dimers, reaction products ≥0.1-<1%
EC number: 605-296-0 with N,N-dimethyl-1,3-propanediamine and1,3-
Reg.nr.: 01-2119970640-38 propanediamine
Skin Sens. 1A, H317
CAS: 108-31-6 <i>Maleic anhydride</i> ≥0.001-<0.1%
EINECS: 203-571-6 🚯 Resp. Sens. 1, H334; STOT RE 1, H372; 🔶 Skin
Reg.nr.: 01-2119472428-31 Corr. 1B, H314; Eye Dam. 1, H318; (1) Acute Tox. 4,
H302; Skin Sens. 1A, H317, EUH071
Specific concentration limit:
Skin Sens. 1A; H317: $C \ge 0.001 \%$

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. · After swallowing: If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device. Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to section 13.

(Contd. on page 4)

GB

Professional Coating Systems

Printing date 05.11.2024

Safety data sheet according to UK REACH

Version number 6 (replaces version 5)

Revision: 05.11.2024

Trade name: Mipa Quick-Primer-Spray

(Contd. of page 3)

Ensure adequate ventilation.

- 6.4 Reference to other sections See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

• **7.1 Precautions for safe handling** Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection: Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

115-10-6 Dimethyl etherWELShort-term value: 958 mg/m³, 500 ppmLong-term value: 766 mg/m³, 400 ppm

67-64-1 Acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

107-98-2 1-methoxy-2-propanol WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk

123-86-4 n-Butyl acetateWELShort-term value: 966 mg/m³, 200 ppmLong-term value: 724 mg/m³, 150 ppm

1330-20-7 Xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

108-31-6 Maleic anhydride

WEL Short-term value: 3 mg/m³ Long-term value: 1 mg/m³ Sen

(Contd. on page 5)

[—] GB



Safety data sheet

according to UK REACH Version number 6 (replaces version 5)

Revision: 05.11.2024

Trade name: Mipa Quick-Primer-Spray

(Contd. of page 4) Ingredients with biological limit values: 1330-20-7 Xylene BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid • Additional information: The lists valid during the making were used as basis. · 8.2 Exposure controls · Appropriate engineering controls No further data; see section 7. · Individual protection measures, such as personal protective equipment · General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection

Safety glasses



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- [.] 9.1 Information on basic physical and chemical properties
- · General Information
- · Physical state
- · Colour:
- · Odour:

Aerosol According to product specification Characteristic

(Contd. on page 6)

GB



Safety data sheet according to UK REACH

according to UK REACH Version number 6 (replaces version 5)

Revision: 05.11.2024

Trade name: Mipa Quick-Primer-Spray

	(Contd. of page 5
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and	
boiling range	-24.9 °C
Flammability	Not applicable.
Lower and upper explosion limit	
· Lower:	2.6 Vol % (67-64-1 Acetone)
Upper:	18.6 Vol % (115-10-6 Dimethyl ether)
Flash point:	<0 °C (DIN EN ISO 1523:2002)
Auto-ignition temperature:	235 °C (DIN 51794, 115-10-6 Dimethyl ether)
Decomposition temperature:	Not determined.
рН	Not determined.
Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
Solubility	Not determined.
· water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log	
value)	Not determined.
· Vapour pressure at 20 °C:	5,200 hPa (115-10-6 Dimethyl ether)
	5,200 IIPa (115-10-0 Dimetry ether)
Density and/or relative density	0.906 m/om3 (DIN EN ISO 2011 1)
Density at 20 °C:	0.806 g/cm ³ (DIN EN ISO 2811-1)
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
 Form: Important information on protection of hea and environment, and on safety. 	Aerosol alth
Ignition temperature:	Product is not selfigniting.
Explosive properties:	In use, may form flammable/explosive vapour-ai
	mixture.
· Solvent content:	
· VOC (EC)	86.38 %
· Solids content (weight-%):	13.6 %
Change in condition	
· Evaporation rate	Not applicable.
Information with regard to physical haza	
classes	ar 9a
· Explosives	Void
Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised
	container: May burst if heated.
[.] Oxidising gases	Void
[.] Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
	Void
tlammable dases in contact with water	
flammable gases in contact with water Oxidising liquids	Void



Safety data sheet

according to UK REACH

Revision: 05.11.2024

Printing date 05.11.2024

Version number 6 (replaces version 5)

Trade name: Mipa Quick-Primer-Spray

		(Contd. of page 6)
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
 Desensitised explosives 	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- · 10.6 Hazardous decomposition products:

Possible in traces. Nitrogen oxides Hydrogen chloride (HCI) Carbon monoxide

Nitrogen oxides (NOx)

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

Primary irritant effect:

· Serious eye damage/irritation Causes serious eye irritation.

• Respiratory or skin sensitisation May cause an allergic skin reaction.

• **STOT-single exposure** May cause drowsiness or dizziness.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

- **12.2 Persistence and degradability** No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.

• 12.4 Mobility in soil No further relevant information available.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

(Contd. on page 8)



Safety data sheet

according to UK REACH

Version number 6 (replaces version 5)

Revision: 05.11.2024

Trade name: Mipa Quick-Primer-Spray

(Contd. of page 7)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN number or ID number	
ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	UN1950 AEROSOLS
IMDG	AEROSOLS
ΙΑΤΑ	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
2	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
A	
Class	2.1 Gases.
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler co	
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capa
	of 1 litre: Category A. For AEROSOLS with capacity above 1 litre: Category B. For WAS
	AEROSOLS: Category C, Clear of living quarter
Segregation Code	SG69 For AEROSOLS with a maximum capa
	of 1 litre:
	Segregation as for class 9. Stow "separated fro
	class 1 except for division 1.4.
	For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision o



Safety data sheet

according to UK REACH

Revision: 05.11.2024

Printing date 05.11.2024

Version number 6 (replaces version 5)

Trade name: Mipa Quick-Primer-Spray

	(Contd. of page
	class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision o class 2.
 14.7 Maritime transport in bulk accor IMO instruments 	rding to Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
Transport category	2
Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poisons Act

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

67-64-1 Acetone

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- Additional classification according to Decree on Hazardous Materials, Annex II:

Class Share in %

NK 50-100

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

[.] Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.

(Contd. on page 10)

Listed

GB

Professional Coating Systems

Safety data sheet

according to UK REACH Version number 6 (replaces version 5)

Revision: 05.11.2024

Printing date 05.11.2024

Trade name: Mipa Quick-Primer-Spray

(Contd. of page 9) H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H372 Causes damage to organs through prolonged or repeated exposure. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. EUH071 Corrosive to the respiratory tract. Classification according to Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols – Category 1 Press. Gas (Liq.): Gases under pressure – Liquefied gas Flam. Liq. 2: Flammable liquids – Category 2 Flam. Lig. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation – Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A Skin Sens. 1B: Skin sensitisation – Category 1B STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 * * Data compared to the previous version altered.

