

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 36 (replaces version 35)

Revision: 14.03.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: Mipa Stabilisier-Verdünnung
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Thinner, Diluent
- **1.3 Details of the supplier of the safety data sheet** • **Manufacturer/Supplier:** MIPA SE Am Oberen Moos 1 D-84051 Essenbach Tel.: +49 8703 92 20 Fax.: +49 8703 92 21 00 e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

• 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- · Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labelling:
- n-Butyl acetate
- · Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

- Precautionary statements
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

(Contd. on page 2)



Safety data sheet

according to 1907/2006/EC, Article 31 Version number 36 (replaces version 35)

Revision: 14.03.2024

Trade name: Mipa Stabilisier-Verdünnung

(Contd. of page 1) P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell.

• Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

[.] Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

• Dangerous components: CAS: 123-86-4 EINECS: 204-658-1

Reg.nr.: 01-2119485493-29

n-Butyl acetate 🚸 Flam. Liq. 3, H226; ᡧ STOT SE 3, H336, EUH066 ____ 50-100%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.03.2024

Professional Coating Systems

Version number 36 (replaces version 35)

Revision: 14.03.2024

Trade name: Mipa Stabilisier-Verdünnung

· 6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Use only in well ventilated areas. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- *Information about fire and explosion protection:* Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls No further data; see section 7.

- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.

• Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• Hand protection

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. of page 2)



Safety data sheet

according to 1907/2006/EC, Article 31 Version number 36 (replaces version 35)

Revision: 14.03.2024

Trade name: Mipa Stabilisier-Verdünnung

(Contd. of page 3)

• *Material of gloves* The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Breakthrough time of glove material** The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and cher	nical properties
· General Information	
Physical state	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
 Melting point/freezing point: 	Undetermined.
 Boiling point or initial boiling point and 	
boiling range	124-128 °C (123-86-4 n-Butyl acetate)
· Flammability	Flammable
· Lower and upper explosion limit	
· Lower:	1.2 Vol % (123-86-4 n-Butyl acetate)
· Upper:	7.5 Vol % (123-86-4 n-Butyl acetate)
· Flash point:	23 °C (DIN 53213, 123-86-4 n-Butyl acetate)
• Auto-ignition temperature:	370 °C (DIN 51794, 123-86-4 n-Butyl acetate)
Decomposition temperature:	Not determined.
·pH ·	Not determined.
· Viscosity:	
 Kinematic viscosity at 20 °C 	10-20 s (DIN 53211/4)
· Dynamic:	Not determined.
Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log	
value)	Not determined.
· Vapour pressure at 20 °C:	10.7 hPa (123-86-4 n-Butyl acetate)
· Vapour pressure at 50 °C:	55 hPa
· Density and/or relative density	
· Density at 20 °C:	0.883 g/cm³ (DIN 53217)
· Relative density	Not determined.
· Vapour density	Not determined.
9.2 Other information	
Appearance:	
· Form:	Fluid
Important information on protection of hea	iith
and environment, and on safety.	Draduat is not colfignities
Ignition temperature:	Product is not selfigniting.
• Explosive properties:	Product is not explosive. However, formation
	explosive air/vapour mixtures are possible.
	(Contd. on page

(Contd. on page 5)

of

GB



Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 14.03.2024

Printing date 14.03.2024

03.2024 Version number 36 (replaces version 35)

Trade name: Mipa	Stabilisier-Verdünnung
------------------	------------------------

	(Cor	ntd. of page
Solvent content:		
VOC (EC)	98.23 %	
Solids content (weight-%):	1.8 %	
Change in condition		
Evaporation rate	Not determined.	
Information with regard to physical haz	ard	
classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Flammable liquid and vapour.	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

• **10.6 Hazardous decomposition products:** Carbon monoxide

SECTION 11: Toxicological information

• 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

123-86-4 n-Butyl acetate

Oral LD50 13,100 mg/kg (rat)

Dermal LD50 >5,000 mg/kg (rabbit)

STOT-single exposure May cause drowsiness or dizziness.

11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

(Contd. on page 6)

GE



Safety data sheet

according to 1907/2006/EC, Article 31 Version number 36 (replaces version 35)

Revision: 14.03.2024

Trade name: Mipa Stabilisier-Verdünnung

(Contd. of page 5)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.

• **vPvB:** Not applicable.

· 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.


SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.





Safety data sheet

according to 1907/2006/EC, Article 31 Version number 36 (replaces version 35)

Revision: 14.03.2024

Trade name: Mipa Stabilisier-Verdünnung

	(Contd. of
Label	3
14.4 Packing group	
ADR, IMDG, IATA	<i>III</i>
14.5 Environmental hazards:	
Marine pollutant:	No
4.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	F-E, <u>S-E</u>
towage Category	A
14.7 Maritime transport in bulk according to	
MO instruments	Not applicable.
Fransport/Additional information:	
4 <i>DR</i>	
imited quantities (LQ)	5L
Fransport category	3
Tunnel restriction code	D/E
MDG	
Limited quantities (LQ)	5L
JN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Poisons Act
- · Regulated explosives precursors
- None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations:

• Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	50-100

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 8)

GB



Safety data sheet according to 1907/2006/EC, Article 31

according to 1907/2006/EC, Article 31 Version number 36 (replaces version 35)

Revision: 14.03.2024

Trade name: Mipa Stabilisier-Verdünnung

(Contd. of page 7)

	TION 16: Other information
	formation is based on our present knowledge. However, this shall not constitute a guarante specific product features and shall not establish a legally valid contractual relationship.
Releva	ant phrases
	Flammable liquid and vapour.
	May cause drowsiness or dizziness.
	66 Repeated exposure may cause skin dryness or cracking.
	fication according to Regulation (EC) No 1272/2008
accord	assification of the mixture is generally based on the calculation method using substance da ling to Regulation (EC) No 1272/2008.
Abbre	viations and acronyms:
	glement international concernant le transport des marchandises dangereuses par chemin de fer (Regulatio
	ing the International Transport of Dangerous Goods by Rail)
	nternational Civil Aviation Organisation
	ccord relatif au transport international des marchandises dangereuses par route (European Agreement Concerni national Carriage of Dangerous Goods by Road)
	nternational Maritime Code for Dangerous Goods
	ternational Air Transport Association
	lobally Harmonised System of Classification and Labelling of Chemicals
	: European Inventory of Existing Commercial Chemical Substances
ELINCS	: European List of Notified Chemical Substances
	nemical Abstracts Service (division of the American Chemical Society)
	platile Organic Compounds (USA, EU)
	ethal concentration, 50 percent
	ethal dose, 50 percent prsistent, Bioaccumulative and Toxic
	ery Persistent and very Bioaccumulative
	g. 3: Flammable liquids – Category 3
	E 3: Specific target organ toxicity (single exposure) – Category 3
	compared to the previous version altered.